



**SKU:** LO-350-S

**UPC:** 0783669570700

**Features & Benefits:**

**Description:** Copper Mechanical Lug, Conductor Range 350-4, 1 Port, 2 Holes, 3/8in Bolt Size, 1-1/16in Hole Spacing, Seamless, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	2
Number of Poles	1
Number of Ports / Wireways	1

### Dimensions

Dimension G (IN)	0.375
Drive Size Main	3/8
Drive Type Main	Internal Hex
Height (IN)	1.043
Height BX (IN)	2
Height (mm)	26.4922
Length (IN)	3.94
Length (mm)	100.076
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.438
Mounting Hole Diameter (mm)	11.1252
Mounting Hole Spacing (IN)	1.063
Mounting Hole Spacing (mm)	27.0002
Tang Length (IN)	2
Tang Length (mm)	50.8
Tang Thickness (IN)	0.25
Tang Thickness (mm)	6.35
Tang Width (IN)	1.125
Tang Width (mm)	28.575
Weight (LB)	0.411
Weight BX (LB)	7.5541
Width (IN)	1.125
Width BX (IN)	6.1875
Width (mm)	28.575

### Material and Finish

Conductor Material	Copper
Connector Finish	NA

Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Bright Dip
Wire Binding Hardware Material	Brass

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1-1/16
Wire Binding Torque	375

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 18
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366957070

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Copper
-------	--------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 4 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA



**Wire Combinations**

NA

**Voltage**

**Voltage Rating**

35 kV