



SKU: LO-350SH

UPC: 0783669570977

Features & Benefits:

Description: Copper Mechanical Lug, Conductor Range 350-4, 1 Port, 1 Hole, 1/2in Bolt Size, Seamless, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Dimension G (IN)	0.5
Drive Size Main	3/8
Drive Type Main	Internal Hex
Height (IN)	1.186
Height BX (IN)	2
Height (mm)	30.1244
Length (IN)	2.219
Length (mm)	56.3626
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.531
Mounting Hole Diameter (mm)	13.4874
Mounting Hole Spacing (mm)	0
Tang Length (IN)	1
Tang Length (mm)	25.4
Tang Thickness (IN)	0.135
Tang Thickness (mm)	3.429
Tang Width (IN)	1.125
Tang Width (mm)	28.575
Weight (LB)	0.276
Weight BX (LB)	5.1203
Width (IN)	1.125
Width BX (IN)	6.1875
Width (mm)	28.575

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA

Material	Copper
Wire Binding Hardware Finish	Bright Dip
Wire Binding Hardware Material	Brass

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	13/16
Wire Binding Torque	275

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 18
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366957097

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 4 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Wire Combinations	NA

Voltage

Voltage Rating

35 kV