



SKU: LO-4

UPC: 0783669953923

Features & Benefits:

Description: Copper Mechanical Lug, Conductor Range 4-14, 1 Port, 1 Hole, 1/4in Bolt Size, Seamless, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Dimension G (IN)	0.281
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.473
Height BX (IN)	2.25
Height (mm)	12.0142
Length (IN)	1.375
Length (mm)	34.925
Mounting Hole Diameter (IN)	0.266
Mounting Hole Diameter (mm)	6.7564
Mounting Hole Spacing (mm)	0
Tang Length (IN)	0.625
Tang Length (mm)	15.875
Tang Thickness (IN)	0.122
Tang Thickness (mm)	3.0988
Tang Width (IN)	0.5
Tang Width (mm)	12.7
Weight (LB)	0.032
Weight BX (LB)	4.18
Width (IN)	0.5
Width BX (IN)	5
Width (mm)	12.7

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper

Wire Binding Hardware Finish
Wire Binding Hardware Material

Zinc Clear Trivalent Chromate
Steel

Additional Technical Specifications

Conductor Type Solid

Bolt and Screw Sizes

Mounting Bolt/Stud Size 1/4
Number of Wire Binding Screws per Port 1
Wire Binding Screw Size 7/16
Wire Binding Torque 2 AWG = 40

General

Bag Quantity 1
Carton Quantity Description STD PACK QTY 100
Direct Burial No
Dual Rated No
NEMA Code S-588-3
UPC Code 78366995392

Testing Standards

CSA File Number LR-29601
CSA Standard C22.2 No. 65-03
Prop65 Compliance This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number 453G
UL / CULUS Specification UL 486A/B Listed
UL File Number E6207

Environment and Temperature

Temperature Rating 90°C

Color

Color Copper

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load) NA
Conductor Range AL Stranded (Primary, run, main, line) NA
Conductor Range AL Stranded (Secondary, tap, load) NA
Conductor Range CU Solid (Primary, run, main, line) 10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load) NA
Conductor Range CU Stranded (Primary, run, main, line) 4 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load) NA
Conductor Range AL Solid (Primary, run, main, line) NA
Wire Combinations NA

Voltage

Voltage Rating

35 kV