



SKU: LSN-025NE

UPC: 0783669993301

Features & Benefits:

Description: Permagraund Copper Eye-Bolt Terminal, Conductor Range 250-6 Sol, 1/4-3/4in Mounting Surface

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Wire Orientation	Parallel

Dimensions

Drive Size Main	3/4
Drive Type Main	External Hex
Height (IN)	3.063
Height BX (IN)	6.5
Length (IN)	1.25
Weight (LB)	1
Weight BX (LB)	101
Width (IN)	1.063
Width BX (IN)	12.75

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper/Aluminum Bronze Alloy

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Clamping Bolt Size	1/2
Number of Wire Binding Screws per Port	0
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	No
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366999330

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Color

Color	Copper
--------------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	4/0 Sol - 6 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA