



SKU: MU-350

UPC: 0783669682984

Features & Benefits:

Description: Copper Mechanical Lug, Conductor Range 350-1/0, 2 Ports, 1 Hole, 1/2in Bolt Size, UL, CSA

Specs

Additional Class Attributes

Collar Style	Round
Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	2
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	2

Dimensions

Dimension G (IN)	0.875
Dimension G (mm)	22.225
Drive Size Main	3/8
Drive Type Main	Internal Hex
Height (IN)	1.125
Height BX (IN)	2.25
Height (mm)	28.575
Length (IN)	3.313
Length (mm)	84.1502
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.563
Mounting Hole Diameter (mm)	14.3002
Tang Length (IN)	1.813
Tang Length (mm)	46.0502
Tang Thickness (IN)	0.344
Tang Thickness (mm)	8.7376
Tang Width (IN)	1.746
Tang Width (mm)	44.3484
Weight (LB)	0.783
Weight BX (LB)	5.6022
Width (IN)	1.874
Width BX (IN)	5
Width (mm)	47.5996

Material and Finish

Conductor Material	Copper
Connector Finish	NA

Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Bright Dip
Wire Binding Hardware Material	Brass

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	13/16
Wire Binding Torque	375

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366968298

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 1/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Wire Combinations	NA

Voltage

Voltage Rating

35 kV