



**SKU:** NBAS-012-2-A

**UPC:** 0783669005615

**Features & Benefits:**

**Description:** Aluminum Neutral Bar, Dual Rated, Conductor Range 4-14, 12 Ports, 2 Holes, #10 Bolt, Headed Slot Drive, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	Thru
Number of Conductors	12
Number of Mounting Holes	2
Number of Poles	1
Number of Ports / Wireways	14
Number of Usable Ports	12
Type of Accessory	NBST-2/0

### Dimensions

Dimension G (IN)	1.116
Dimension G (mm)	28.3464
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.547
Height BX (IN)	1.9
Length (IN)	4.416
Mounting Bolt/Stud Size (mm)	254
Mounting Hole Diameter (IN)	0.203
Mounting Hole Position (IN)	4 & 11
Mounting Hole Spacing (IN)	2.184
Mounting Hole Spacing (mm)	55.4736
Weight (LB)	0.102
Weight BX (LB)	2.135
Width (IN)	0.312
Width BX (IN)	4

### Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Zinc Clear Trivalent Chromate
Wire Binding Hardware Material	Steel

## Additional Technical Specifications

Conductor Type	Solid
----------------	-------

## Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/4
Wire Binding Torque	10 - 18 AWG = 20

## General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 20
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366900561

## Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	NA
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

## Color

Color	Silver
-------	--------

## Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	4 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol

## Voltage

Voltage Rating	35 kV
----------------	-------