



SKU: PBTD-10-1/0

UPC: 0783669077520

Features & Benefits:

Description: Nimbus Insulated Aluminum Multi-Tap Connector, Conductor Range 1/0-14, 10 Ports, Dual Sided Entry, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	10
Number of Poles	1
Number of Ports / Wireways	10
Number of Usable Ports	10
Replacement Part(s)	PORTPLUG-1/0, SCREWCAP-1/0

Dimensions

Drive Size Main	3/16
Drive Type Main	Internal Hex
Height (IN)	1.627
Height BX (IN)	3.625
Height (mm)	41.3258
Length (IN)	6.623
Length (mm)	168.2242
Max Insulation OD (IN)	0.511
Max Insulation OD (mm)	12.9794
Weight (LB)	0.693
Weight BX (LB)	3.026
Width (IN)	1.825
Width BX (IN)	6.375
Width (mm)	46.355

Material and Finish

Connector Finish	Tin
Insulation	Plastisol
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	3/8
Wire Binding Torque	10 - 14 AWG = 35

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 4
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366907752

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol
Flex Conductor Range	NA

Color

Color	Black
-------	-------

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Environmental Conditions	Cold temperature rated to -45°C
Flammability Rating	Insulation rated per UL 94
Temperature Rating	90°C