



SKU: PDB-26-750-1

UPC: 0783669711448

Features & Benefits:

Description: Power Distribution Block, Lay-In, Dual Rated, Line Conductor Range 750-250, Load Range 250-6, 2 Ports Per Pole Line Side, 6 Ports Per Pole Load Side, 1 Pole, UL, CSA, Includes Cover

Specs

Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	Thru
Number of Conductors	8
Number of Poles	1
Number of Ports Per Pole Primary	2
Number of Ports Per Pole Secondary	6

Dimensions

Drive Size Main	3/8
Drive Size Tap	1/4
Drive Type Main	Internal Hex
Drive Type Tap	Internal Hex
Height (IN)	4.947
Height BX (IN)	4.75
Height (mm)	125.6538
Length (IN)	4.014
Length (mm)	101.9556
Mounting Hole Diameter (IN)	0.281
Mounting Hole Spacing (IN)	3
Mounting Hole Spacing (mm)	76.2
Weight (LB)	2.953
Weight BX (LB)	3.3944
Width (IN)	5.959
Width BX (IN)	5
Width (mm)	151.3586

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Enclosure Material	Valox
Insulation Material	NA
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	13/16
Wire Binding Torque	375

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366971144

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
RUS Listed	No
UL Control Number	NA
UL / CULUS Specification	UL 1059 Recognized
UL File Number	E84782

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	750 kcmil - 250 kcmil
Conductor Range AL Stranded (Secondary, tap, load)	250 kcmil - 6 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	750 kcmil - 250 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	250 kcmil - 6 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Additional Technical Specifications

Connector Amperage Rating CU (Derated where applicable)	1520 Amps
Conductor Type	Solid

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Flammability Rating	NA
---------------------	----

Temperature Rating

90°C