



**SKU:** PED-6-4/0-Z

**UPC:** 0783669700121

**Features & Benefits:**

**Description:** Aluminum Multi-Tap Connector, Dual Rated, Conductor Range 4/0-6, 6 Ports, UL

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	6
Number of Poles	1
Number of Ports / Wireways	6

### Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	1
Height BX (IN)	2.25
Height (mm)	25.4
Length (IN)	5.502
Length (mm)	139.7508
Weight (LB)	0.266168128598898
Weight BX (LB)	2.8189
Width (IN)	0.75
Width BX (IN)	4.25
Width (mm)	19.05

### Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
--	---

Wire Binding Screw Size 9/16

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366970012

### Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

### Environment and Temperature

Temperature Rating 90°C

### Color

Color Silver

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	4/0 Str - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

### Voltage

Voltage Rating 600 V