



SKU: PET-4-500-Z

UPC: 0783669710182

Features & Benefits:

Description: Aluminum Spade Type Transformer Lug, Dual Rated, Conductor Range 500-2, 4 Ports

Specs

Additional Class Attributes

| | |
|----------------------------|------------|
| Connection | Mechanical |
| Contains DE-OX® | No |
| Number of Conductors | 4 |
| Number of Poles | 1 |
| Number of Ports / Wireways | 4 |

Dimensions

| | |
|-----------------|--------------|
| Drive Size Main | 5/16 |
| Drive Type Main | Internal Hex |
| Height (IN) | 1.625 |
| Height BX (IN) | 2.75 |
| Height (mm) | 41.275 |
| Length (IN) | 7.906 |
| Length (mm) | 200.8124 |
| Weight (LB) | 1.418 |
| Weight BX (LB) | 3.7329 |
| Width (IN) | 1 |
| Width BX (IN) | 6 |
| Width (mm) | 25.4 |

Material and Finish

| | |
|--------------------------------|----------|
| Conductor Material | Aluminum |
| Connector Finish | Tin |
| Insulation | NA |
| Material | Aluminum |
| Wire Binding Hardware Finish | Tin |
| Wire Binding Hardware Material | Aluminum |

Additional Technical Specifications

| | |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

Bolt and Screw Sizes

| | |
|--|---|
| Number of Wire Binding Screws per Port | 1 |
|--|---|

| | |
|-------------------------|-----|
| Wire Binding Screw Size | 3/4 |
|-------------------------|-----|

General

| | |
|-----------------------------|----------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 3 |
| Direct Burial | No |
| Dual Rated | Yes |
| NEMA Code | S-588-4 |
| UPC Code | 78366971018 |

Testing Standards

| | |
|--------------------|---|
| ANSI Specification | ANSI C119.6 |
| Prop65 Compliance | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number | NA |
| UL File Number | NA |

Color

| | |
|-------|--------|
| Color | Silver |
|-------|--------|

Conductor Ranges

| | |
|--|-------------------|
| Conductor Range AL Solid (Secondary, tap, load) | NA |
| Conductor Range AL Stranded (Primary, run, main, line) | 500 kcmil - 2 Str |
| Conductor Range AL Stranded (Secondary, tap, load) | NA |
| Conductor Range CU Solid (Primary, run, main, line) | NA |
| Conductor Range CU Solid (Secondary, tap, load) | NA |
| Conductor Range CU Stranded (Primary, run, main, line) | 500 kcmil - 2 Str |
| Conductor Range CU Stranded (Secondary, tap, load) | NA |
| Conductor Range AL Solid (Primary, run, main, line) | NA |