



**SKU:** PG402-S-Z

**UPC:** 0783669730289

**Features & Benefits:**

**Description:** Aluminum Parallel Groove Clamp, Dual Rated, Conductor Range 4/0-2, 3/8in Steel Bolt

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	2
Number of Poles	1
Wire Orientation	Parallel

### Dimensions

Drive Size Main	9/16
Drive Type Main	External Hex
Height (IN)	1.849
Height BX (IN)	7
Height (mm)	46.9646
Length (IN)	1.5
Length (mm)	38.1
Weight (LB)	0.207
Weight BX (LB)	11.126
Width (IN)	1.719
Width BX (IN)	8
Width (mm)	43.6626

### Material and Finish

Clamping Hardware Material	Steel
Conductor Material	Aluminum
Connector Finish	Clear
Insulation Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### Bolt and Screw Sizes

Clamping Bolt Size	3/8
Mounting Bolt/Stud Size	NA
Number of Wire Binding Screws per Port	1

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366973028

### Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
-------------------	---

### Color

Color	Silver
-------	--------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	4/0 Str - 2 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA