



**SKU:** PG620-S-Z

**UPC:** 0783669730142

**Features & Benefits:**

**Description:** Aluminum Parallel Groove Clamp, Dual Rated, Conductor Range 2/0-6 Sol, 3/8in Steel Bolt

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	2
Number of Poles	1
Wire Orientation	Parallel

### Dimensions

Drive Size Main	9/16
Drive Type Main	External Hex
Height (IN)	1.75
Height BX (IN)	7
Height (mm)	44.45
Length (IN)	1.188
Length (mm)	30.1752
Weight (LB)	0.173
Weight BX (LB)	9.5361
Width (IN)	1.557
Width BX (IN)	8

### Material and Finish

Clamping Hardware Material	Steel
Conductor Material	Copper
Connector Finish	Clear
Insulation Material	NA
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### Additional Technical Specifications

Conductor Type	Solid
----------------	-------

### Bolt and Screw Sizes

Clamping Bolt Size	3/8
--------------------	-----

Mounting Bolt/Stud Size	NA
Number of Wire Binding Screws per Port	1

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366973014

### Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
-------------------	---

### Color

Color	Silver
-------	--------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	2/0 Sol - 6 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	2/0 Sol - 6 Sol