



SKU: PG620-Z

UPC: 0783669730180

Features & Benefits:

Description: Aluminum Parallel Groove Clamp, Dual Rated, Conductor Range 2/0-6 Sol, 7/16 Aluminum Bolt

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	2
Number of Poles	1
Wire Orientation	Parallel

Dimensions

Drive Size Main	5/8
Drive Type Main	External Hex
Height (IN)	1.563
Height BX (IN)	7
Height (mm)	39.7002
Length (IN)	1.375
Length (mm)	34.925
Weight (LB)	0.117539674292428
Weight BX (LB)	8.126
Width (IN)	1.563
Width BX (IN)	8
Width (mm)	39.7002

Material and Finish

Clamping Hardware Material	Aluminum
Conductor Material	Copper
Connector Finish	Clear
Insulation Material	NA
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Clamping Bolt Size	7/16
Mounting Bolt/Stud Size	NA
Number of Wire Binding Screws per Port	1

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366973018

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
-------------------	---

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	2/0 Sol - 6 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	2/0 Sol - 6 Sol