



**SKU:** SPSS-5

**UPC:** 0783669233353

**Features & Benefits:**

**Description:** Permaground Bronze Service Post Connector, Male, Conductor Range 1/0-2, 1/2-13 x 3/4in Stud Size, Short Stud, Single Conductor, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Poles	1
Number of Ports / Wireways	1

### Dimensions

Drive Size Main	3/4
Drive Type Main	External Hex
Height (IN)	8
Height BX (IN)	2
Length (IN)	7.63
Mounting Bolt/Stud Size (mm)	30810.2
Weight (LB)	0.249
Weight BX (LB)	6.3719
Width (IN)	10.88
Width BX (IN)	6.1875

### Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Bronze

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2-13
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA

## General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	No
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366923335

## Testing Standards

CSA File Number	AP-100973-1
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	8M24
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E158587

## Environment and Temperature

Temperature Rating	90°C
--------------------	------

## Color

Color	Bronze
-------	--------

## Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	2 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

## Voltage

Voltage Rating	35 kV
----------------	-------