

SKU: TLK-2

UPC: 0783669879025

Features & Benefits:

Description: Aluminum Transformer Lug Kit, Dual Rated, Includes (12) TA-250, (8) 1/4-20 x 3/4 Bolts, (8) 1/4-20 x 1-3/4 Bolts, (16) 1/4-20 Free Spin Flange Nuts



Specs

Additional Class Attributes

Contains DE-OX®	No
Includes	(12) TA-250, (8) 1/4-20 X 3/4 Bolts, (8) 1/4-20 X 1-3/4 Bolts, (16) 1/4-20 Free Spin Flange Nuts

Dimensions

Height (IN)	2.375
Height BX (IN)	2.25
Height (mm)	60.325
Length (IN)	5
Weight (LB)	1.05159073860459
Weight BX (LB)	2.5815
Width (IN)	5
Width BX (IN)	5
Width (mm)	127

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation Material	NA
Material	Aluminum

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366987902

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to

	contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
---------------------------	------

Color

Color	Silver
--------------	--------

Voltage

Transformer kVA Size	50 to 75 (1-PHASE)
Voltage Rating	35 kV