



SKU: ULT-2-Z

UPC: 0783669930733

Features & Benefits:

Description: Permagraund Copper Grounding C Crimp, Main Conductor Range 8 Str-8 Sol, Tap Range 8-10 Sol, CSA

Specs

Additional Class Attributes

Fixing Type	NA
ILSCOs Die Catalog Number	ILD-162
ILSCOs Die Index Number	162

Dimensions

Height (IN)	0.5
Height BX (IN)	2.25
Height (mm)	12.7
Length (IN)	0.486
Length (mm)	12.3444
Weight (LB)	0.01
Weight BX (LB)	1.09
Width (IN)	0.353
Width BX (IN)	5
Width (mm)	8.9662

Material and Finish

Conductor Material	Copper
Connector Finish Material	Bare
Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366993073

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	8 Sol
Conductor Range CU Solid (Secondary, tap, load)	8 Sol - 10 Sol
Conductor Range CU Stranded (Primary, run, main, line)	8 Str
Conductor Range CU Stranded (Secondary, tap, load)	8 Str - 10 Str

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL / CULUS Specification	UL 486A/B Listed

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Voltage

Voltage Rating	35 kV
----------------	-------