



EXB-NFD-0303P - EXB-NFD Series, AL Non Fused Disconnect Switch, Switch Rating 30- 3-Pole - Top Conduit 2", Bottom Conduit 1/2", Wire Size 14-4

By Killark
Catalog # [EXB-NFD-0303P](#)



EXB-NFD Series - Aluminum Non Fused Disconnect Switch -
Switch Rating 30- 3-Pole - Top Conduit 2 Inch - Bottom Conduit
1/2 Inch - Wire Size 14-4

Features

- Copper-free aluminum construction, high strength, lighter in weight and corrosion resistant.
- Fewer cover bolts (no corner bolts required) reduces installation and maintenance time.
- Cover bolts are stainless steel.
- Gasketed flange with O-ring located inside the bolt circle to seal out moisture.
- Stainless steel hinges are standard.
- Switch operating handle of copper-free aluminum can be padlocked, with up to three locks, in either the "ON" or "OFF" position.
- Ductile mounting lugs adjust to irregular mounting surfaces.
- Bodies have top and bottom drilled and taped conduit entrances for power and drain/breather.
- Global applications (ATEX) Enclosures are available for global applications with "CEN" suffix.
- Assemblies that are modified to CENELeC/ATEX standards maintain their North American certifications.

General

Actuator	Handle
Catalog Number	EXB-NFD-0303P
EU RoHS Indicator	Contact Manufacturer
Enclosure Type	Bolted
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Mounting Type	Wall
Number Of Poles	3
Operating Temperature Celcius Max	40 Degree
Series	EXB-NFD
Size	8" x 8" x 6"
Type	Aluminum Non-Fused Disconnect Switch
UPC	783936012179

Dimensions

Depth	4
Dimensions	14.06 in x 10.3 in x 10.3 in
Gross Weight with Packaging	40
Height	10.3 in
Length	14.06 in
Weight	40 lb
Width	10.3 in

Electrical Ratings

Amperage Rating	30 A
Frequency Rating	60 Hz
Primary Voltage	600 VAC

Conductor Related

Number Of Wires	4
-----------------	---

Certifications And Compliance

ATEX File Number	PTB 07 ATEX 1024x
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11716
Hazardous Rating(s)	<ul style="list-style-type: none"> • Class I, Divisions 1 & 2, Groups B, C, D • Class I, Zones 1 & 2, Groups IIB+H2, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
Nema Rating	3, 4, 4X, 7(B, C, D), 9(E, F, G)
UL File Number	E10514 / E83969 / E12379

Product Assets

- [Catalogs - Killark Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Installation Manuals - EXB/LT-FDS & NFD IOM K1517](#)
- [Specifications - EXBNFD0303P](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
KILL-EXBNFD0303P-SPEC-EN | REV 3/2025