



# OC-2 - 3/4" C Hub, Aluminum O Series Conduit Body

By Killark  
Catalog # [OC-2](#)



\*Representative Image

## Features

- Raintight when used with gasketed covers.
- Malleable iron suitable for use in concrete.
- Interchangeable with competitive products.
- Stainless steel screws on stamped and cast covers.
- Tapered threaded hubs (NPT).

## Application

- To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

## General

|                   |                                              |
|-------------------|----------------------------------------------|
| Catalog Number    | OC-2                                         |
| Color             | Gray                                         |
| EU RoHS Indicator | Contact Manufacturer                         |
| Finish Type       | Powder Epoxy Paint                           |
| Hub Pattern       | C                                            |
| Material          | Aluminum, Copper Free (less than 4/10 of 1%) |
| Series            | O Series                                     |
| Type              | Conduit Body                                 |
| UPC               | 783936450025                                 |

## Dimensions

|                             |                    |
|-----------------------------|--------------------|
| Dimensions                  | 7 in x 2 in x 2 in |
| Gross Weight with Packaging | 0.33               |
| Height                      | 2 in               |
| Hub Size                    | 3/4"               |
| Length                      | 7 in               |

|        |         |
|--------|---------|
| Weight | 0.33 lb |
| Width  | 2 in    |

## Certifications And Compliance

|                          |                                                                                                                                                                              |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Buy America(n) Qualified | Contact Manufacturer                                                                                                                                                         |
| CSA File Number          | LR11852                                                                                                                                                                      |
| Hazardous Rating(s)      | Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2). |
| UL File Number           | E3397                                                                                                                                                                        |

## Logistics

|                 |   |
|-----------------|---|
| Carton Quantity | 5 |
|-----------------|---|

## Product Assets

- [3D Models - OC-2 3D Model](#)
- [Catalogs - Killark Catalog](#)
- [Certifications - E Series, O Series, CO & TW Series Conduit Bodies CSA Certificate of Conformity](#)
- [Customer Notices - Prop 65 Notice](#)
- [Engineering Drawing - OC-2 Engineering Drawing](#)
- [Sales Drawings - OC-2 Sales Drawing](#)
- [Specifications - O Series & Form 5 Cross Reference](#)
- [Specifications - Conduit Fill Information](#)
- [Specifications - O Series & Duraloy 5 Series Conduit Bodies Specification Sheet](#)



A Hubbell brand