



# Versamate Series 60A 3 Pole 4 Wire Receptacle Assembly

By Killark  
Catalog # [VR642](#)

60A 3 Pole 4 Wire Receptacle Assembly.



## Features

- Patented “Breech-Lock” cap serves as both flip lid and screw cover.
- Patented notch in cap arm holds cap open for easy plug insertion or maintenance.
- Type 4X rating when inserted into VersaMate receptacle and locking ring is tightened.
- Patented pin design uses slotted spring clip which avoids excessive wear while providing continuous electrical pin to sleeve contact.
- “Increased Safety” type box terminals with gripper ribs securely clamp around conductors.
- Boxes come with a green grounding screw.

## General

Application	
Catalog Number	VR642
EU RoHS Indicator	Contact Manufacturer
Finish Type	Finition époxy/polyester en poudre cuite
Material	Body-Copper-free aluminum; Contacts-Brass; Spring tensioner-Patented beryllium copper; External screws-316 stainless steel
Series	VersaMate
Style	Style II
Type	
UPC	783936834504

## Dimensions

Dimensions	4.5 in x 4.25 in x 4.66 in
Height	4.66 in
Length	4.5 in
Width	4.25 in

## Electrical Ratings

Amperage Rating	60 A
Frequency Rating	50-400 Hz
Voltage Rating	600 VAC 250 VDC

## Conductor Related

Number Of Wires	3
-----------------	---

## Product Assets

[Customer Notices - Prop 65 Notice](#)  
[Installation Manuals - Versamate 60 Amp Original Terminal IOM K1191](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
KILL\_CA-VR642-SPEC-EN | REV 6/2024