



VWSQ Series 30A 2P 3W NEMA 4X Mechanically Interlocked Receptacle

By Killark
Catalog # [VWSQ3023](#)

30A 2W3P NEMA 4X Mechanically Interlocked Receptacle

Features

- Compact size and footprint
- Plug Interlock Mechanism for Dead-Front construction. Switch cannot be turned “ON” without fully inserted plug. Plug cannot be removed with switch in “ON” position
- Factory Wired Receptacle (Load Side)
- “Off” position is padlockable for maintenance safety
- Auxiliary Contact (late-make early-break) rated 10 Amp, 1/3 HP at 125/250 VAC.
- Adjustable mounting lugs
- Feed-through construction
- Horsepower-rated internal switch

General

Catalog Number	VWSQ3023
EU RoHS Indicator	Contact Manufacturer
Hub Pattern	Feed-Thru
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Number Of Poles	2
Receptacle Type	Mechanically Interlocked
Series	VWSQ
UPC	783936833392

Dimensions



*Representative Image

Hub Size 1"

Electrical Ratings

Amperage Rating 30 A

Conductor Related

Number Of Wires 3

Certifications And Compliance

Nema Rating 3, 4, 4X, 7(B, C, D), 9(F, G)

Logistics

Carton Quantity 1

Product Assets

- [Certifications - VWSQ Series Receptacles CSA Certification](#)
- [Customer Notices - Prop 65 Notice](#)
- [Installation Manuals - KIL_VWSQ 30A Switched Receptacles IOM_K1225](#)
- [Specifications - VWSQ3023 Specification Sheet English](#)
- [Specifications - VWSQ3023 Specification Sheet French](#)
- [Specifications - VSQ/VSQFS Series Receptacles Specification Sheet](#)