



# XEDS-100 - XEDS Series, 100 Amp Max, Non-Fused Disconnect Switch

By Killark  
Catalog # [XEDS-100](#)

XEDS Series, 100 Amp Max, Non-Fused Disconnect Switch



## Features

- External handle is vault type with standard provisions for locking in "OFF" position with up to three padlocks.
- Provisions for locking in "ON" position available as factory modification (add suffix SU40 to catalog number).
- Enclosure and external handle is cast copper-free aluminum alloy (less than 4/10 of 1%).
- Cover bolts are stainless steel.
- Eaton (Cutler Hammer) Type DS Switches.
- Two cast conduit hubs, one top and one bottom.
- Internal disconnect handle mechanism is a sliding plate mounted to the cover.

## Specifications

Hazardous Rating(s)	<ul style="list-style-type: none"> <li>• Class II, Divisions 1 &amp; 2, Groups E, F, G</li> <li>• Class III, Divisions 1 &amp; 2</li> </ul>
EU RoHS Indicator	Contact Manufacturer
Nema Rating	3R, 4, 9(E, F, G)
UL File Number	E53290
CSA File Number	LR11714

## Conductor

Number Of Wires	4
-----------------	---

Number Of Poles	3
-----------------	---

## Current

Primary Voltage	600 VAC/250 VDC
Frequency Rating	60 Hz

## Dimensions

Depth	7
Width	9.125 in
Weight	17 lb.
Height	16 in

## General

Type	Non-Fused Disconnect
Enclosure Type	Bolted
Series	XEDS Series
Material	Aluminum, Copper Free (less than 4/10 of 1%)
UPC	783936898087
Mounting Type	Wall

## Operational

Operating Temperature Celcius Max	40 Degree
-----------------------------------	-----------