



## Patented Malleable Liquidtight Screw On Straight Connectors

Innovative electrical fittings with premium quality and service offering more than 1,600 SKUs and numerous labor savings products

### Features

- No disassembly required for installation
- Long ferrule prevents pullout and tight bend conduit pop-out
- Liquidtight/Raintight/Oiltight
- Compact, slim diameter

### Standard Materials

- Malleable Iron

### Standard Finish

- Zinc Plated

### Applicable Third Party Standards

- CULUS 514B, File Number: E207875
- NEMA FB-1
- Patent #: US 7,914,048



Catalog Number	Trade Size	Dim A (in)	Dim B (in)	Dim C (in)	Box	Weight Per C (lb)	Insulated
LTQ38-ICKON	3/8	1.13	0.56	1.13	25	16	Yes
LTQ38KON	3/8	1.13	0.50	1.13	25	15	No
LTQ50-ICKON	1/2	1.25	0.56	1.25	25	18	Yes
LTQ50KON	1/2	1.25	0.50	1.25	25	18	No
LTQ75-ICKON	3/4	1.25	0.56	1.56	25	29	Yes
LTQ75KON	3/4	1.25	0.50	1.56	25	29	No
LTQ100KON	1	1.44	0.63	1.81	5	40	No
LTQ100-ICKON	1	1.44	0.69	1.81	5	40	Yes
LTQ125-ICKON	1 1/4	1.50	0.75	2.25	5	56	Yes
LTQ125KON	1 1/4	1.50	0.69	2.25	5	55	No
LTQ150-ICKON	1 1/2	1.63	0.81	2.44	2	71	Yes
LTQ150KON	1 1/2	1.63	0.75	2.44	2	71	No
LTQ200-ICKON	2	1.75	0.81	3.00	1	100	Yes
LTQ200KON	2	1.75	0.75	3.00	1	99	No