

GFNT2-DIN



UPC Code: 07847772576

Country of Origin: China

GFCI Receptacles

Item Description

20 Amp, 125 Volt, NEMA 5-20R, 2P, 3W, DIN-Rail Self-Test GFCI Receptacle, Mountable Module Receptacle, Straight Blade, Extra-Heavy Duty Industrial Grade, Terminal Block Wired - BLACK

Technical Information

AC Horsepower Ratings

At Rated Voltage: 1 HP

Electrical Specifications

Grounding: Self-Grounding

Pole: 2

Wire: 3

Short Circuit Current Rating: 10kA

Environmental Specifications

Flammability: Rated V-0 per UL94

Operating Temperature: -35C to +66C

Material Specifications

Face Material: PBT

Enclosure Material: Polycarbonate

Enclosure Cover Material: Polycarbonate

Line Contacts: Brass

Mechanical Specifications

Product ID: Ratings are permanently marked on device

Standards and Certifications

NEMA: WD-1 & WD-6

ANSI: C-73

Applicable Standards: UL 943, UL 498, CSA C22.2 No. 42 & 144, FedSpec W-C-596

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 ·

FAX: 1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2012-2018 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

