|             | 2  |   |  |  |                |                       |                                   | 1                                      |                |  |   |                         |                      |                            |  |  |
|-------------|--|---|--|--|----------------|-----------------------|-----------------------------------|--|----------------|--|---|-------------------------|----------------------|----------------------------|--|--|
|             |  | THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE US |  |  |                |                       |                                   |  |                | ED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.  |   |                         |                      |                            |  |  |
|             |  |   |  |  |                | <u> </u>              | PART NAME                         | PANDUIT<br>PART<br>NUMBER<br>(SEE NOTE |                | ENGTH<br>IN.<br>MM.)   | (SE   | STATI<br>LOAD<br>EE NOT |                      | APPROX.<br>WEIGHT          |  |  |
|             |  | .58   |  |  |                |                       |                                   | LD5**6-A                               |                | 0±.13<br>29±3.3)   |   | 39 lbs<br>7.0 g/        |                      | .089  bs/ft<br>(.133 g/mm) |  |  |
| В           | .70  |   |  |  |                |                       |                                   | LD5**8-A                               | 96.<br>(243    | .0±.13<br>88±3.3)  | ( 7   | 39 lbs/<br>7.0 g/r      | mm )                 | .089  bs/ft<br>(.133 g/mm) |  |  |
|             | [17.8]<br>   |   |  |  |                |                       | LATCHING<br>DUCT                  | LD5**10-A                              |                | .0±.13<br>18±3.3)  |   | 39 lbs.<br>7.0 g/r      |                      | .089 lbs/ft<br>(.133 g/mm) |  |  |
|             |  |   |  |  |                |                       |                                   | LD5**2-A                               |                | 74±.13<br>).0±3.3  |   | 39 lbs.<br>7.0 g/r      |                      | .089  bs/ft<br>(.133 g/mm) |  |  |
|             |  |   |  |  |                |                       |                                   | LD5**3-A                               |                | .11±.13<br>).0±3.3   |   | 39 lbs/<br>7.0 g/r      |                      | .089  bs/ft<br>(.133 g/mm) |  |  |
|             | NOTES:  1. SEE CURRENT CATALOG FOR ADDITIONAL PART NUMBER SUFFIXES TO INDICATE COLOR AND OR PACKAGE QUANTITY.  2. PART IS DESIGNED TO SUPPORT MAXIMUM WEIGHT ON A CLEADRY, SMOOTH SURFACE. THE SURFACE MUST BE PROPERLY PREPARED IN ACCORDANCE WITH PANDUIT RECOMMENDATIONS.  3. TO APPLY PART: a. REMOVE PROTECTIVE LINER. b. PLACE PART IN DESIRED LOCATION. c. APPLY PRESSURE TO FLAT SURFACE OF PART.  NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY PANDUIT WIH RESPECT TO ADHESIVE BOND PERFORMANCE. AMONG OTHER THINGS, THE CONDITIONS UNDER WHICH THESE MOUNTS MAY BE APPLIED AND/OR THE SURFACE TO WHICH THEY MAY BE APPLIED ARE BEYOND PANDUIT'S CONTROL.  DIMENSIONS IN PARENTHESES ARE IN METRIC |   |  |  |                |                       |                                   |  |                |  | OR  EIGHT ON A CLEAN BE PROPERLY ECOMMENDATIONS.  PART.  SPECT TO ADHESIVE WHICH THESE MOUNTS ED ARE BEYOND | 9                       |                      |                            |  |  |
| -           |  |   |  |  |                |                       |                                   | LATCHING DUCT                          |                |  |   |                         |                      |                            |  |  |
| A           |  |   |  |  |                |                       |                                   |  |                |  |   | A                       |                      |                            |  |  |
|             |  |   |  |  |                |                       |                                   |  |                | ITEM REVISION  | CUSTOMER DRAWING  ITEM REVISION NAME  D15247BA/03   |                         |                      |                            |  |  |
|             |  |   |  |  |                |                       |                                   |  | DATASET FILE N | NAME   | DC_LD5/03   | PANDUI                  |                      |                            |  |  |
|             |  |   |  |  |                |                       |                                   |  |                | UNLE<br>DIMENSIO   | UNLESS OTHERWISE SPECIFII<br>DIMENSIONAL TOLERANCES ARE:  |                         | IFIED,<br>E: IN [mm] |                            |  |  |
|             | 03A  | 03A 11-06-19 BSN BETL ELN P. UPDATED LEN                        |  |  | P. UPDATED LEN | GTH TOLERANCE TO MATC | TH TOLERANCE TO MATCH CONTROL DWG |  |                | .X : .XXX : .XXX : .XX : |   |                         | PVC DRAWING NUMBER:  |                            |  |  |
| DA/14       | 15   | 02-20-13 JBN RTFI RTFI N. UPDATED DRAWING BORDER & TITLE BLOCK  |  |  |                | SS-15247              | THIRD ANGLE SS-1524               |  |                |  |   |                         |                      |                            |  |  |
| D10100DA/14 | REV DATE BY CHK APR DESCRIPTION  |   |  |  |                |                       | ECN                               | RS DATE                                | 02–19–79       | HVP  | FULL  | SHT 1 0F 1              | SIZE                 |                            |  |  |
|             |  |   |  |  |                | 2                     |                                   |  |                | •  |   | 1                       | ,                    |                            |  |  |