

MATERIAL SAFETY DATA SHEET

<u>Chemical Name or Synonym</u> Fiberglass Reinforced Plastic (FRP) and Precast Polymer Concrete Products

 $\label{eq:product_Name} \frac{\text{Product Name}}{\text{CDR}^{\text{TM}}, \text{ Comcore@, Custom Composites}^{\text{TM}},} \\ \text{Electrimold}^{\text{TM}}, \text{ Hotbox@, Polycast@, Polyvent@,} \\ \text{Quazite@, and Western Power Products}^{\text{TM}}$

SECT	ION 1									
Manufacturer's										
Name:	Hubbel	l Power System	ıs, Inc.			Emergen	ev.			
Address:	2911 In	dustrial Park I	Orive			Telephon		(865) 986-5533		
City, State, and Zip: Lenoir City, TN 37771						Other Inf	Other Information			
Signature of Person Responsible for Prep	aration (o _l	otional)				Date Prep	pared	9/12/2011		
SECT	ION 2									
Hazardous Compone	ent(s) (chei	nical & common 1	name(s))	CAS	OSHA	ACGH		%		
Th: 4 4	L - 1 - C' '4'	£	I "20CED 10:	10 1200 (-) O-4-1 1000) A	I W/h:	-1. :- £		. 4 !	
				10-1200 (c) October, 1989						
			• •	in whole or part upon its	1 0			iich does not release or	otherwi	
result in exposure to	a hazardoi	us chemical under	normal condi	tions of use. It is therefor	e not considere	d a hazardous ma	terial.			
SECT	ION 3	- PHYSIC	AL & CH	HEMICAL CHA	RACTER	RISTICS				
Boiling Point	N/A			Specific Gravity(H ₂ O=1)	1.3 – 2.3			Vapor Pressure (mm Hg)	N/A	
Vapor Density (air=1)	N/A			Solubility in Water	N/A			Reactivity in Water	N/A	
Appearance and Odor	N/A			Melting Point	N/A					
SECT	ION 4	- FIRE &	EXPLOS	SION DATA						
Flash Point	N/A	Method Used	N/A	Flammable Limits in Air % by Volume	N/A	LEL Lower	N/A	UEL Upper	N/A	
Auto-Ignition Temperature	N/A			Extinguisher Media	N/A					
Special Fire Fighting Procedures	N/A									
Unusual Fire and Explosion Hazards		None Known (I	FRP and polyn	ner concrete products are	not flammable	under normal con-	ditions of	use).		

SECTION 5	- PHYSICAL HAZ	ARDS (REACTIVITY DAT	A)				
Stability	Unstable ☐ Stable ☐	Conditions	NONE				
Incompatibility (Materials to Avoid)	N/A						
Hazardous Decomposition Products	N/A						
Hazardous Polymerization	May Occur ☐ Will Not Occur ☐	Conditions to Avoid	NONE				
SECTION 6	-HEALTH HAZAR	RDS					
1. Acute: NONE			not hazardous but may produce nuisance e silica when it is ground or cut with a dry abrasive.				
Signs and symptoms of Exposur	е	Repeated and prolonged exposure to dust containing respirable silica may cause injury to the lungs (silicosis).					
Medical Conditions Generally Aggravated by Exposure		Asthma and other respin	ratory illnesses.				
Emergency and First Aid Proceed	lures	Move exposed personnel to a dust free area. Flush eyes with plenty of water.					
ROUTES	1. Inhalation	NIOSH approved dust mask should be	used when cutting or grinding.				
OF	2. Eyes	Full eye protection should be used who	en cutting or grinding.				
ENTRY	3. Skin4. Ingestion	N/A N/A					
SECTION 7	- SPECIAL PRECA	AUTIONS AND SPILL/LEA	K PROCEDURES				
Precautions to be taken	Wear goggles and appropriate respiratory protection when dry sawing or grinding.						
Other precautions	NIOSH approved dust mask when dry sawing or grinding.						
Steps to be taken in case material is released or spilled	FRP and polymer concrete is a non-toxic solid and requires no special procedures.						
Waste Disposal Methods (consult federal, state, and local regulations)	FRP and polymer concrete may be disposed of by land filling according to local laws and ordinances						
SECTION 8 -	- SPECIAL PROTEC	CTION INFORMATION/CON	TROL MEASURES				
Respiratory Protection (Specify Type)	Use NIOSH approved dust mask for prolonged grinding or cutting if dusty conditions exist.						
Ventilation YES	Local Exhaust YES	Mechanical N/A Special (General)	N/A Other N/A				
Protective Gloves Not Requ	ired Eye Protection	Wear safety glasses to protect eyes fro	m dust particles.				
Other Protective Clothing or Equ	uipment NONE						
Work/Hygienic Practices	N/A						