

**Liquid Tight Connectors**

**1 INCH ALUMINUM STRAIGHT LT CONNECTOR**



**Catalog Number** PR5234AL  
**UPC** 784011219728

**Description**


PVC coated liquid tight connectors are used with liquid tight conduit to wire motors, transformers, processing equipment, pumps, etc. The flexible conduit and the PVC coated connector work together to seal out water and other corrosive liquids, protecting the conductors from damage.

**Application**

- Used with liquid tight conduit to wire motors, transformers, processing equipment, pumps, and more.

**Features**

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 3/8" through 6"
- Sealing sleeves on all conduit openings
- Available in straight, 45° or 90° body configurations
- Available with an external grounding lug



**General Information**

Trade Size	1
Material	ALUMINUM
Material	ALUMINUM
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane
Configuration	STRAIGHT

**Dimensions**

Dimension A (Inches) 1.96

Dimension B (Inches)	2.06
----------------------	------

Dimension C (Inches)	0.75
----------------------	------

## Technical Specification Documents

---

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Installer Certification and Tools	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Chemical Resistance Charts	AVAILABLE ON WEBSITE
----------------------------	----------------------

Performance Specifications	AVAILABLE ON WEBSITE
----------------------------	----------------------

## Technical Information

---

Conduit Body	LT
--------------	----

Fitting Configuration	STRAIGHT
-----------------------	----------

Fitting Type	LIQUID-TIGHT CONNECTOR
--------------	------------------------

Product Category	FITTING
------------------	---------

Product Family	Liquid Tight Connectors
----------------	-------------------------

## Notes

---

- When transitioning from flex to fittings with female connection, it is suggested to use a PVC Coated Nipple with PVC Coated LTR Fittings.