

### Liquid Tight Connectors

## 2 INCH 90 DEGREE LT CONNECTOR W/ GROUND



**Catalog Number** PR5357GR  
**UPC** 784011208920

### Description

PVC coated liquid tight connectors with ground are used with liquid tight conduit to wire motors, transformers, processing equipment, pumps, etc. The flexible conduit and the PVC coated connector work together to seal out water and other corrosive liquids, protecting the conductors from damage.

### Application

- Used with liquid tight conduit to wire motors, transformers, processing equipment, pumps, and more.

### Features


- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 3/8" through 6"
- Sealing sleeves on all conduit openings
- Available in straight, 45° or 90° body configurations
- Available with an external grounding lug

### General Information

|                 |   |
|-----------------|---|
| Trade Size      | 2   |
| Material        | FERROUS METAL                                 |
| Material        | FERROUS METAL                                 |
| Exterior Finish | A nominal .040 inch (40 mil) gray PVC coating |
| Interior Finish | A nominal .002 inch (2 mil) red urethane      |
| Configuration   | 90  |
| Grounding Lug   | Attached                                      |

### Dimensions

|                      |      |
|----------------------|------|
| Dimension A (Inches) | 3.89 |
|----------------------|------|



|                         |        |
|-------------------------|--------|
| Dimension B (Inches)    | 3.44   |
| Dimension C (Inches)    | 0.88   |
| Ground Wire             | 4/3/04 |
| Nominal Weight (Pounds) | 2.7    |

## Standards

---

|                               |         |
|-------------------------------|---------|
| UL 467 (Steel Fittings only)  | E217890 |
| UL 514B (Steel fittings only) | E200413 |

## Technical Specification Documents

---

|                                   |                      |
|-----------------------------------|----------------------|
| Specification Guide (1995 Master) | AVAILABLE ON WEBSITE |
| Specification Guide (2004 Master) | AVAILABLE ON WEBSITE |
| Installer Certification and Tools | AVAILABLE ON WEBSITE |
| Chemical Resistance Charts        | AVAILABLE ON WEBSITE |
| Performance Specifications        | AVAILABLE ON WEBSITE |

## Technical Information

---

|                       |                         |
|-----------------------|-------------------------|
| Conduit Body          | LT with ground          |
| Fitting Configuration | 90                      |
| Fitting Type          | LIQUID-TIGHT CONNECTOR  |
| Product Category      | FITTING                 |
| Product Family        | Liquid Tight Connectors |

## Notes

---

- When transitioning from flex to fittings with female connection, it is suggested to use a PVC Coated Nipple with PVC Coated LTR Fittings.