

### EL Style Malleable Elbows

## 3/4 INCH ALUMINUM M/F 90 DEGREE MALLEABLE ELBOW



**Catalog Number** PREL296SA  
**UPC** 784011219544

### Description

PVC coated EL style malleable elbows with male and female threads (Male/Female) are used in a conduit run to change direction 90° or to terminate at a fitting or box.

### Application

- Used in a conduit run to change direction 90 degree or to terminate at a fitting or box

### Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- Various configurations in 10 trade sizes from 1/2" through 4"
- Sealing sleeves on all conduit openings

### General Information

Trade Size	3/4
Material	ALUMINUM
Material	ALUMINUM
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane

### Dimensions


Dimension A (Inches)	1.63
Nominal Weight (Pounds)	

### Standards

NEC/CEC	Class III
NEC/CEC	Class II, Division 1, Groups E, F, G
NEC/CEC	Class II, Division 2, Groups F, G
NEC/CEC	Class I, Division 1 & 2, Groups A, B, C, D

### Technical Specification Documents

Specification Guide (1995 Master) AVAILABLE ON WEBSITE



Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

**Technical Information**

---

Conduit Body	90
Fitting Configuration	M/F
Fitting Type	MALLEABLE ELBOW
Product Category	HAZARDOUS LOCATION FITTING
Product Family	EL Style Malleable Elbows
Rating	Hazardous Location