

EL Style Malleable Elbows

1 INCH ALUMINUM M/F 90 DEGREE MALLEABLE ELBOW

ISO
9001:2015
CERTIFIED

Catalog Number PREL396SA

UPC 784011219551

Description

PVC coated EL style malleable elbows with male and female threads (Male/Female) are used in a conduit run to change direction 90° or to terminate at a fitting or box.

Application


- Used in a conduit run to change direction 90 degree or to terminate at a fitting or box

Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- Various configurations in 10 trade sizes from 1/2" through 4"
- Sealing sleeves on all conduit openings

General Information

Trade Size	1
Material	ALUMINUM
Material	ALUMINUM
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane



Dimensions

Dimension A (Inches) 1.88

Nominal Weight (Pounds)

Standards

NEC/CEC Class II, Division 2, Groups F, G

NEC/CEC Class II, Division 1, Groups E, F, G

NEC/CEC Class I, Division 1 & 2, Groups A,B,C,D

NEC/CEC Class III

Technical Specification Documents

Specification Guide (1995 Master) AVAILABLE ON WEBSITE

Specification Guide (2004 Master) AVAILABLE ON WEBSITE

Installer Certification and Tools AVAILABLE ON WEBSITE

Chemical Resistance Charts AVAILABLE ON WEBSITE

Performance Specifications AVAILABLE ON WEBSITE

Technical Information

Conduit Body 90

Fitting Configuration M/F

Fitting Type MALLEABLE ELBOW

Product Category HAZARDOUS LOCATION FITTING

Product Family EL Style Malleable Elbows

Rating Hazardous Location