

Pulling Elbows

4 INCH LBD PULLING ELBOW



Catalog NumberPRLBD10900

UPC784011205127

Description

PVC coated LBD conduit bodies are used at 90° bends in conduit runs to allow straight pulls at bends, to serve as pull outlets for stiff conductors, to allow for service entrance into buildings, or to allow conductor entrance into motors. Electrical continuity of the conduit system is maintained across assembled joints.

Application



- Act as pull outlets for conductors that are stiff due to large size or type of insulation
- Make 90 degree bends in conduit system, allowing straight pull in either direction
- Provide for conduit service entrance to buildings
- Provide for conductor entrance to motors
- Provide access to wiring for maintenance and future expansion

Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 10 trade sizes from 1/2" through 4"
- Sealing sleeves on all conduit openings
- Molded-in seal between body and cover
- Domed covers allow gentle bends of conductors
- Shipped with covers
- Angled covers allow straight pulling in either direction

General Information

Trade Size	4
Material	FERROUS METAL
Material	FERROUS METAL
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating



A nominal .002 inch (2 mil) red urethane

Dimension A (Inches)	20.88
Dimension B (Inches)	10.92
Dimension C (Inches)	7.83
Dimension D (Inches)	4.75
Dimension E (Inches)	19.89
Nominal Weight (Pounds)	70

UL 514B E200413

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

Conduit Body	LBD
Feed Type	Feed Thru
Fitting Type	PULLING ELBOW
Product Category	FITTING
Product Family	Pulling Elbows