

### Conduit Unions UNF & UNY Unions

## 1/2 INCH FEMALE-TO-MALE (F/M) UNY UNION



<b>Catalog Number</b>	PRUNY105
<b>UPC</b>	784011207831

### Description

PVC coated UNY unions are used to connect conduit to a conduit fitting, junction box, or device enclosure. One end is a male thread and the other is female.

### Application

- Applicable for Hazardous Locations

### Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings
- Molded PVC gasket seals fitting


### General Information

Trade Size	1/2
Material	FERROUS METAL
Material	FERROUS METAL
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane

### Dimensions

Length (Inches)	2.38
Max Diameter (Inches)	2
Nominal Weight (Pounds)	0.4

### Standards



CSA	C22.2 No. 30
NEC/CEC	Class III
NEC/CEC	Class I, Division 1 & 2, Groups A, B, C, D
NEC/CEC	Class II, Division 2, Groups F, G
NEC/CEC	Class II, Division 1, Groups E, F, G
UL 1203	E476062

### Technical Specification Documents

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

### Technical Information

Fitting Configuration	F/M
Fitting Type	UNION
Product Category	HAZARDOUS LOCATION FITTING
Product Family	Conduit Unions UNF & UNY Unions
Rating	Hazardous Location

