

Conduit Unions UNF & UNY Unions

1 INCH FEMALE-TO-MALE (F/M) ALUMINUM UNY UNION

ISO
9001:2015
CERTIFIED

UL
US
LISTED

Catalog Number PRUNY305SA

UPC 784011219384

Description

PVC coated UNY unions are used to connect conduit to a conduit fitting, junction box, or device enclosure. One end is a male thread and the other is female.

Application

- Applicable for Hazardous Locations

Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings
- Molded PVC gasket seals fitting

General Information


| | |
|-----------------|---|
| Trade Size | 1 |
| Material | ALUMINUM |
| Material | ALUMINUM |
| Exterior Finish | A nominal .040 inch (40 mil) gray PVC coating |
| Interior Finish | A nominal .002 inch (2 mil) red urethane |

Dimensions

| | |
|-----------------------|------|
| Length (Inches) | 2.75 |
| Max Diameter (Inches) | 2.75 |

Standards

| | |
|---------|--|
| CSA | C22.2 No.30 |
| NEC/CEC | Class I, Division 1 & 2, Groups A, B, C, D |
| NEC/CEC | Class II, Division 2, Groups F, G |
| NEC/CEC | Class III |
| NEC/CEC | Class II, Division 1, Groups E, F, G |



SAFETY US
E476062



UL 1203

E476062

Technical Specification DocumentsSpecification Guide (1995 Master) AVAILABLE ON WEBSITESpecification Guide (2004 Master) AVAILABLE ON WEBSITEInstaller Certification and Tools AVAILABLE ON WEBSITEChemical Resistance Charts AVAILABLE ON WEBSITEPerformance Specifications AVAILABLE ON WEBSITE**Technical Information**Fitting Configuration F/MFitting Type UNIONProduct Category HAZARDOUS LOCATION FITTINGProduct Family Conduit Unions UNF & UNY UnionsRating Hazardous Location