

Conduit Unions UNF & UNY Unions

2 INCH FEMALE-TO-MALE (F/M) ALUMINUM UNY UNION



Catalog Number PRUNY605SA
UPC 784011219414

Description

PVC coated UNY unions are used to connect conduit to a conduit fitting, junction box, or device enclosure. One end is a male thread and the other is female.

Application

- Applicable for Hazardous Locations

Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings
- Molded PVC gasket seals fitting

General Information


Trade Size	2
Material	ALUMINUM
Material	ALUMINUM
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane

Dimensions

Length (Inches)	3.75
Max Diameter (Inches)	4.5

Standards

CSA	C22.2 No. 30
NEC/CEC	Class I, Division 1 & 2, Groups C, D
NEC/CEC	Class II, Division 2, Groups F, G
NEC/CEC	Class III
NEC/CEC	Class II, Division 1, Groups E, F, G



UL 1203

E476062

Technical Specification Documents

Specification Guide (1995 Master) AVAILABLE ON WEBSITE

Specification Guide (2004 Master) AVAILABLE ON WEBSITE

Installer Certification and Tools AVAILABLE ON WEBSITE

Chemical Resistance Charts AVAILABLE ON WEBSITE

Performance Specifications AVAILABLE ON WEBSITE

Technical Information

Fitting Configuration F/M

Fitting Type UNION

Product Category HAZARDOUS LOCATION FITTING

Product Family Conduit Unions UNF & UNY Unions

Rating Hazardous Location