

Project Name

Location

Prepared By

**SATCO S8530**

9WPLH/LED/827/BP/2P

Notes

(revised) 04-14-2023 00:07:02

General

Status	Active
Watts	9W
Fluorescent Equivalent	18W/26W
Volts	120V-277V
Ballast Type	Type B
Shape	PL
Base	G24d (2-Pin)
ANSI Base	G24d
Finish	Frost
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	900L
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL
Operating Position	Horizontal
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Operating Frequency	50/60Hz
Power Factor	0.99
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	6.63
MOD	1.09
Housing Color	White
Weight (lb.)	0.14

Additional Information

Installation Notes	2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp