



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 240V A. Rating: 200A Wattage: 2W No. Of Poles: 2P F. Rating: 60Hz Action: DOUBLE THROW Material: STEEL Enclosure: TYPE 1. 2-3 point mounting holes. O. Cycles: 8000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: INDOOR

| General technical data | |
|--|-------------------------------------|
| mechanical service life (operating cycles) typical | 8000 |
| fastening method | SURFACE |
| number of poles | 2 |
| suitability for operation | LOAD TRANSFER BETWEEN POWER SOURCES |
| Electricity | |
| ampacity | 200 A |
| supply voltage frequency rated value 50/60 Hz | Yes |
| Model | |
| product brand name | SIEMENS |
| product type designation | DOUBLE THROW SWITCH |
| type of electrical connection | MECHANICAL LUGS |
| Mechanical Design | |
| design of the housing | TYPE 1 |
| design of the actuating element | DOUBLE THROW |
| material | STEEL |
| General product approval | |
| certificate of suitability | UL98 |

last modified:

9/16/2021

