1/11/2018 Product Details

Product 20586

Number:

Order FT40DL/841/RS/ECO

Abbreviation:

General DULUX 40W long compact fluorescent lamp with 4-pin base, 4100K color

Description: temperature, 82 CRI, ECOLOGIC for use on magnetic, electronic and dimming

ballasts



Product Information

FT40DL841RSECO 10/CS 1/SKU Abbrev. With Packaging Info. Average Rated Life (hr) 15000 Base 2G11 Bulb L (T5) 80 - 89 Color Rendering Index (CRI) 4100 Color Temperature/CCT (K) 0.709 Diameter (in) Diameter (mm) 18.00 Family Brand Name Dulux® L **Industry Standards** ANSI C78.901 - 2001 Initial Lumens at 25C 3150 Mean Lumens at 25C 2709 22.4 Maximum Overall Length - MOL (in) Maximum Overall Length - MOL (mm) 573 Nominal Wattage (W) 40.00





Footnotes

- Approximate initial lumens after 100 hours operation.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- There is a NEMA supported, industry issue where T2, T4, and T5 fluorescent and compact fluorescent lamps operated on high frequency ballasts may experience an abnormal end-of-life phenomenon. This end-of-life phenomenon can resultin one or both of the following: 1. Bulb wall cracking near the lamp base. 2. The lamp can overheat in the base area and possibly melt the base and socket. NEMA recommends that high frequency compact fluorescent ballasts have an end-of-life shutdown circuit which will safely and reliably shut down the system in the rare event of an abnormal end-of-life failure mode described above. The final requirements of this system are yet to be defined by ANSI. For additional information refer to NEMA papers on their WEBSITE at www.NEMA.org.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.