



Product Number:

74233

Order Abbreviation:

HIBAY1A/200UNVD850/GR

General Description:

High Bay 1A, 200 Watts, 120-277V, 0-10V Dimmable, 80+ CRI, 5000K, gray finish

Product Information

Diameter (in)	8.8
Diameter (mm)	223.5
Power Factor	≥0.90
Primary Lamp Type	SMD
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Total Harmonic Distortion (THD)	≤20 %
Efficacy (LPW)	103
Abbrev. With Packaging Info.	HIBAY1A200UNVD850GR 1/CS 1/SKU
Color Temperature/CCT (K)	5000
Ordering Abbreviation	HIBAY1A/200UNVD850/GR
Average Rated Life 1 (hr)	63000
Lumens	20600
Nominal Voltage (V)	120.00
Nominal Wattage (W)	200.00
UPC Code	UPC046135742330
Color Rendering Index (CRI)	>80
Service Life Rating	≥63000
Lumens (lm)	20600
Wattage (W)	200.00
Accessories	Hook
Color Range	5000 K
Connectors	Flying leads
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	Gray
Luminaire Type	High bay
Maximum Operating Temperature-Celsius	50
Maximum Operating Temperature-Fahrenheit	122
Power Input	200
Mounting	Hook
Dimensions	8.8x15.2
Certification Listing	cULus, FCC, RoHS, DLC

