SYLVANIA Lamps

ULTRA LED™ High Lumen Lamps

Application

ULTRA LED HID replacement lamps are ideal for indoor high/low bay lighting and outdoor decorative post top fixtures in walkway lighting applications.

Benefits and Features

- Lasts up to 5 times longer than HID lamps
- No warm-up time, instant on with full light output and stable color
- Consumes up to 76% less energy than equivalent HID lamps while delivering same light output
- Rated for open and enclosed fixtures
- Replacement for 70W-400W HID medium/mogul base applications
- Up to 145 LPW
- 3000K, 4000K and 5000K color temperatures
- CRI 80+
- 360° beam angle (or omnidirectional) with Type V distribution

Electrical

- 120-277Vac
- Power Factor 98%
- 6kV surge protection

Rated Life

- 50,000 hours (L₇₀)

Warranty

- Standard 5 year lamp warranty

Ambient Operating Range

- -40°F to +122°F (-40°C to +50°C)

Certifications and Listings

- DLC 5.0 Rated
- IP64 Rated
- UL Damp Rated

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.ledvanceUS.com/fcc15b.



Wattage Comparison

Traditional Source	Traditional System Wattage	LED System Wattage	Energy Savings	Energy Savings Over Lamp Life*
HID Metal Halide	100W	27W	73%	\$402
HID Metal Halide	150W	36W	76%	\$627
HID Metal Halide	250W	80W	68%	\$935
HID Metal Halide	320W	100W	69%	\$1,210
HID Metal Halide	400W	120W	70%	\$1,540

^{*}Energy savings over life of lamp calculated at \$0.11/kWh

Installation

- Requires easy ballast by-pass.
- Lamp operates directly on line voltage 120-277 Vac.















Specification Data

Project	
Comments	
Prepared by	

Ordering Guide

LED	XX	HIDR	8	XX	XXX
LED Lamps and Retrofits	Wattage	Lamp Type:	CRI	Color Temperature:	Base Type
	18, 27, 36,	HID Replacement	8 = 80 +	30 = 3000K	MED = E26 Medium Base
	80, 100, 120			40 = 4000K	
				50 = 5000K	

Ordering Information

					Input	Average			Typical			
Item	Ordering	Power	Base		Voltage	Life		Case	Lumens			
Number	Abbreviation	(W)	Туре	Replaces	(V)	(hrs)	CCT	Qty	(lm)	CRI	DLC	CEC
40706	LED27HIDR830 4/CS 1/SKU	27	Medium base	100W	120-277	50,000	3000K	4	3600	+08	No	Yes
40708*	LED27HIDR850 4/CS 1/SKU	27	Medium base	100W	120-277	50,000	5000K	4	3900	+08	No	Yes
40872	LED36HIDR830MED 4/CS 1/SKU	36	Medium Base	150W	120-277	50,000	3000K	4	4800	+08	No	Yes
40709*	LED36HIDR830 4/CS 1/SKU	36	Mogul base†	150W	120-277	50,000	3000K	4	4800	+08	Yes	Yes
40715*	LED80HIDR830 4/CS 1/SKU	80	Mogul base†	250W	120-277	50,000	3000K	4	10,800	+08	Yes	Yes
40717*	LED80HIDR850 4/CS 1/SKU	80	Mogul base†	250W	120-277	50,000	5000K	4	11,600	+08	Yes	Yes
40718*	LED100HIDR830 4/CS 1/SKU	100	Mogul base†	320W	120-277	50,000	3000K	4	13,500	+08	Yes	Yes
40721*	LED120HIDR830 4/CS 1/SKU	120	Mogul base†	400W	120-277	50,000	3000K	4	16,200	+08	Yes	Yes

Accessory Information

Item	Ordering	
Number	Abbreviation	Description
75055	LED/ADAPTOR/MOGULBASE*	LED Retrofit HID Mogul Base Adapter

 $^{^*\}mbox{Enables}$ lamps with E26 medium base to be used in EX39 mogul base socket applications.





^{*}Lamp will be discontinued once inventory is depleted.


†EX39 base will work in both exclusionary and non-exclusionary sockets.


Physical Information


Lamp Description	(A) MOL	(B) Diameter
LED HIDR 27W	6.6 in	2.5 in
LED HIDR 36W Medium	7.8 in	3.4 in
LED HIDR 36W Mogul	8.5 in	3.4 in
LED HIDR 80W	9.8 in	4.8 in
LED HIDR 100W	10.7 in	4.8 in
LED HIDR 120W	11.7 in	4.8 in














Additional Specifications

- Not intended for use in dimming applications
- Verify fixture size before installation to ensure fit
- Not suited with outdoor fixtures with air vents
- Should not be directly exposed to water/humidity

LEDVANCE LLC 181 Ballardvale Street, Suite 203 Wilmington, MA 01887 USA Phone 1-800-LIGHTBULB (1-800-544-4828) www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks. All other trademarks are those of their respective owners. Licensee of product trademark SYLVANIA in general lighting. Specifications subject to change without notice.



SCAN TO FOLLOW US ON SOCIAL MEDIA

