



Representative

Catalog Number: 9MI34U2WNAA/75
Product ID: 7TAA057180R0001
UPC Number: 70891731304
Status: Active

DuraGard Rotary Controlled, Watertight, Non-Metallic Interlocked Receptacle- 30 Amp, 30 250V

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	DuraGard Waterproof Connections
Special Features	Not just "watertight"; Waterproof for washdown duty (DurORing Sealing) that eliminates the need for costly "weather boots" or "adapters."
Application	For use where electrical connections need protection from water and/or dust entrance to the contacts or the wiring compartment.
Number Of Poles	3
Number Of Wires	4
Amperage Rating	30 Amp
Voltage Rating	250V
Material	DuraV

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Number of poles	3

Packaging

Outer Quantity	1
Outer Dimensions (inches)	14.88x10.25x13.25
Weight Uom	8.21 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com