



Actual

Catalog Number: TY300-50X-100
Product ID: 7TAG054360R0279
UPC Number: 78621023224
EAN Number: 05414363075325
Status: A

Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 302.26mm (11.9 Inches), Width of 4.673mm (0.184 Inches), Thickness of 1.24mm (0.049 Inches), Tensile Strength Rating of 220 Newtons (50 Pounds), 100 Pack

North American Specifications (UNSPSC)

UNSPSC	39121703 Cable ties
IGCC	5034 Cable ties
Brand Name	Ty-Fast
Type	General Purpose
Width	0.184 in ; 4.674 mm
Length	11.9 in ; 302.26 mm
Thickness	0.049 in ; 1.24 mm
Bundle Diameter	3 in ; 76.2 mm
Material	Nylon/Polyamide 6.6
Color	Black
Lock Mechanism	Plastic Pawl
Tensile Strength	50 pounds ; 222 newtons

European Specifications (ETIM)

ETIM	EC000046 Cable tie
Band width	4.673mm
Length belt/tape/tie	302.26mm
Tie thickness	1.24mm
Max. bundle diameter	76.2mm
Min. holding force	220N
Operating temperature	-40-+85°C
Model	Internal toothing
Band closure	Plastic lip/-cam
Material	Plastic
Material quality	Polyamide PA
Surface protection	Untreated
Halogen free	Y
Colour	Black
Transparent	N
Reflective (fluorescent)	N
Text strip	None
Solvable fastener	N
VG approval	N
MIL approval	Y
UL approval	Y

Packaging

Inner Quantity	100
Inner Dimensions (inches)	16x2x6
Outer Quantity	5000
Outer Dimensions (inches)	17x13.5x10.25
Weight Uom	3.75 lbs. per 1000

For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com