





Complete Insulated Program





(Wind) Toll Free: (800) 494-6104

Arc Flash Protection:

Wiha Insulated tools can be a vital component in your Arc Flash protection strategy. What is Arc Flash?

ARC FLASH

An Arc Flash is an electrical explosion due to a fault condition or short circuit when either a phase to ground or phase to phase conductor is connected. Arc flashes cause electrical equipment to explode, resulting in an arc-plasma fireball. Temperatures may exceed 35,000° F (the surface of the sun is 9000° F). These high temperatures cause rapid heating of surrounding air and extreme pressures, resulting in an arc blast. The arc blast will likely vaporize all solid copper conductors which will expand up to 67,000 times its original volume when it is vaporized. The result of this violent event is usually destruction of the equipment involved, fire, and severe injury or death to any nearby people.

WHY ARC FLASHES HAPPEN

There are a variety of reasons why an Arc Flash can occur, but most of them are preventable. Most arc flashes occur when maintenance workers are manipulating live equipment for testing or repair and accidentally cause a fault. Improper tools, improper electrical equipment, corrosion of equipment, improper work techniques and lack of training are just some of the events that can lead to a devastating arc flash or arc blast.

ARC FLASH COMPLIANCE

There are 4 main regulations that govern electrical safety & arc flash:

1. OSHA Standards 29CFR, Part 1910. Occupational Safety and Health Standards. 1910 sub part S (electrical) Standard number 1910.333 specifically addresses Standards for Work Practices and references NFPA 70E. OSHA 29CFR 1910.335 (a) (1)(i) requires the use of protective equipment when working where a potential electrical hazard exists and 29CFR 1910.132(d)(1) which requires the employer assess the workplace for hazards and the need for personal protective equipment. OSHA compliance is required by any plant building or facility.

2. The National Fire Protection Association (NFPA) Standard 70 -2002 "The National Electrical Code" (NEC) contains requirements for warning labels.

3. NFPA 70E provides guidance on implementing appropriate work practices that are required to safeguard workers from injury while working on or near exposed electrical conductors or circuit parts that could become energized. Part II 2-1.3.3 regarding Arc Flash Analysis states that a "Flash Hazard Analysis shall be done before a person approaches any exposed electrical conductor or circuit part that has not been placed in an electrical safe work condition". This Arc Flash Hazard Analysis must be done to determine the level of Personal Protection Equipment PPE that a worker must use, and the Arc Flash Boundary in inches along with the incident energy found at each location. Each panel must be marked with an ANSI z535 approved Arc Flash Warning Label.

4. The Institute of Electronics and Electrical Engineers (IEEE) 1584 -2002 Guide to Performing Arc-Flash Hazard Calculations

copyright © information by: American Trainco, Inc. http://www.martinarcflash.com

OSHA

Wiha tools assists with compliance of OSHA 29CFR 1910 (Sub Parts electrical standard)



Wiha Insulated Cable Cutters & Pliers

Page **Description** Ir



nsulated	Cable	Cutters	13

Insulated WaterPump Pliers

13



3

10/	iha Insulated Hacksaw	
VV	Description	Page
	-	i age
	Insulated Hacksaw	13
Wibo Incula	ated Bon Un SlimI ino Blad	o Soto
	ated Pop-Up SlimLine Blad Description	Page
wika	Insulated Pop-Up Sets	17
Wiha Insu	llated Pico Finish Screwdri	
	Description	Page
	Insulated Slotted Drivers	20
	Insulated Phillips Drivers	20
	Insulated PicoFinish Sets	20
Wiha	Insulated SlimLine Tools	
	Description	Page
	Insulated SlimLine Handles	18
A	Insulated SlimLine Blade Sets	17-18
	Insulated SlimLine Blades	19
	Insulated SlimLine Drivers	20
	Insulated SlimLine Driver Sets	21
Wiha In	sulated TorqueControl Too	ols
	Description	Page
	Insulated Torque Ratchet	16
		-
Wiha Ins	sulated Pop-Up Insert Bit S	ets
	Description	Page
	Insulated Pop-Up Sets	27-28
Wiha	Insulated Multi-Bit Holders	
	Description	Page
HTT- 8	Insulated Multi-Bit Drivers	27
Wiha Ins	sulated Belt Pack Pouch S	ets
	Description	Page
A A	Insulated Belt Pack Pouches Pliers & Cutters Pliers/Cutters & Screwdrivers Pliers/Cutters & Multi Bit Set	28

W	iha Insulated Tools	
	Description	Page
wiha •	Xeno Terminal Block Combination Screwdrivers	25
	Insulated TorqueControl Handle & Blade Holder	17
wiha	Voltage Detectors	25
	Insulated Hex Inch/Metric T-handles	15
= wiha	Insulated Slotted Drivers	22-23
- 	Insulated Phillips Drivers	22-23
	Insulated Torx [®] Drivers	24
- wiha O	Insulated Nut Drivers	26
🗾 👘 👘	Insulated Pozidriv [®]	25
	Insulated Square Tip	24
	Insulated Tweezers	14

Wiha Insi	ulated 1000Volt Pliers/Cut	ters
	Description	Page
	Insulated Combination Pliers	36
<8	Insulated Heavy Duty Diagonal Cutters	37
	Insulated Pliers	38
	Insulated Stripping Pliers	37
	Insulated Pliers Sets	28-35

Wi	iha Insulated Inomic Plier	S
	Description	Page
-	Insulated Inomic Pliers	39
	Inomic Combo Pliers	
	Inomic Long Nose Pliers	
	Inomic Diagonal Cutters	

Wiha Insulated Industrial Pliers/Cutters Description Page



Wiha Insulated Open-End Wrenches

Insulation Test Standards: Insulation according to ASTM F-1505, EN/IEC 60900, VDE 0680, DIN 7446 and CSA

> Steel Forged from chrome vanadium, meets -**DIN 3110**

High visibility, grip is double coated **☆1000V**

Insulation

Each tool individually tested to 10,000 Volts & certified to 1000 Volt ac or 1500 Volt dc



Angled 15°

\pm 1000Volt

20190	14 Piece Insulated Inch Open					
End Wren	End Wrench Set					
Item	0	OAL	0	OAL	••	
No.	Inch	Inch	Inch	Inch	lbs.	
20190	5/16	3.9	3/4	7.0	5.70	
	3/8	4.1	13/16	7.5		
	7/16	4.6	7/8	7.6		
	1/2	5.5	15/16	7.9		
	9/16	5.7	1	8.4		
	5/8	6.2	1-1/16	9.2		
	11/16	6.5	1-1/8	9.1		



\Rightarrow 1000Volt

20091 15 Piece Insulated Metric Open End Wrench Set OMM OAL Item Омм OAL <u>ب ب</u> No. mm mm mm lbs. mm 20091 6.0 97 14 150 3.0 7.0 98 15 151 8.0 104 16 164 9.0 108 17 162 10.0 107 19 178 11.0 118 22 196 12.0 129 24 211 13.0 137

G

☆1000Volt

201 Inch Open-End Wrenches, With Insulated Handle Insulation According to VDE Specification 0680 and EN/IEC 60900, DIN 7446 and CSA, up to 1000 Volt. Individually Tested. Chrome-vanadium steel, hardened. Angled 15°

narueneu.	/ ligiou				
Item	0	OAL	OAL	•••	
No.	Inch	Inch	mm	lbs.	pkg.
20131	1/4	3.4	87.5	.04	1
20133	5/16	3.9	100	.05	1
20135	3/8	4.1	105	.09	1
20136	7/16	4.6	117	.09	1
20137	1/2	5.5	140	.15	1
20138	9/16	5.7	146	.15	1
20140	5/8	6.2	158	.20	1
20141	11/16	6.5	165	.23	1
20142	3/4	7.0	178	.33	1
20144	13/16	7.5	191	.42	1
20145	7/8	7.6	192	.44	1
20146	15/16	7.9	201	.51	1
20147	1	8.4	213	.61	1
20148	1-1/16	9.2	233	.79	1
20149	1-1/8	9.2	233	.77	1
20151	1-1/4"	7.5		-	1
20154	1-1/2"	7.5			1

* Lengths are +/- 5% due to coating process

☆1000Volt

200 Metric Open-End Wrenches, With Insulated Handle Item Омм OAL OAL 🖵 No. Inch mm mm lbs. pkg. 6.0 97 3.8 20006 .04 1 20007 7.0 98 3.9 .05 1 20008 8.0 104 4.1 .07 1 20009 9.0 108 4.3 .07 1 20010 10.0 107 4.2 .08 1 20011 11.0 118 4.6 .11 1 20012 12.0 129 5.1 .11 1 20013 13.0 137 5.4 .19 1 20014 14.0 150 5.9 .19 1 20015 15.0 151 5.9 .17 1 16.0 .22 20016 164 6.5 1 .24 20017 17.0 168 6.4 1 20018 18.0 173 6.8 .41 1 19.0 178 7.0 .32 20019 1 20.0 .36 20020 190 6.9 1 20022 22.0 196 7.7 .39 1 20024 24.0 211 8.3 .58 1 20027 27.0 218 8.6 .68 1 20030 30.0 235 9.3 .97 1 20032 32.0 237 9.3 1.01 1



lpha1000Volt

20192	8 Piece Insulated Inch Open End
Wrench Se	et

Item	0	OAL	0	OAL	.
No.	Inch	Inch	Inch	Inch	lbs.
20192	5/16	3.9	9/16	5.7	1.59
	3/8	4.1	5/8	6.2	
	7/16	4.6	11/16	6.5	
	1/2	5.5	3/4	7.0	



1000Volt

20093	8 Piec	8 Piece Insulated Metric Open					
End Wren	End Wrench Set						
Item		OAL	Омм	OAL	•••		
No.	mm	mm	mm	mm	lbs.		
20093	6.0	97	13.0	137	1.4		
	7.0	98	14.0	150			
	8.0	104	17.0	162			
	10.0	107	19.0	178			



5

Wiha Insulated Open-End Wrenches



Wiha Insulated Ratchet Wrenches









☆1000Volt

213 Inch Insulated Ratchet Wrenches, With Insulated Handle Insulation According to EN/IEC 60900, ISO 3110 Specification, Up To 1000 Volt. Individually Tested. Blade chrome-vanadium steel, bardened

Blade chrome-vanadium steel, hardened.						
Item	0	OAL	OAL	•••		
No.	Inch	mm	Inch	lbs.	pkg.	
21325	3/8	140	5.5	.14	1	
21327	7/16	143	5.6	.15	1	
21329	1/2	154	6.1	.18	1	
21331	9/16	162	6.4	.22	1	
21333	5/8	177	7.0	.30	1	
21335	3/4	209	8.2	.46	1	

☆1000Volt

212 Metric Insulated Ratchet Wrenches, With Insulated Handle Insulation According to EN/IEC 60900, ISO 3110 Specification, Up To 1000 Volt. Individually Tested. Blade chrome-vanadium steel, hardened.

6

Item	Омм	OAL	OAL	€		
No.	mm	mm	Inch	lbs.	pkg.	
21208	8.0	125	4.9	.08	1	
21210	10.0	140	5.5	.12	1	
21212	12.0	150	5.9	.18	1	
21213	13.0	152	6.0	.18	1	
21214	14.0	163	6.4	.22	1	
21217	17.0	193	7.6	.38	1	
21219	19.0	210	8.3	.45	1	

20196 13 Pc. Insulated Metric Open						
End Wren	End Wrench Set In Tool Box Tray					
Item	0	OAL	0	OAL	₅	
No.	mm	mm	mm	mm	lbs.	
20196	8.0	104	16.0	164	4.90	
	10.0	107	17.0	168		
	11.0	118	18.0	173		
	12.0	129	19.0	178		
	13.0	137	22.0	196		
	14.0	150	24.0	211		
	15.0	151				



21	391	6 Piece Inch Insulated Ratchet
Wre	nches	Set

Item	0	OAL	0	OAL	€€
No.	Inch	Inch	Inch	Inch	lbs.
21391	3/8	5.5	9/16	6.4	1.95
	7/16	5.6	5/8	7.0	
	1/2	6.1	3/4	8.2	
	1/2	0.1	0,4	0.2	



21290	7 Pie	7 Piece Metric Insulated Ratchet						
Wrenches Set								
Item	Омм	OAL	Омм	OAL	•••			
No.	mm	mm	mm	mm	lbs.			
21290	8.0	4.9	14.0	6.4	2.10			
	10.0	5.5	17.0	7.6				
	12.0	5.9	19.0	8.3				
	13.0	6.0						



Toll Free: (800) 494-6104

Wiha Insulated Deep Offset Ring Wrenches







$\pm 1000Volt$

21094	16 Piece Inch Insulated Offset					
Ring Wrenches Set						
Item No.	Inch:	╺┶				
21094	1/4, 5/16, 3/8, 7/16, 1/2,	lbs.				
	9/16, 5/8, 11/16, 3/4,	8.70				
	25/32, 13/16, 7/8, 15/16,					
	1, 1-1/16, 1-1/4"					



210 Insulated Inch Offset Ring

Wrenches	Blade CV	steel, ha	ardened.	
Item	0	÷ •		
No.	Inch	lbs.	pkg.	
21040	1/4	.16	1	
21042	5/16	.18	1	
21044	3/8	.20	1	
21046	7/16	.22	1	
21048	1/2	.30	1	
21050	9/16	.30	1	
21052	5/8	.34	1	
21054	11/16	.34	1	
21056	3/4	.44	1	
21057	25/32	.58	1	
21058	13/16	.52	1	
21060	7/8	.64	1	
21062	15/16	.90	1	
21064	1.0	.96	1	
21066	1-1/16	1.28	1	
21068	1-1/4	1.38	1	

1000Volt



 21095
 8 Piece Metric Insulated Offset

 Ring Wrenches Set
 Item No.
 Metric:

 21095
 10.0, 11.0, 12.0, 13.0,
 Ibs,

 14.0, 15.0, 17.0, 19.0mm
 3.20



☆1000Volt

 21093
 16 Piece Metric Insulated Offset

 Ring Wrenches Set

 Item No.
 Metric:

21093	8.0, 9.0, 10.0, 11.0, 12.0, 13.0,
•••	14.0, 15.0, 17.0, 19.0, 20.0, 22.0,
lbs. 8.70	24.0, 27.0, 30.0, 32.0mm



210 Insulated Metric Offset Ring Wrenches, Insulation According to EN/IEC 60900, ISO 3110 Specification, Up To 1000 Volt. Individually Tested. Blade Chrome-Vanadium steel, hardened.

vanadium steel, nardened.						
Item	Омм	OAL	OAL	•••		
No.	mm	mm	Inch	lbs.	pkg.	
21008	8.0	159	6.3	.16	1	
21009	9.0	159	6.3	.18	1	
21010	10.0	171	6.8	.20	1	
21011	11.0	178	7.0	.22	1	
21012	12.0	191	7.5	.30	1	
21013	13.0	194	7.6	.30	1	
21014	14.0	203	8.0	.34	1	
21015	15.0	203	8.0	.34	1	
21017	17.0	219	8.6	.44	1	
21019	19.0	241	9.5	.52	1	
21020	20.0	250	9.8	.58	1	
21022	22.0	257	10.1	.64	1	
21024	24.0	279	11.0	.90	1	
21027	27.0	286	11.3	.96	1	
21030	30.0	311	12.3	1.28	1	
21032	32.0	318	12.5	1.38	1	

Use & Care Guide For Insulated Tools:

Store tools to minimize risk of damage to insulation, always wear approved eye protection, Inspect insulation prior to each use of any insulated tool. Use insulated tools where the ambient temperature is between -20 to +70° C. Have a qualified safety technician visually inspect insulation on tools annually for safe use.



7

Wiha Insulated Adjustable Wrenches



76208 Insulated 8" Adjustable Wrench Insulation According to ASTM, EN/IEC, NFPA, CSA and ISO Specification, up to 1000 Volt. Individually Tested. Etched on scale for pre-setting size. Slip guard handle for added protection. Item OAL OAL Capacity 🕁 🛲

No.	Inch	mm	Opening	lbs.	pkg.	
76208	8.0	200	1"	.7	1	

☆1000Volt

76210	Insulated 10" Adjustable Wrench					
Etched on scale for pre-setting size.						
Slip guard	Slip guard handle for added protection.					
Item	OAL	OAL	Capacity	.		
No.	Inch	mm	Opening	lbs.	pkg.	
76210	10.0	250	1-1/4"	1.4	1	

1000Volt

76212	Insul	ated 1	2" Adjusta	able \	Vrench	
Etched on scale for pre-setting size.						
Slip guard	handle	for ad	lded protect	tion.		
Item	OAL	OAL	Capacity	•••		
No.	Inch	mm	Opening	lbs.	pkg.	
76212	12.0	300	1-1/2"	1.9	1	

☆1000Volt

76215	Insulated 15" Adjustable Wrench						
Etched on scale for pre-setting size.							
Slip guard	handle	for ad	ded protect	ion.			
Item	OAL	OAL	Capacity	₅⊸			
No.	Inch	mm	Opening	lbs.	pkg.		
76215	15.0	380	1-11/16"	2.8	1		



m1000Volt

76290	3 Pc. Insulated Adjustable
Wrenches	Etched on scale for pre-setting
size. Slip g	uard handle for added protection.
Item No.	Set includes the following:
76290	8.0", 10.0", 12.0" Adjustable Pliers
⋰	lbs. 4.0

Wiha Insulated Electrician's Knives



Each tool individually tested to 10,000 volts & rated to 1000Volt ac or 1500Volt dc





1000Volt

15000 Insulated Electrician's Cable Stripping Knife, With Insulated Handle, Insulation According To VDE Specification, Up To 1000 Volt. Individually Tested. Blade tool steel, hardened, molded directly on. Cover included.

Item	Blade	OAL	OAL	•••		
No.	mm	mm	Inch	lbs.	pkg.	
15000	50	216	8.5	.30	1	

35

15050

15050 Insulated Stripping Knife, With Insulated Handle Insulation According To VDE Specification, Up To 1000 Volt. Individually Tested. Blade tool steel, hardened. Insulation molded directly on. Hooked cutting edge, half-round ground. Cover included. Item No. mm mm Inch Ibs. pkg.

222 8.75 .22 1

1000Volt

15003 Insulated Electrician's Cable Stripping Knife, With Insulated Handle, Insulation According To VDE Specification, Up To 1000 Volt. Individually Tested. Straight, partly insulated, strong blade.

Insulation molded directly on. Cover included.						
Item	Blade	OAL	OAL	•••		
No.	mm	mm	Inch	lbs.	pkg.	
15003	50	230	9.0	.23	1	

WARNING!

Insulated Tools are intended to provide protection against accidental contact with charged energized circuits. For maximum safety we recommend de-energizing all circuits whenever possible before starting work on electrical apparatus or conductors. Always visually inspect insulation on tools before use, do not use tools if insulation shows signs of wear or damage to the insulated areas of the tool. Wear appropriate eye protection when using hand tools. Use NFPA70E certified insulated protective outer wear when appropriate.





136 Inch Insulated Hex L-keys, With Insulated Handle. Insulation According to IEC 60900 Specification, Up To 1000 Volt. Individually Tested. Blade chrome-vanadium steel, hardened.

01001, 11010					
Item	0	OAL	OAL	•••	-
No.	Inch	mm	Inch	lbs.	pkg.
13670	1/16	79	3.1	.05	1
13671	5/64	84	3.3	.05	1
13672	3/32	89	3.5	.05	1
13673	7/64	94	3.7	.06	1
13663	1/8	104	4.1	.06	1
13665	5/32	104	4.1	.06	1
13666	3/16	134	5.3	.10	1
13667	7/32	134	5.3	.12	1
13668	1/4	134	5.3	.16	1
13669	5/16	144	5.7	.24	1
13662	3/8	234	9.2	.51	1
13664	1/2	234	9.2	.77	1

Wiha Insulated Hex L-keys





8 Piece Insulated Inch Hex 13690 L-key Set Item OAL OAL • • 0 0 No. Inch Inch lbs. Inch Inch 1/8 4.1 1/4 5.3 2.17 13690 5/32 4.1 5/16 5.7 3/16 5.3 3/8 9.2 7/32 5.3 1/2 9.2



13694	12 Pc	12 Pc. Insulated Inch Hex L-key Set				
Item	0	OAL	0	OAL	÷.	
No.	Inch	Inch	Inch	Inch	lbs.	
13694	1/16	3.1	3/16	5.3	2.40	
	5/64	3.3	7/32	5.3		
	3/32	3.5	1/4	5.3		
	7/64	3.7	5/16	5.7		
	1/8	4.1	3/8	9.2		
	5/32	4.1	1/2	9.2		
-						



136 Metric Insulated Hex L-keys, With Insulated Handle. Insulation According to IEC 60900 Specification, Up To 1000 Volt. Individually Tested. Blade chrome-vanadium steel, hardened

steel, harde	enea.				
Item	Омм	OAL	OAL	• •	
No.	mm	mm	Inch	lbs.	pkg.
13650	1.5	100	3.9	.09	1
13651	2.0	105	4.1	.09	1
13652	2.5	115	4.5	.09	1
13653	3.0	130	5.1	.10	1
13654	4.0	120	4.7	.10	1
13655	5.0	140	5.5	.10	1
13656	6.0	140	5.5	.13	1
13658	8.0	150	5.9	.24	1
13659	10.0	220	8.7	.51	1
13657	12.0	260	10.2	.77	1



☆ 1000Volt 7 Piece Insulated Metric Hex 13691 L-key Set

Item	Омм	OAL	Омм	OAL	.
No.	mm	mm	mm	mm	lbs.
13691	3.0	130	8.0	150	2.07
	4.0	120	10.0	220	
	5.0	140	12.0	260	
	6.0	140			
			•		



13693	10 Pi	10 Piece Insulated Metric Hex					
L-key Set							
Item		OAL	Омм	OAL	÷.		
No.	mm	mm	mm	mm	lbs.		
13693	1.5	100	5.0	140	2.26		
	2.0	105	6.0	140			
	2.5	115	8.0	150			
	3.0	130	10.0	220			
	4.0	120	12.0	260			



9

Wiha Insulated **Hex Bit Sockets**

				☆1000Volt
318	Insulat	ed 3/8"	Drive	Sockets
Chrome-	vanadium	steel, fo	rged, o	il-hardened.
Item		OAL	•••	
No.	Inch	Inch	lbs.	pkg.
31805	3/16	3.1"	.13	1
31807	7/32	3.1"	.14	1
31809	1/4	3.1"	.14	1
31811	5/16	3.1"	.16	1
31813	3/8	3.1"	.18	1
31815	7/16	3.1"	.20	1
31817	1/2	3.1"	.22	1

*Sockets must be used with insulated ratchets & extensions



7 Pc. Insulated 3/8" Drive Socket 31890 Set - Inch CV steel, forged, oil-hardened sockets. Insulated to EN/IEC 60900. Set includes the following: Item No. 31890 3/16, 7/32, 1/4, 5/16, 3/8, lbs. 1.7 7/16, 1/2"





*Sockets must be used with insulated ratchets & extensions

Wiha Insulated Socket Adapters / Reducers



#31650

Insulated Socket Adapters / Reducers CV

steel, forged, oil-hardened.						
Item		• •	-			
No.	Size	lbs.	pkg.			
31350	1/4 - 3/8		1			
31450	3/8 - 1/2		1			
31460	3/8 - 1/4		1			
31650	1/2 - 3/8		1			

Wiha Insulated 1/4" Sockets, Accessories & Sets



313 Insulated 1/4" Drive Sockets-6 Point, Insulation According To ASTM F-1505, DIN 7448 & CSA Specification, Up To 1000 Volt. Individually Tested. Chromevanadium steel, forged, oil-hardened.

vanadiani	stool, longo	a, on n	al dollou.	
Item		€		
No.	Inch	lbs.	pkg.	
31336	3/16	.03	1	
31337	7/32	.03	1	
31338	1/4	.03	1	
31339	9/32	.04	1	
31340	5/16	.04	1	
31341	11/32	.05	1	
31342	3/8	.05	1	
31343	7/16	.06	1	
31344	1/2	.07	1	
31345	9/16	.07	1	

*Sockets must be used with insulated ratchets & extensions



31390	13 Pc Insulated 1/4" Drive Socket
Set - Inch	CV steel, forged, oil-hardened
sockets. I	nsulated after EN/IEC 60900.
Item No.	Set includes the following:
31390	3/16, 7/32, 1/4, 9/32, 5/16, 11/32,
.	3/8, 7/16, 1/2, 9/16"
lbs. 1.39	1/4" x 50mm Extension Bar
	1/4" x 100mm Extension Bar
	1/4" Ratchet - 140mm



313	Insulated	1/4"	Drive Sockets-6				
Point, Insulation According							
Chrome-	Chrome-vanadium steel, forged, oil-hardened.						
Item		•••					
No.	mm	lbs.	pkg.				
31326	5.0	.03	1				
31327	6.0	.03	1				
31328	7.0	.03	1				
31329	8.0	.04	1				
31330	9.0	.04	1				
31331	10.0	.05	1				
31332	11.0	.05	1				
31333	12.0	.06	1				
31334	13.0	.06	1				
31335	14.0	.07	1				

*Sockets must be used with insulated ratchets & extensions



31391 13 Pc. Insulated 1/4" Drive Socket Set - Metric CV steel, forged, oil-hardened sockets. Insulated after EN/IEC 60900. Item No. Set includes the following: 31391 5, 6, 7, 8, 9, 10, 11, 12, 13, 14mm ••• 1/4" x 50mm Extension Bar 1/4" x 100mm Extension Bar lbs. 1.41 1/4" Ratchet - 140mm



Toll Free: (800) 494-6104

Wiha Insulated 1/4" Sets & Accessories



☆1000Volt

 31394
 11 Pc. Insulated 1/4" T-handle &

 Socket Set-Inch CV steel, forged, oil-hardened
 sockets. Insulated after EN/IEC 60900.

 Item No.
 Set includes the following:

 31394
 3/16, 7/32, 1/4, 9/32, 5/16, 11/32,

 ↓
 3/8, 7/16, 1/2, 9/16"

 Ibs. 1.40
 Insulated 1/4" T-handle

Each tool individually tested to 10,000 volts & certified to 1000Volt ac or 1500Volt dc







 Insulated 1/4" Drive Ratchet,

 EN/IEC 60900 & CSA
 Chrome-Vanadium

 steel. Thumb lever for rapid reverse.

 Item
 OAL
 OAL
 Image: Colored colo

☆1000Volt

29006 Insulated 1/4" Drive T-handle, With Insulated Handle. Insulation according to EN/IEC 60900 & CSA specification, up to 1000 Volt. Individually Tested. Blade CV steel, hardened.

Item		OAL	OAL	•••	
No.	Inch	mm	Inch	lbs.	pkg.
29006	1/4	160	6.2"	.57	1



128	Insulated 1/4" Extension Bars,					
ASTM F-1505, EN/IEC 60900 & CSA						
Chrome-Vanadium steel.						
Item		OAL	OAL	•••		
No.	Inch	mm	Inch	lbs.	pkg.	
12854	1/4"	50	2.0	.08	1	
12855	1/4"	100	3.9	.12	1	

Wiha Insulated 3/8" Sockets



lpha1000Volt

314Insulated 3/8" Drive Sockets -Insulation according to EN/IEC 60900, DIN7448 & CSA specification, up to 1000 Volt.Individually Tested.

CV steel, forged, oil-hardened.						
Item		÷.				
No.	Inch	lbs.	pkg.			
31425	1/4	.07	1			
31428	9/32	.07	1			
31429	5/16	.07	1			
31430	11/32	.07	1			
31431	3/8	.08	1			
31432	7/16	.08	1			
31433	1/2	.10	1			
31434	9/16	.10	1			
31435	5/8	.10	1			
31436	11/16	.13	1			
31437	3/4	.14	1			
31438	13/16	.17	1			
31439	7/8	.18	1			

*Sockets must be used with insulated ratchets & extensions



☆1000Volt

315Insulated 3/8" Drive Sockets-Metric Insulation according to VDE, EN/IEC60900, DIN 7448 & CSA specification, upto 1000 Volt. Individually Tested. Chrome-vanadium steel, forged, oil-hardened.

vanadium s	steel, torge	ea, oli-na	iraenea.	
Item		€		
No.	mm	lbs.	pkg.	
31506	6.0	.07	1	
31507	7.0	.07	1	
31508	8.0	.07	1	
31509	9.0	.07	1	
31510	10.0	.07	1	
31511	11.0	.08	1	
31512	12.0	.10	1	
31513	13.0	.10	1	
31514	14.0	.10	1	
31515	15.0	.10	1	
31516	16.0	.10	1	
31517	17.0	.11	1	
31518	18.0	.12	1	
31519	19.0	.14	1	
31520	20.0	.15	1	
31521	21.0	.17	1	
31522	22.0	.18	1	
31524	24.0	.26	1	



Wiha Insulated 3/8" Sockets & Sets



 31493
 10 Pc. Insulated 3/8" Drive Socket

 Set - Inch
 CV steel, forged, oil-hardened

 sockets.
 Insulated to EN/IEC 60900.

 Item No.
 Set includes the following:

 31493
 5/16, 3/8, 7/16, 1/2,

 • •
 9/16, 5/8, 11/16, 3/4"

 Ibs. 2.50
 3/8" x 125mm Extension Bar

 3/8" Ratchet - 190mm



31590	10 Pc. Insulated 3/8" Drive Socket				
Set - Metr	Set - Metric CV steel, forged, oil-hardened				
sockets. I	nsulated to EN/IEC 60900.				
Item No.	Set includes the following:				
31590	8, 10, 11, 12, 13, 14, 17, 19mm				
.	3/8" x 125mm Extension Bar				
lbs. 2.50	3/8" Ratchet - 190mm				



31491	16 Piece Insulated 3/8" Drive		
Socket Se	t - Inch/Metric CV steel, forged, oil-		
hardened sockets. Insulated to EN/IEC 60900.			
Item No.	Set includes the following:		
31491	5/16, 3/8, 7/16, 1/2,		
÷÷	9/16, 5/8, 11/16, 3/4"		
lbs. 2.01	8, 10, 11, 12, 13, 14, 17, 19mm		



31495 24 Pc. Insulated 3/8" Drive Socket Set - Inch CV steel, forged, oil-hardened sockets. Insulated to EN/IEC 60900. Item No. Set includes the following: 31495 1/4, 9/32, 5/16, 11/32, 3/8, 7/16 ••• 1/2, 9/16, 5/8,11/16, 3/4" Sockets 3/8" x 125mm Extension Bar lbs. 9.07 3/8" x 250mm Extension Bar 3/8" Ratchet - 190mm Insulated Electrician's Knife - 50mm Slotted: 3.5, 4.5, 6.5mm Phillips: #1, 2, 3 6.3" Long Nose Pliers 8.0" Combo Pliers 6.3" Diagonal Cutters *Sockets must be used with insulated ratchets & extensions



31592 24 Pc. Insulated 3/8" Drive Socket Set - Metric CV steel, forged, oil-hardened sockets. Insulated to EN/IEC 60900. Item No. Set includes the following: 31592 6, 7, 8, 9, 10, 11, 12, 13, 14, 17, 19mm Sockets lbs. 3/8" x 125mm Extension Bar 9.08 3/8" x 250mm Extension Bar 3/8" Batchet - 190mm Insulated Electrician's Knife - 50mm Slotted: 3.5, 4.5, 6.5mm Phillips: #1, 2, 3 6.3" Long Nose Pliers 8.0" Combo Pliers 6.3" Diagonal Cutters

*Sockets must be used with insulated ratchets & extensions



12852	Insu	ated 3	8/8" D	rive F	Ratchet,	
EN/IEC 60900 CV steel. Socket release						
button. Thumb lever for rapid reverse.						
Item		OAL	OAL	<u>ب</u>		
No.	Inch	mm	Inch	lbs.	pkg.	
12852	3/8"	190	7.5	.93	1	



31496 10 Pc. Insulated 3/8" T-handle & Socket Set-Inch CV steel, forged, oil-hardened sockets. Insulated after EN/IEC 60900.

Set includes the following:			
5/16, 3/8, 7/16, 1/2, 9/16, 5/8,			
11/16, 3/4"			
3/8" x 125mm Extension Bar			
Insulated 3/8" T-handle			

31595	10 Pc. Insulated 3/8" T-handle &				
Socket Set - MM CV steel, forged, oil-hardened					
sockets. In	sulated after EN/IEC 60900.				
Item No.	Set includes the following:				
31595	8, 10, 11, 12, 13, 14, 17, 19mm				
• ` •	3/8" x 125mm Extension Bar				
lbs. 2.47	Ins. 3/8" T-handle				

Wiha Insulated 3/8" Socket Accessories



128	Insulat	ed 3/8'	' Exte	nsion	Bars,	
EN/IEC 60900 Chrome-Vanadium steel.						
Item		OAL	OAL	.		
No.	Inch	mm	Inch	lbs.	pkg.	
12856	3/8"	125	4.9	.41	1	
12857	3/8"	250	9.8	.57	1	



1000VoltInsulated 3/8" Drive T-handle OrBreaker Bar. Insulation according toEN/IEC 60900 specification, up to 1000VoltRated. Individually Tested.Blade chrome-vanadium steel, hardened.

vanaulum st	eei, na	liueneu	J.		
Item	Омм	OAL	OAL	••	-
No.	Inch	mm	Inch	lbs.	pkg.
29009	3/8	200	7.9"	.55	1
12327	3/8	216	8.5"	.68	1



Wiha Insulated 1/2" Sockets & Sets

☆1000Volt

317 Insulated 1/2" Drive Sockets -Insulation According to ASTM, DIN & CSA Specification, Up To 1000Volt. Individually Tested. CV steel, forged, oil-hardened.

	ov stoci, iorge	a, on ne	aluciteu.
Item		÷÷	
No.	Inch	lbs.	pkg.
31703	5/16	.16	1
31704	11/32	.16	1
31705	3/8	.16	1
31707	7/16	.16	1
31708	1/2	.16	1
31709	9/16	.17	1
31710	5/8	.19	1
31712	11/16	.19	1
31713	3/4	.21	1
31714	13/16	.23	1
31715	7/8	.27	1
31716	15/16	.35	1
31718	1	.33	1
31720	1-1/8	.44	1
31722	1-1/4	.58	1
*Sockets m	nust be used with in	sulated ra	atchets & extensions



$\pm 1000Volt$

316	Insulated 1/2'	' Drive	Sockets -
Metric	1000 Volt.		
Item		••	-
No.	mm	lbs.	pkg.
31608	8.0	.15	1
31609	9.0	.15	1
31610	10.0	.16	1
31611	11.0	.16	1
31612	12.0	.16	1
31613	13.0	.17	1
31614	14.0	.17	1
31615	15.0	.17	1
31616	16.0	.19	1
31617	17.0	.19	1
31618	18.0	.20	1
31619	19.0	.21	1
31620	20.0	.25	1
31621	21.0	.25	1
31622	22.0	.28	1
31623	23.0	.29	1
31624	24.0	.30	1
31626	26.0	.37	1
31627	27.0	.41	1
31628	28.0	.44	1
31630	30.0	.51	1
31632	32.0	.55	1



\Box	
31790	24 Piece Insulated 1/2" Drive
Socket Se	et - Inch CV steel, forged, oil-
hardened	sockets. Insulated to EN/IEC 60900.
Item No.	Set includes the following:
31790	3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4,
	13/16, 7/8, 15/16, 1" Sockets
₅⁺₽	1/2" x 125mm Extension Bar
lbs.	1/2" x 250mm Extension Bar
11.41	1/2" Ratchet - 260mm
	Ins. Electrician's Knife - 50mm
	Slotted: 3.5, 4.5, 6.5mm
	Phillips: #1, 2, 3
	6.3" Long Nose Pliers
	8.0" Combo Pliers
	6.3" Diagonal Cutters

Each tool individually tested to 10,000 volts & certified to 1000Volt ac or 1500Volt dc



☆1000Volt

31691	24 Piece Insulated 1/2" Drive
Socket Se	et - Metric CV steel, forged, oil-
hardened	sockets. Insulated to EN/IEC 60900.
Item No.	Set includes the following:
31691	8, 9, 10, 12, 13, 14, 15, 17,
	19, 22, 24mm Sockets
₅⁺ъ	1/2" x 125mm Extension Bar
lbs.	1/2" x 250mm Extension Bar
11.39	1/2" Ratchet - 260mm
	Ins. Electrician's Knife - 50mm
	Slotted: 3.5, 4.5, 6.5mm
	Phillips: #1, 2, 3
	6.3" Long Nose Pliers
	8.0" Combo Pliers
	6.3" Diagonal Cutters

☆1000Volt



31792	14 Pc. Insulated 1/2" Drive Socket
Set - Inch	CV steel, forged, oil-hardened
sockets. In	sulated to EN/IEC 60900.
Item No.	Set includes the following:
31792	3/8, 7/16, 1/2, 9/16, 5/8, 11/16,
<u>⊷</u> ٹی	3/4, 13/16, 7/8, 15/16, 1"
lbs.	1/2" x 125mm Extension Bar
7.64	1/2" x 250mm Extension Bar
	1/2" Ratchet - 190mm



$\pm 1000Volt$

31694	14 Pc. Insulated 1/2" Drive
Socket Set	t - Metric CV steel, forged, oil-
hardened s	sockets. Insulated to EN/IEC 60900.
Item No.	Set includes the following:
31694	8, 9, 10, 11, 12, 13, 14,
• ` •	17, 19, 22, 24mm
lbs.	1/2" x 125mm Extension Bar
7.64	1/2" x 250mm Extension Bar
	1/2" Ratchet - 190mm

Each tool individually tested to 10,000 volts & certified to 1000Volt ac or 1500Volt dc

*Sockets must be used with insulated ratchets & extensions



Wiha Insulated 1/2" Socket accessories



12853	Insi	ulated	1/2" I	Drive	Ratchet,	
IEC/EN 60900 & CSA						
Chrome-Va	anadiu	im stee	el. Rev	ersible	e.	
Item		OAL	OAL	₅⁺₽		
No.	Inch	mm	Inch	lbs.	pkg.	
12853	1/2"	260	10.2	1.55	1	



128 Insulated 1/2" Extension Bars,

OAL OAL 🖵

125 4.9

250 9.8

Inch Ibs. pkg.

1

.45 1

.91 1

EN/IEC 60900 & CSA

Chrome-vanadium steel.

Inch mm

1/2"

1/2"

Item

No.

12858

12859

Wiha Insulated Hacksaw



Uses standard 12" blade

☆1000Volt

19767 Hacksaw, With Insulated Handle Insulation According to EN/IEC 60900, DIN ISO, ASTM & CSA Specification, Up To 1000 Volt. Individually Tested. OAL OAL -Item No. mm Inch lbs. pkg. 19767 457mm 18.0" 1.92 1

Insulated Cable Cutters



For cutting solid aluminum & copper conductors

11950Cable Cutter, With InsulatedHandle. Insulation According to EN/IEC,ASTM & CSA Specification, Up To 1000Volt. Individually Tested. Blade alloyed toolsteel. Induction hardened.

Item	OAL	OAL	Cap	acity	•••	
No.	mm	Inch	mm	Inch	lbs.	pkg.
11950	500	19.6	12	1/2"	3.0	1

Insulated Waterpump Pliers



m m m m 1000Volt

29240 Waterpump Pliers, With Insulated Handle. Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification, Up To 1000 Volt. Individually Tested Box joint. Chromevanadium steel, drop forged, oil hardened. Item OAL OAL Capacity No. Inch pkg. mm mm lbs. 29240 240 7/8" 9.5 1.1 1

For cutting multi strand aluminum & copper cables

40800 Large Capacity Cable Cutter, With Insulated Handle Insulation According to EN/IEC 60900, ASTM F-1505 & CSA Specification, Up to 1000 Volt. Individually Tested. Easy cutting blades, dropped forged, oil hardened. Cuts cable diameters up to 50mm. Not to be used on steel rods.

Item	OAL	OAL	Cap	acity	• ` •	
No.	mm	Inch	mm	Inch	lbs.	pkg.
40800	800	31.5	50	2"	8.0	1



alloyed tool steel. Induction hardened.					
Item	OAL	OAL	Capacity	ず→	
No.	mm	Inch	mm	lbs.	pkg.
29250	250	10	7/8"	1.1	1

	A 1000Volt
29012	Insulated 1/2" Drive T-handle,

With Insulated Handle. Insulation according to EN/IEC 60900 & CSA Specification, Up To 1000 Volt. Individually Tested Blade VC steel, hardened. Item OMM OAL OAL ÷ ۰. No. Inch mm Inch lbs. pkg. 29012 1/2 200 7.9" .68 1



12326 Insulated 1/2" Drive Breaker Bar,

IEC/EN 60900 & CSA										
Chrome-Vanadium steel.										
Item		OAL	OAL	•••						
No.	Inch	mm	Inch	lbs.	pkg.					
12326	1/2"	267	10.5	1.04	1					



((104) Toll Free: (800) 494-6104

Wiha Insulated Ratcheting Cable Cutters

Each tool individually tested to 10,000 Volts & certified to 1000 Volt ac or 1500 Volt dc



\pm 1000Volt

119High Voltage Double-InsulatedRatcheting Cable CuttersHigh leverageratchet cable cutter with shear type blades cutsstranded and flexible copper and aluminumcable. Not for use on steel. Features built insafety release in all cutting positions, andhigh-visibility comfort grip handles.

Item	OAL	OAL	up to	Inch		• ` •
No.	mm	Inch	MCM	Dia.	Cap.	lbs.
11960	250	10.0"	500	1.25"	32ml	1.6
11975	280	11.0"	750	2.0"	52ml	2.0



☆1000Volt

11980 Insulated ACSR Ratcheting

Cable Cutter Replaceable tool steel cutting blades are securely mounted for accurate cutting. Handles lock in closed position for easier storage. High leverage ratchet mechanism for best cutting performance.

Item	OAL	OAL	up to	Inch		.
No.	mm	Inch	MCM	Dia.	Cap.	lbs.
11980	353	13.9	477	1.25"	32ml	3.42





75205	Insulated Serrated Straight										
Fine Tip Tweezers, IEC/EN 60900 & CSA											
Standards	, 10,000) Volt T	ested								
Item	OAL	OAL	•••	-							
No.	mm	Inch	lbs.	pkg.							
75205	130	5.0	.06	1							

1000Volt

75220	Insulated Serrated Straight										
Blunt Tip Tweezers, IEC/EN 60900 & CSA											
Standards	Standards, 10,000 Volt Tested										
Item	OAL	OAL	•••								
No.	mm	Inch	lbs.	pkg.							
75220	200	8.0	.18	1							



	on										
75210	Insulat	Insulated Serrated Straight									
Blunt Tip Tweezers, IEC/EN 60900 & CSA											
Standards	s, 10,000) Volt T	ested								
Item	OAL	OAL	•••								
No.	mm	Inch	lbs.	pkg.							

5.0

.08 1

130



lpha1000Volt

75302	Insulated Serrated Angled										
Fine Tip Tweezers, IEC/EN 60900 & CSA											
Standards	Standards, 10,000 Volt Tested										
Item	OAL	OAL	•••								
No.	mm	Inch	lbs.	pkg.							
75302	145	6.0	.08	1							



1000Volt

75210

75215	215 Insulated Serrated Straight										
Blunt Tip Tweezers, IEC/EN 60900 & CSA											
Standards	Standards, 10,000 Volt Tested										
Item	OAL	OAL	•••								
No.	mm	Inch	lbs.	pkg.							
75215	145	6.0	.10	1							



<u>☆1000V</u>olt

75304 Insulated Serrated Angled Blunt Tip Tweezers, IEC/EN 60900 & CSA Standards, 10,000 Volt Tested

Standards,	10,00	U VOIL	reste	a	
Item	OAL	OAL	•••	P	
No.	mm	Inch	lbs.	pkg.	
75304	200	8.0	.16	1	





33478	5 Piece Metric T-ha	ndle Hex Set
Item	Metric:	₊⁺₊
No.	4.0, 5.0, 6.0,	lbs.
33478	8.0. 10.0mm	1.20

Wiha Insulated T-handle Metric Nut Drivers

7.1

7.1

7.5

.18

.26

.46

10

10

10



5.9

5.9

5.9

182

182

191

33445

33447

33449

6.0

8.0

10.0

150

150

150

onto biado.	Wind C		nunuit	, mana c	ompone			
Item	0))			.		
No.	mm	mm	Inch	mm	Inch	lbs.	pkg.	
33632	8.0	200	7.9	232	9.1	.15	5	
33634	10.0	230	9.0	262	10.3	.18	5	
33637	13.0	230	9.0	262	10.3	.26	5	
33641	17.0	230	9.0	268	10.6	.46	5	



Wiha Insulated Torque **Ratchet Wrenches**



301 **Insulated Torque Ratchet** Wrenches, 1/4, 3/8, 1/2" Drives Insulated to EN/IEC 60900:2004, ASTM F1505, CSA Standards Visible reading scale for easy reading and adjustment. Locking endcap Torque adjuster for easy adjustment. Accuracy +/- 10%. Dual scale reading Ft. lbs. / Nm.

Item		OAL	OAL		•••	
No.	Inch	mm	Inch	Nm	lbs.	pkg.
30114	1/4"	210	8.25	5-25	1.02	1
30138	3/8"	370	14.5	5-50	2.72	1
30152	1/2"	530	21.0	40-220	3.64	1

In Roll-up Pouch 1000Volt

28792 16 Piece Insulated **TorqueControl Set With SlimLine Blades** Certified to EN ISO 6798. BS EN 26789. ASME B107.14M. Set includes Insulated multicomponent adjustable TorqueVario-S handle, 13 SlimLine blades, SlimLine blade holder & Torque adjustment tool. Item No.

SlimLine Slotted: 4.0, 5.5, 6.5mm 28792 SlimLine Phillips: #1, 2 SlimLine Terminal Xeno: #1, 2 SlimLine **TORX***: T8, T10, T15, T20 SlimLine Square: #1, 2 28727 - Handle Range 18-62 Inch/lbs. SlimLine Blade Holder **↓** Ibs. 1.27

With Certificate of Calibration

Wiha Insulated Torque Ratchet Wrench Sets



	UIL
30190	16 Pc. Insulated 3/8" Drive
Ratchetin	g Torque Wrench & Socket Set -
Inch CV	steel, forged, oil-hardened
sockets. In	nsulated to EN/IEC 60900.
Item No.	Inch 3/8" Drive Sockets:
30190	1/4, 9/32, 5/16, 11/32, 3/8, 7/16
• •	1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8"
lbs.	3/8" x 125mm Extension Bar
8.80	3/8" x 250mm Extension Bar
	3/8" Drive Ratcheting Torque
	Wrench - 5-50 Nm

*Sockets must be used with insulated ratchets & extensions



m lpha1000Volt

30192 16 Pc. Insulated 3/8" Drive **Ratcheting Torque Wrench & Socket Set -**Metric CV steel, forged, oil-hardened sockets. Insulated to EN/IEC 60900. Item No. Metric 3/8" Drive Sockets: 30192 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20mm lbs. 3/8" x 125mm Extension Bar 8.80 3/8" x 250mm Extension Bar 3/8" Drive Ratcheting Torque Wrench - 5-50 Nm

*Sockets must be used with insulated ratchets & extensions



Certified to EN ISO 6798, BS EN 26789, ASME B107.14M Specifications



28791 8 Piece Insulated TorqueControl Set With Slotted & Phillips SlimLine Blades Set includes Insulated multi-component adjustable TorqueVario-S handle, 5 SlimLine blades, SlimLine blade holder & Torque adjustment tool. Item No. Slotted: 3.0, 4.0, 5.5mm

28791	Phillips: #1, 2
	28726-Handle Range 10-50 Inch/lbs.

+ → lbs. .87

Wiha Insulated TorqueControl Tools



Includes SlimLine blade holder #28350



lpha1000Volt

Insulated TorqueVario-S, With 287 Window Scale Insulation 4 up to 1000Volt EN/IEC, EN ISO, BS EN, ASME & CSA, +/- 6% Accuracy. Ergonomic multi-component handle, light & compact. Handle sizes proportioned to optimize torque range. Audible & perceptible click when torque setting has been attained. In Plastic Tube Holder

Seen anan							
ltem	Range			=		•	
No.	Inch I	bs.	Increments	mm	I	bs.	pkg.
28750	5 - 1	18	.5 In/lbs	126-13	31.	56	1
28751	10 - 5	50	2 In/lbs	133-13	38.	74	1
28752	18 - 6	62	2 In/lbs	137-14	42.	84	1
287	Ins	sula	ted Torq	ueVa	rio-	s	
Handle - I	n Nev	vton	Meter S	cale			
Item	Ra	nge			-		
No.	N	m	mm	lbs.	pkg.		
28740	0.5	- 2.0	131	.64	1		
28741	1.0	- 5.0	138	.56	1		
28742	2.0	- 7.0	142	.84	1		

Each TorqueVario handle has unique serial number & certificate of calibration

Wiha Insulated TorqueControl & SlimLine Tool Sets



Wiha Insulated TorqueControl Tools

Includes Certificate



*Requires SlimLine blade holder #28350

	i torque o	oung nuo	been a	littuinte	<i>.</i>
Item	Range			•••	
No.	Inch Ibs.	Increments	mm	lbs.	pkg.
28724	5 - 18	.5 In/lbs	126-131	.43	1
28726	10 - 50	2 In/lbs	133-138	.40	1
28727	18 - 62	2 In/lbs	137-142	.69	1
287	Insulated	Torque	/ario-S	Hand	lle -
In Newto	n Meter S	Scale			
Item	Range			-	
No.	Nm	mm	lbs. pl	kg.	
28734	0.5 - 2.0	0 131	.45	1	
28736	1.0 - 5.0	0 138	.45	1	
28738	2.0 - 7.0	0 142	.72	1	

Each TorqueVario handle has unique serial number & certificate of calibration

A1000Volt

28350	Insulated SlimLine Torque
Blade Hole	der Chrome-vanadium-molybdenum
steel. Through hardened black finish. ClicFix	
quick release	se holder securely locks bits.

Item		OAL	OAL	•••	
No.	mm	mm	Inch	lbs.	pkg.
28350	6.0	170	6.75	.06	1



Meets VDE, EN/IEC, ASTM, CSA, NFPA specifications



lpha1000Volt

283 Insulated Easy-TorqueControl

Adapters Ideal for torque sensitive

aniba wihn

terminations. For use with SlimLine blades. Repeatable accuracy to +/- 10%

ricpeutubl	0 400	uluoy	10 17	10/0			
Item			OAL	OAL	•••		
No.	Nm	In/lbs	mm	Inch	lbs.	pkg.	
28366	0.8	7.0	60	2.38	.13	1	
28367	2.0	17.7	60	2.38	.13	1	
28368	2.5	23.1	60	2.38	.13	1	
28369	2.8	24.7	60	2.38	.13	1	
28371	4.0	35.4	60	2.38	.13	1	

Wiha Cushion Grip Stubby SlimLine Blade Holder & Set



 \bigcirc

28302

 28302
 SlimLine Stubby Blade Holder,

 With Wiha-SoftFinish® Handle. Insulation

 According to VDE, ASTM, EN/IEC, NFPA70E

 & CSA, A up to 1000 Volt. Wiha-SoftFinish®

 handle, multi-component, cushion grip.

 Item
 O == = • • • = •

 No.
 Size mm Inch Ibs. pkg.

2.2

.11 1



1/4" 57

.85	Xeno SL/PZ: #1, #2
	TORX*: T8, T10, T15, T20
	Square: #1, #2
	Hex Metric: 3.0, 4.0, 5.0mm
	SlimLine Stubby Blade Holder

Wiha Insulated Pop-Up SlimLine Sets





Each SlimLine bit can be taken in and out of the holder easily and conveniently







8 Piece Insulated SlimLine Blade 28391 Set High quality CV steel, through hardened. Cushion grip. Friction hold blade holder, holds blades securely. Up to 33% narrower insulation diameter then standard insulated tools. In roll up pouch

in roll up pouc	11
Item No.	Slotted: 4.0, 6.5
28391	Phillips: #1, #2
	Xeno SL/PH: #2
lbs45	TORX*: T15, T20
	28301 - SlimLine Blade Holder



30 Piece Insulated SlimLine Blade 28399 Set High quality CV steel, through hardened. Friction hold blade holder, holds blades securely. In belt wallet storage pouch

securely. I	in beit wallet storage pouch.
Item No.	Slotted: 2.5, 3.0, 3.5, 4.0, 5.5, 6.5mm
28399	Phillips: #1, #2
.	Pozidriv [®] : #1, #2
lbs.	Xeno SL/PH: #1, #2
1.20	Xeno SL/PZ: #1, #2
	TORX *: T8, T9, T10, T15, T20, T25
	Square: #1, #2
	Hex Metric: 1.5, 2.0, 2.5, 3.0,
	4.0, 5.0, 6.0mm
	28301 - SlimLine Blade Holder





28392 12 Piece Insulated SlimLine Blade Set High quality CV steel, through hardened. Cushion grip. Friction hold blade holder, holds blades securely. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. In roll up pouch

Item No.	Slotted: 3.0, 5.5mm
28392	Phillips: #2
<u>.</u>	Xeno SL/PH: #1, #2
lbs.	Square: #1, #2
.52	TORX [®] : T8, T10, T15, T20
	28301 - SlimLine Blade Holder



28390 15 Piece Insulated SlimLine Blade Set High quality CV steel, through hardened. Cushion grip. Friction hold blade holder, holds blades securely. Up to 33% narrower insulation diameter then standard insulated tools. In roll up pouch

	• •
Item No.	Slotted: 3.0, 4.0, 5.5, 6.5
28390	Phillips: #1, #2
	Xeno SL/PH: #1, #2
lbs.	TORX [®] : T8, T10, T15, T20
.56	Square: #1, #2
	28301 - SlimLine Blade Holder

28398 19 Piece Insulated SlimLine Blade Set High quality CV steel, through hardened. Cushion grip. Friction hold blade holder, holds blades securely. In zipper case

Item No.	
28398	Slotted: 3.0, 4.0, 5.5mm
• ` •	Phillips: #1, #2
lbs.	Xeno SL/PH: #1, #2
.64	Xeno SL/PZ: #1, 2
	TORX*: T8, T10, T15, T20
	Square: #1, 2
	Hex Metric: 3.0, 4.0, 5.0mm
	28301 - SlimLine Blade Holder

Wiha Cushion Grip SlimLine Blade Holder



28301 SlimLine Blade Holder, With Wiha-SoftFinish® Handle Insulation According to VDE, ASTM F-1505 and EN/ IEC 60900, NFPA70E & CSA, ☆ up to 1000 Volt. Chrome-vanadium steel, throughhardened. Insulation molded directly onto blade. Friction hold blade holder, holds blades securely. Wiha-SoftFinish® handle,

multi-component, cushion grip.								
ltem	0	 -	—	==	==	• •		
No.	Size	mm	Inch	mm	Inch	lbs.		
28301	1/4"	50	2.0	160	6.3	.15		





\cong 1000Volt

28304 SlimLine Blade Holder, With Wiha-SoftFinish® Handle. Insulation According to VDE, ASTM, EN/IEC, NFPA70E & CSA, \leftrightarrow up to 1000 Volt. Wiha-SoftFinish® handle, multi-component, cushion grip

Item		•			0.
No.	-		Inch		
28304	1/4"	114	4.5	.21	1



28302 SlimLine Stubby Blade Holder, With Wiha-SoftFinish® Handle. Insulation According to VDE, ASTM, EN/IEC, NFPA70E & CSA, \Leftrightarrow up to 1000 Volt. Wiha-SoftFinish® handle, multi-component, cushion grip,

nanale, main compensit, cuemen gript								
Item	0	==	==	•••				
No.	Size	mm	Inch	lbs.	pkg.			
28302	1/4"	57	2.2	.11	1			



Wiha Insulated SlimLine Blades

Integrated Slim Insulation molded directly onto blade

High quality CV steel, throughhardened

not exceed screw head diameter

10,000 Volt Rated

Insulation Test Standards: Insulation according to EN/IEC 60900, ASTM F-1505, VDE 0682/part 201, DIN 7437, NFPA70E & CSA specification

Wiha SlimTECHNOLOGY Achieves blade diameters

up to 33% narrower utilizing integrated insulation



	E plim (20311) 0 294.6 with
283	Insulated Slotted SlimLine Blades
line I in	- blade - base

Insulation does

SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools.

Item	0	0	Slim	Max	Inch/	•••	-
No.	mm	Inch	Dia.	Nm	lbs.	lbs.	Pkg.
28307	2.5	3/32	4.0	0.4	3.5	.02	1
28308	3.0	1/8	4.0	0.6	5.3	.02	1
28310	3.5	9/64	4.0	2.5	22.1	.02	1
28309	4.0	5/32	4.0	2.5	22.1	.02	1
28312	5.5	7/32	6.0	3.8	33.6	.02	1
28315	6.5	1/4	6.0	5.5	48.6	.02	1



SlimLine Blades Up to 33% narrower insulation diameter then standard insulated tools. Slim Max Inch/ Item (\mathbf{R}) No. Dia. lbs. Pkg. Size Nm lbs. 28320 33.6 .02 1 1 4.0 3.8 28321 .02 2 6.0 5.5 48.7 1



283 Insulated Square SlimLine Blades Up to 33% narrower insulation diameter then standard insulated tools.

Item	0	Slim	Max	Inch/	ずず
No.	Size	Dia.	Nm	lbs.	lbs. Pkg.
28346	1	4.0	3.8	33.6	.02 1
28347	2	6.0	5.5	48.7	.02 1

283	Insulated Phillips SlimLine Blades
ዏ	a sime applied that with

SlimLine bl	ades ha	ive up	to 339	% narr	ower			
insulation diameter then standard insulated tools.								
Item	•	Slim	Max	Inch/	÷.			
No.	Size	Dia.	Nm	lbs.	lbs.	Pkg.		
28317	1	4.0	3.8	33.7	.02	1		
28319	2	6.0	5.5	48.8	.02	1		



283 Insulated Xeno Slotted/Phillips SlimLine Blades Up to 33% narrower insulation diameter then standard insulated tools.

Item	Ð	Slim	Max	Inch/	•••	
No.	Size	Dia.	Nm	lbs.	lbs.	Pkg.
28327	1	4.0	3.8	33.6	.02	1
28329	2	6.0	5.5	48.7	.02	1



283 Insulated Hex Metric SlimLine Blades Up to 33% narrower insulation diameter then standard insulated tools

diameter	diameter then standard insulated tools.							
Item		Slim	Мах	Inch/	÷			
No.	Size	Dia.	Nm	lbs.	lbs.	Pkg.		
28332	1.5	4.0	0.9	7.9	.02	1		
28333	2.0	4.0	1.8	15.9	.02	1		
28334	2.5	4.0	3.8	33.6	.02	1		
28335	3.0	4.0	5.5	48.7	.02	1		
28336	4.0	6.0	5.5	48.7	.02	1		
28337	5.0	6.0	5.5	48.7	.02	1		
28338	6.0	6.0	5.5	48.7	.02	1		

283 Insulated Pozidriv[®] SlimLine Blades

the Proster with

SlimLine blades have up to 33% narrower

insulation diameter then standard insulated tools.							
Item	\mathbf{O}	Slim	Max	Inch/	•••		
No.	Size	Dia.	Nm	lbs.	lbs.	Pkg.	
28330	1	4.0	3.8	33.7	.02	1	
28331	2	6.0	5.5	48.8	.02	1	

)			_		_
283	Insulated	TOR	X °Slin	nLine	Blades

Up to 33% narrower insulation diameter then standard insulated tools.

Item	0	Slim	Мах	Inch/		
No.	Size	Dia.	Nm	lbs.	lbs.	Pkg.
28339	T8	4.0	1.3	11.5	.02	1
28344	Т9	4.0	1.3	11.5	.02	1
28340	T10	4.0	3.8	33.6	.02	1
28341	T15	6.0	5.5	48.7	.02	1
28342	T20	6.0	5.5	48.7	.02	1
28343	T25	6.0	5.5	48.7	.02	1



() Toll Free: (800) 494-6104

Insulated PicoFinish Precision Screwdrivers

☆1000Volt

320 Insulated Slotted PicoFinish Screwdrivers. Individually Tested Protective Insulation 1000Volt AC. VDE & GS Tested.

insulation	1 1000	J v Oit <i>i</i>	чc, v		03 1	esieu.
Item	0	0	—	==	•••	
No.	mm	Inch	mm	mm	lbs.	pkg.
32000	1.5	.06	40	154	.05	1
32001	2.0	.08	40	154	.07	1
32002	2.5	.10	60	160	.07	1
32003	3.0	.12	60	160	.08	1
32004	3.5	.14	60	160	.08	1

321 Insulated Phillips PicoFinish Screwdrivers. Individually Tested Protective Insulation 1000Volt AC, VDE & GS Tested.

Item	0	•	—	• ` •	
No.	Size	mm	mm	lbs.	pkg.
32106	00	40	154	.05	1
32107	0	60	160	.07	1
32108	1	60	160	.08	1



	-	
PicoFinish	Set High quality CV steel, thr	ough
hardened,	black finish	• •
Item No.	Slotted: 1.5, 2.0, 2.5, 3.0, 3.5	lbs.
32088	Phillips: #00, #0, #1	.35

Individually Tested Protective Insulation 1000Volt AC, VDE & GS Tested



PicoFinish Set High quality CV steel, through hardened, black finish

Item No.	Slotted: 1.5, 2.5, 3.5	€ • • Ibs.
32085	Phillips: #0, #1	.26

Wiha Insulated SlimLine Screwdrivers



 320
 Insulated Slotted SlimLine

 Screwdrivers Insulation According to

 ASTM F-1505, New VDE Specification

 0682/part 201 and EN/IEC 60900, NFPA70E

 & CSA, ☆ up to 1000 Volt. Individually

 Tested to 10,000Volts. High quality CV

 steel, through hardened. SlimLine blades have

 up to 33% narrower insulation diameter then

 standard insulated tools. Wiha-SoftFinish®

 handle, multi-component, cushion grip.

Item	0	0	Slim	—		÷	
No.	mm	Inch	Dia.	mm	mm	lbs.	Pkg.
32046	3.5	9/64	3.5	100	204	.07	1
32049	4.0	5/32	4.0	100	211	.12	1
32052	4.5	3/16	4.5	125	211	.14	1
32055	5.5	7/32	5.5	125	243	.21	1
32058	6.5	1/4	6.5	150	268	.25	1



Item	•	Slim	=	==	÷	
No.	Size	Dia.	mm	mm	lbs.	Pkg.
32145	1	4.5	80	204	.12	1
32146	2	6.0	100	211	.21	1

Tested to	10,000	Volts.				
Item	\oplus	Slim	 -	==	•••	
No.	Size	Dia.	mm	mm	lbs.	Pkg.
30746	1	4.5	80	191	.12	1
30747	2	6.0	100	218	.21	1



358 Insulated Square SlimLine Drivers Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/ IEC 60900, NFPA70E & CSA, \leftrightarrow up to 1000 Volt. Individually Tested to 10,000Volts. Item Ο Slim ___ _____ No. Size Dia. mm mm lbs. Pka. 35844 1 4.0 100 218 .12 1

4.5

125



2

35845



243

.19

wiha

325Insulated Security TORX® SlimLineDrivers Insulation According to ASTM, NewVDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, ☆ up to 1000Volt. Individually Tested to 10,000Volts.

Item	\odot	—	==	•••		
No.	Size	mm	mm	lbs.	Pkg.	
32512	T10s	100	204	.08	1	
32513	T15s	100	211	.12	1	
32514	T20s	100	211	.12	1	
32515	T25s	125	243	.18	1	
32517	T27s	125	243	.21	1	
32518	T30s	125	243	.21	1	
32519	T40s	150	268	.26	1	





32198 11 Piece Insulated SlimLine Slotted, Phillips, Xeno & Square Screwdrivers. Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, A up to 1000 Volt. Individually Tested to 10,000Volts. High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. Wiha-SoftFinish® handle, multi-component, cushion grip. Item No. Slotted: 3.5, 4.0, 4.5, 5.5, 6.5mm

	, , , , , ,
32198	Phillips: #1, 2
•••	Square: #1, 2
lbs. 1.75	Xeno: #1, 2



32197 8 Piece Insulated SlimLine Slotted, Phillips & Square Screwdrivers. Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/ IEC 60900, NFPA70E & CSA, $\,\, \curvearrowleft \,$ up to 1000 Volt. Individually Tested to 10,000Volts. High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. Wiha-SoftFinish® handle, multicomponent, cushion grip.

Item No.	Slotted: 3.5, 4.0, 4.5, 5.5mm
32197	Phillips: #1, 2
	Square: #1, 2
€	lbs. 1.18



32196 6 Piece Insulated SlimLine Slotted, Phillips & Square Screwdrivers. Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, 🔶 up to 1000 Volt. Individually Tested to 10,000Volts. High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. Wiha-SoftFinish® handle, multicomponent, cushion grip.

Item	‡ () Slotted: 4.5, 6.5mm	••
No.	Phillips: #1, #2	lbs.
32196	O Square: #1, #2	1.15



32596 6 Pc. Insulated SlimLine Security TORX® Screwdrivers. Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, ightarrow up to 1000 Volt. Individually Tested to 10,000Volts. High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. Item No. Security TORX*: T10s, T15s, 32596 T20s, T25s, T27s, T30s ••• lbs. 1.18

Wiha Slim TECHNOLOGY

Achieves blade diameters up to 33% narrower utilizing Wiha integrated insulation





30770 2 Pc. Insulated SlimLine Terminal Block Xeno Slotted/Phillips Screwdrivers. Meets ASTM, VDE, EN/IEC, NFPA70E & CSA Specs, Tested to 10,000Volts. High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. ⊕ Xeno: #1x80mm Item No. 30770 ① Xeno: #2x100mm € • Ibs. .34



32189 2 Pc. Insulated SlimLine Slotted & Phillips Screwdrivers. Meets ASTM, VDE, EN/IEC, NFPA70E & CSA Specs, Individually Tested to 10,000Volts. High quality CV steel, through hardened, SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. Item No. 1 Slotted: 4.5x125mm 32189 **Phillips:** #2x100mm 🖵 lbs. .37



32079 30 Pc. Insulated SlimLine Slotted & Phillips Screwdriver Display. Meets ASTM, VDE, EN/IEC, NFPA70E & CSA Specs, Tested to 10,000Volts. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. High quality CV steel, through hardened. Item 6 of each: No. Slotted: 3.5, 4.5, 5.5mm 32079 Phillips: #1, #2



Wiha Insulated Screwdrivers with SoftFinish[®] Cushion Grip Handle

Insulation Test Standards: Insulation according to EN/IEC 60900, ASTM F-1505, New VDE 0682/part 201, DIN 7437, NFPA70E & CSA

Responds to OSHA's use specification 29 CFR1910 Each tool individually tested to 10,000 Volts & certified to 1000 Volt ac or 1500 Volt dc

SoftFinish® handle Solid molded core with soft outer cushion grip. 40% more torque than conventional handles

Insulation Molded directly onto the blade for permanent bonding

Ì1000V



☆1000Volt



Slotted Screwdriver, With Wiha-SoftFinish® Handle. Insulation According to 320 ASTM F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, \leftrightarrow up to 1000 Volt. Individually Tested.

Blade

CVM tool steel, hardened

to average 58/60RC

	1000 101	. maivi	uualiy re	Sicu.						
Item	₽Φ	‡ ()	‡ ()	 =	—		==	€		
No.	mm	Inch	Inch	mm	Inch	mm	Inch	lbs.	pkg.	
32005	2.0	.078	5/64	60	3.0	164	6.5	.05	10	
32010	2.5	.098	3/32	75	3.0	179	7.1	.06	10	
32012	3.0	.118	1/8	100	4.0	204	8.0	.07	10	
32015	3.5	.139	9/64	100	4.0	204	8.0	.07	10	
32017	4.0	.157	5/32	100	4.0	211	8.3	.12	10	
32023	4.5	.177	3/16	100	4.0	211	8.3	.12	10	
32024	4.5	.177	3/16	125	5.0	236	9.3	.12	10	
32027	4.5	.177	3/16	150	6.0	261	10.2	.14	10	
32025	4.5	.177	3/16	175	7.0	286	11.2	.13	10	
32028	4.5	.177	3/16	200	8.0	311	12.3	.15	10	
32031	5.5	.216	7/32	125	5.0	243	9.5	.15	10	
32026	5.5	.216	7/32	175	7.0	293	11.5	.21	10	
32034	6.0	.236	15/64	150	6.0	268	10.6	.21	10	
32039	6.5	.255	1/4	150	6.0	268	10.6	.21	10	
32042	8.0	.315	5/16	175	7.0	299	11.8	.34	10	
32045	10.0	.393	3/8	200	8.0	318	12.5	.39	10	



UÇ	$ \cong$ 1000Volt
32105	2 Piece Slotted & Phillips Set
Item	\$ () Slotted: 5.5
No.	Phillips: #2
32105	



UQ	☆1000Volt
33532	2 Piece Slotted & Phillips Set
Item	\$ () Slotted: 6.0
No.	Phillips: #2
33532	↓ ↓ lbs50



Phillips Screwdriver, With Wiha-SoftFinish® Handle. Insulation According to ASTM 321 F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, 4 up to 1000 Volt. Individually Tested.

1000 001.	maiviauc	my ica	icu.						
Item	0	—	—			• ` •			
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.		
32100	0	60	2.4	164	6.5	.06	10		
32101	1	80	3.0	191	7.5	.12	10		
32102	2	100	4.0	218	8.6	.20	10		
32103	3	150	6.0	268	10.6	.34	10		
32104	4	200	8.0	318	12.5	.39	10		





Wiha Insulated Screwdriver Sets





1000Volt

☆1000Volt



$\mathbf{0}$

5.9

32192	14 Piece Slot/Phil/Inch Nut
Drivers &	Pliers/Cutters Set
Item No.	Slotted: 3.0, 4.5, 6.5mm
32192	Phillips: 1, 2
↓ ↓	Nut Drivers Inch: 1/4, 5/16,
lbs.	11/32, 3/8, 1/2"
5.5	8.0" Combo Pliers,
	6.3" Diagonal Cutters
	6.3 & 8.0" Long Nose Pliers/Cutters



0 32093 **10 Piece Slotted & Phillips Set**

Item No. Slotted: 2.0, 2.5, 3.0, 3.5, 4.5, 6.5 Phillips: #0, 1, 2, 3 32093 • bs. 1.63

☆1000Volt



32190 15 Piece Slotted, Phillips & Inch Nut Drivers Set Item No. Slotted: 2.0, 2.5, 3.0, 3.5, 4.5, 6.5, 8.0mm 32190 Phillips: #1, 2, 3 <u>ب ب</u> lbs. Nut Drivers Inch: 1/4, 5/16,

3/8, 7/16, 1/2"





32095	19 Piece Slotted, Phillips,
Square, X	eno Screwdriver Set
Insulated	Screwdriver set in a light weight tool
box tray.	
Item No.	Slotted: 2.5, 3.0, 3.5, 4.0, 4.5,
32095	5.5, 6.0, 6.5, 8.0, 10.0mm
	Phillips: #0, #1, #2, #3
•••	Square: #1, #2
lbs.	Xeno Terminal: #1, #2
4.92	Cat. III Voltage Detector -
	(Battery Operated)



Wiha Insulated Hex Metric Screwdrivers

wiha



323 Hex Metric Screwdriver, With Wiha-SoftFinish® Handle

Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, \triangle up to 1000 Volt. Individually Tested Blade high alloy CVM steel, hardened, black finish. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi component auchion arin

muili-compon	ieni, cu	shion y	np.					
Item		—				• •		
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.	
32302	2.5	75	3.0	179	7.0	.06	10	
32303	3.0	75	3.0	179	7.0	.08	10	
32304	4.0	75	3.0	186	7.3	.12	10	
32305	5.0	75	3.0	186	7.3	.15	10	
32306	6.0	100	3.9	218	8.6	.24	10	
32308	8.0	100	3.9	218	8.6	.34	10	

Wiha Insulated **TORX®** Screwdrivers

wiha



325 TORX[®] Screwdriver, With Wiha-SoftFinish[®] Handle

Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E and CSA, riangleq up to 1000 Volt. Individually Tested. Blade high alloy cvm steel, hardened, black finish, Insulation molded directly onto blade.

Item Image: Size Image: Size <thimage: size<="" th=""> <t< th=""></t<></thimage:>
32505 T5 60 2.4 164 6.5 .06 10 32511 T6 60 2.4 164 6.5 .06 10 32516 T7 60 2.4 164 6.5 .06 10 32521 T8 60 2.4 164 6.5 .06 10 32526 T9 60 2.4 164 6.5 .06 10 32531 T10 60 2.4 164 6.5 .06 10
32511 T6 60 2.4 164 6.5 .06 10 32516 T7 60 2.4 164 6.5 .06 10 32521 T8 60 2.4 164 6.5 .06 10 32526 T9 60 2.4 164 6.5 .06 10 32531 T10 60 2.4 164 6.5 .06 10
32516 T7 60 2.4 164 6.5 .06 10 32521 T8 60 2.4 164 6.5 .06 10 32526 T9 60 2.4 164 6.5 .06 10 32531 T10 60 2.4 164 6.5 .06 10
32521 T8 60 2.4 164 6.5 .06 10 32526 T9 60 2.4 164 6.5 .06 10 32531 T10 60 2.4 164 6.5 .06 10
32526 T9 60 2.4 164 6.5 .06 10 32531 T10 60 2.4 164 6.5 .06 10
32531 T10 60 2.4 164 6.5 .06 10
32536 T15 80 3.0 191 7.5 .12 10
32541 T20 80 3.0 191 7.5 .12 10
32546 T25 80 3.0 198 7.8 .17 10
32551 T27 100 4.0 218 8.6 .20 10
32556 T30 100 4.0 218 8.6 .20 10
32561 T40 150 6.0 274 10.8 .30 10
32566 T45 150 6.0 274 10.8 .35 10

Wiha Insulated Square Tip Screwdrivers

☆1000Volt

Square Tip Screwdriver, With 358 Wiha-SoftFinish® Handle Insulation According to ASTM, VDE, EN/IEC, NFPA70E and CSA, A up to 1000 Volt. Individually Tested. Blade high alloy CVM steel, hardened, black finish.

Item	0	— —	 -		==	÷	
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.
35811	1	100	4.0	210	8.2	.12	10
35812	2	150	6.0	268	10.5	.19	10



☆1000Volt



32366	6 Piece Insulated Hex Metric
Screwdriv	er Set
Item No.	
32366	Hex Metric:
	2.5, 3.0, 4.0, 5.0, 6.0, 8.0mm
÷	→ lbs. 1.06



32590	6 Piece TORX [®] Set
Item No.	TORX:
32590	T8, T9, T10, T15, T20, T25
	 Ibs83







Wiha Insulated Pozidriv[®] Screwdrivers

\pm 1000Volt

C

324 Pozidriv[®] Screwdriver, With Wiha SoftFinish[®] Handle. Insulation According to ASTM F-1505, VDE, 0682/part 201, EN/IEC 60900, NFPA70E & CSA specification.

12.2

Individuall	y Tested.							
Item	\bullet	—	—		€			
No.	Size	mm	mm	Inch	lbs.	pkg.		
32400	0	60	164	6.5	.11	10		
32401	1	80	191	7.5	.13	10		
32402	2	100	218	8.6	.23	10		
32403	3	150	267	10.5	.30	5		

Insulated Terminal Block Xeno Screwdrivers



Combination Slotted/Phillips Terminal Block Drivers

Slotted/Phillips or Slotted/Pozidriv®

 \pm 1000Volt

wiha



wiha



307Combination Terminal Block XenoScrewdriver, With Wiha SoftFinish® Handle.Insulation According to ASTM F-1505, VDE,0682/part 201, EN/IEC 60900, NFPA70E &CSA specification. Individually Tested.Blade CVM steel, hardened, black finish.Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushiongrip. For combination Slotted/Phillips headterminal screws.

Item	\oplus	=	==		ず→━━
No.	Size	mm	mm	Inch	lbs. pkg.
30700	1	80	191	7.5	.13 10
30701	2	100	218	8.6	.23 10

Cat. III Voltage Detector -Battery Operated



25500 Battery Operated Voltage Detector Tests 90-1000 Volts. Category III, CE IEC 61010-1 With audible sound and light warnings. Bequires 2 AAA batteries.

Wallingo. Hoganoo E / WWW ballonoo.				
Item	==	==	•••	
No.	mm	Inch	lbs.	pkg.
25500	150	6.0	.13	1

Slotted/Pozidriv®

wiha

307Combination Terminal Block XenoScrewdriver, With Wiha SoftFinish® Handle.Insulation According to ASTM F-1505, VDE,0682/part 201, EN/IEC 60900, NFPA70E &CSA specification. Individually Tested.Blade CVM steel, hardened, black finish.Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushiongrip. For combination Slotted/Pozidriv® headterminal screws.

Item	()	 -	==		
No.	Size	mm	mm	Inch	lbs. pkg.
30711	1	80	191	7.5	.12 10
30712	2	100	218	8.6	.21 10

Insulated Single-Pole Voltage Detector



To DIN 57860/6 And DIN VDE 0680-6, GS Tested. Blade CVM steel, hardened, nickelplated. Insulation molded directly onto blade. Amber LED light. 10,000Volt tested.

s. pkg.
4 1

Wiha Insulated Screwdrivers



A 1000Volt
 32089
 9 Pc. Slotted, Phillips, Square &
 Voltage Detector Set In Molded Carry Case
 Item Slotted: 3.5, 4.0, 4.5, 5.5mm
 No. Phillips: #1, #2
 32089 Xeno Slt/Ph: #2
 Ins. Single Pole Voltage Detector
 ↓ bls. 1.81



32087	7 Pc. Slotted, Phillips, Square &					
Voltage D	Voltage Detector Set					
Item	Slotted: 4.0, 5.5, 6.5mm					
No.	Phillips: #1, #2					
32087	Square: #2					
	Ins. Single Pole Voltage Detector					
	lbs. 1.36					



Toll Free: (800) 494-6104

Wiha Insulated Metric & Inch Nut Drivers

0



 322
 Metric Nut Drivers, With Wiha-SoftFinish® Handle Insulation According to ASTM

 F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, ☆ up to

 1000 Volt. Individually Tested. Blade CVM steel, hardened. Insulation molded directly onto

ł	olade.	Deep drawn	1" socket.	Wiha-Soft	Finish [®] ha	indle, m	ulti-componer	nt.	
	tem	0	—			÷.	-		
	No.	mm	mm	mm	Inch	lbs.	pkg.		
3	2206	4.0	125	236	9.3	.15	10		
3	2209	5.0	125	236	9.3	.16	10		
3	2212	5.5	125	236	9.3	.16	10		
3	2215	6.0	125	236	9.3	.16	10		
3	2218	7.0	125	243	9.6	.25	10		
3	2221	8.0	125	243	9.6	.25	10		
3	2224	9.0	125	243	9.6	.25	10		
3	2227	10.0	125	243	9.6	.27	10		
3	2230	11.0	125	243	9.6	.37	10		
3	2233	12.0	125	243	9.6	.38	10		
3	2236	13.0	125	243	9.6	.39	10		
3	2238	14.0	125	243	9.6	.39	10		
3	2239	15.0	125	243	9.6	.40	10		
3	2240	16.0	125	243	9.6	.42	10		
3	2241	17.0	125	243	9.6	.44	10		

	ź	1000Vol	t
	0411		with
	- Alter		arite •
0	• mpn -	<u> </u>	-

-		
32291	5 Pc. Nut Driver Set - Met	ric Sizes
Item	Metric:	÷÷.
No.	6.0, 7.0, 8.0, 9.0, 10.0mm	lbs.
32291		1.36



322	Inch Nut Driv	vers, Wit	h Wiha-S	oftFinish	I [®] Handl	е	
ltem	0	—		==	• •		
No.	Inch	Inch	mm	Inch	lbs.	pkg.	
32255	5/32	5.0	236	9.3	.15	10	
32258	3/16	5.0	236	9.3	.15	10	
32261	7/32	5.0	236	9.3	.16	10	
32264	1/4	5.0	243	9.6	.24	10	
32267	5/16	5.0	243	9.6	.25	10	
32268	11/32	5.0	242	9.6	.26	10	
32270	3/8	5.0	243	9.6	.26	10	
32273	7/16	5.0	243	9.6	.36	10	
32276	1/2	5.0	243	9.6	.39	10	
32278	9/16	5.0	243	9.6	.39	10	
32280	5/8	5.0	243	9.6	.41	10	



32296	11 Pc. Nut Driver Set - Incl	۱ Sizes
Item	Inch: 5/32, 3/16, 7/32, 1/4,	÷.
No.	5/16, 11/32, 3/8, 7/16,	lbs.
32296	1/2, 9/16, 5/8"	3.00



7/16, 1/2, 9/16, 5/8"

32288

3.16

0	Ô ☆1000Volt					
32292	5 Pc. Nut Driver S	Set - Inch Sizes				
Item	Inch:	€**				
No.	7/32, 1/4, 5/16,	lbs.				
32292	3/8, 1/2"	1.52				

	100000	1000Volt
32294	7 Pc. Nut Driver Set -	Inch Sizes
Item	Inch:	s-s
No.	3/16, 7/32, 1/4, 5/16,	lbs.
32294	3/8, 7/16, 1/2"	2.24

☆1000Volt





38025 Magnetic Bit Holder, 1/4" Wiha Powerhandle & insulated shaft. Holds up to 6 bits. (Holder only) 🖵 lbs. .26

Multi-Bit Screwdrivers

Wiha Insulated Pop-Up Insert Bit Sets



WARNING!

Insulated Tools are intended to provide protection against accidental contact with charged energized circuits. For maximum safety we recommend de-energizing all circuits whenever possible before starting work on electrical apparatus or conductors. Always visually inspect insulation on tools before use, do not use tools if insulation shows signs of wear or damage to the insulated areas of the tool. Wear appropriate eye protection when using hand tools. Use NFPA70E certified insulated protective outer wear when appropriate.

Use & Care Guide For Insulated Tools:

Store tools to minimize risk of damage to insulation, always wear approved eye protection, Inspect insulation prior to each use of any insulated tool. Use insulated tools where the ambient temperature is between -20 to +70° C. Have a qualified safety technician visually inspect insulation on tools annually for safe use.



Toll Free: (800) 494-6104



Cutters Set High quality CV steel, through hardened. Cushion grip handle with magnetic holder to securely hold bits. Pliers & Cutters drop-forged from special tool steel. Industrial Soft grip ergonomically designed handle body. In belt pack pouch

Item No.	Set Includes 1/4" Insert Bits:
32990	Slotted: 4.5, 5.5, 6.0mm • Phillips: #0, 1, 2, 3
•••	Square: #1, 2, 3 • TORX®: T15, T20, T25
lbs.	8.0"/200mm Long Nose Pliers
3.60	8.0"/200mm High Leverage Cutters
	9.5"/245mm Lineman's Pliers



32886 17 Pc. Insulated Pop-Up Bit Holder & Pliers/Cutters Set High quality CV steel, through hardened. Cushion grip handle with magnetic holder to securely hold bits. Pliers & Cutters additionally induction hardened. Hard chrome finish for long lasting corrosion protection. Two component Insulated soft grip handle. In belt pack pouch

Item No.	Set Includes 1/4" Insert Bits:
32886	Slotted: 4.5, 5.5, 6.0mm • Phillips: #0, 1, 2, 3
• ` •	Square: #1, 2, 3 • TORX [®] : T15, T20, T25
lbs.	8.0"/200mm Long Nose Pliers
3.72	8.0"/200mm High Leverage Cutters
	9.5"/245mm Lineman's Pliers





\ge 1000Volt

32873 3 Piece Insulated Pliers/Cutters

In Belt Pack Pouch Tools meet EN/IEC, ASTM, VDE, NFPA70E & CSA standards. Pliers chrome finish for long lasting corrosion protection. Soft grip ergo designed handle body, safety slip guard.

Item No.	Insulated Pliers & Cutters
32873	6.3" / 160mm Diagonal Cutters
	8.0" / 200mm Long Nose Pliers
	8.0" / 200mm Combination Pliers
• •	lbs. 2.12

Wiha Insulated Belt Pack Pouch Sets



1000Volt

328713 Piece Insulated Pliers/Cutters & Multi-Bit Set In BeltPack PouchTools meet EN/IEC, ASTM, VDE, NFPA70E & CSAstandards.Pliers chrome finish for long lasting corrosion protection.Soft grip ergo designed handle body, safety slip guard.Insulatedmulti-bit screwdriver includes Slotted, Phillips & Square bits.

Item No.	Pliers/Cutters & Multi-Bit Set	
32871	6.3" / 160mm Diagonal Cutters	
	8.0" / 200mm Long Nose Pliers	
	Set Includes Bit Holder & The Following Bits:	
	Slotted: 4.5, 6.5mm • Phillips: 1, 2 • Square: 1, 2	
	/ lbs. 1.67	





☆1000Volt

32875 5 Pc. Insulated Pliers/Cutters & SlimLine Screwdrivers In Belt Pack Pouch Tools meet EN/IEC, ASTM, VDE, NFPA70E & CSA standards. Pliers chrome finish for long lasting corrosion protection. Soft grip ergo designed handle body, safety slip guard. Insulated cushion grip drivers, multi-component. Blade CVM tool steel, hardened.

Item No.	Insulated Pliers/Cutters & Screwdrivers	
32875	9.0" / 225mm Lineman's Pliers	
	8.0" / 200mm Long Nose Pliers	
	Insulated SlimLine SoftFinish® Screwdrivers:	
	Slotted: 4.5, 6.5mm • Phillips: 2	
₅⁺₽	lbs. 2.26	



☆1000Volt

328725 Piece Insulated Pliers/Cutters & Screwdrivers In BeltPack PouchTools meet EN/IEC, ASTM, VDE, NFPA70E & CSAstandards.Pliers chrome finish for long lasting corrosion protection.Soft grip ergo designed handle body, safety slip guard.Insulatedcushion grip drivers, multi-component.Blade CVM tool steel, hardened.Item No.Insulated Pliers/Cutters & Screwdrivers328726.3" / 160mm Diagonal Cutters

2872	6.3" / 160mm Diagonal Cutters
	8.0" / 200mm Long Nose Pliers
	Insulated SoftFinish [®] Screwdrivers:
	Slotted: 3.0, 4.5mm • Phillips: 2
÷÷	lbs. 1.77



Wiha Insulated Master Electrician's Tools

Insulation Test Standards: Insulation according to EN/IEC 60900, ASTM F-1505, New VDE 0682/part 201, DIN 7437, NFPA70E & CSA



All Tools In Dedicated Positions **For Quick** Storage & Easy Location Tracking





32800 80 PC. Insulated Master Electrician's Tool Set In Rolling Water Tight Traveling Tool Box - 10,000Volt Tested, 1000Volt Rated

-	-	
Item# 32800	Set Includes:	↓ ↓ lbs. 33.9
6.3" Long Nose Pliers		6.3" Diagonal Cutters
8.0" Long Nose	Pliers	8.0" High Leverage Cutters
6.3" Bent Nose	Pliers	6.3" Cable Cutters
6.3" Long Flat I	Nose Pliers	6.3" Stripping Pliers
9.0" Combo Plie	ers/Crimpers	8.0" Adjustable Wrench
Insulated Inch	Sockets: 1/2, 9/16,	Insulated Slotted: 2.5, 3.0, 3.5,
5/8, 11/16, 3/4,	13/16, 7/8"	4.0, 4.5, 5.5, 6.0, 6.5, 8.0, 10.0mm
Insulated Metric Sockets:		Insulated Phillips: #0, 1, 2, 3
13.0, 14.0, 15.0), 17.0, 19.0,	Insulated Xeno Slotted/Phillips
20.0, 22.0mm		Terminal: #1, 2
Insulated Rate	het 3/8" Drive	Insulated Square: #1, 2
Insulated 4.9"	Extension 3/8" Dr.	Insulated TORX: T6, T7, T8, T9,
Insulated Inch Nut Drivers:		T10, T15, T20, T25, T30
7/32, 1/4, 5/16,	3/8, 7/16"	Insulated L-key: 10mm
Insulated Metric Nut Drivers:		Insulated L-key: 1/2"
5.0, 5.5, 6.0, 7.	0, 8.0,	Insulated Cable Knife: 50mm
10.0, 13.0mm		Insulated Folding Ruler In/MM
Insulated T-handle Inch Hex:		Cat. III Voltage Detector-
5/32, 3/16, 7/32, 1/4, 5/16, 3/8"		Battery Operated
Insulated T-handle Metric Hex:		
4.0, 5.0, 6.0, 8.0mm		

Use & Care Guide For Insulated Tools:

Store tools to minimize risk of damage to insulation, always wear approved eye protection, Inspect insulation prior to each use of any insulated tool. Use insulated tools where the ambient temperature is between -20 to +70° C. Have a qualified safety technician visually inspect insulation on tools annually for safe use.

Wiha Insulated Master Electrician's Tools



32801	112 Pc. Insulated Master Electrician's Tool Set In Rollin	g
Water Tigh	t Traveling Tool Box - 10,000Volt Tested, 1000Volt Rated	ł

Item# 32801 Set Includes:	
6.3" Long Nose Pliers	6.3" Diagonal Cutters
8.0" Long Nose Pliers	8.0" High Leverage Cutters
6.3" Bent Nose Pliers	6.3" Cable Cutters
6.3" Long Flat Nose Pliers	6.3" Stripping Pliers
9.0" Combo Pliers/Crimpers	8.0" Adjustable Wrench
Insulated Inch Sockets: 1/2, 9/16,	Insulated Slotted: 2.5, 3.0, 3.5,
5/8, 11/16, 3/4, 13/16, 7/8"	4.0, 4.5, 5.5, 6.0, 6.5, 8.0, 10.0mm
Insulated Metric Sockets:	Insulated Phillips: #0, 1, 2, 3
13.0, 14.0, 15.0, 17.0, 19.0,	Insulated Xeno Slotted/Phillips
20.0, 22.0mm	Terminal: #1, 2
Insulated Ratchet 3/8" Drive	Insulated Square: #1, 2
Insulated 4.9" Extension 3/8" Dr.	Insulated TORX: T6, T7, T8, T9,
Insulated Inch Nut Drivers:	T10, T15, T20, T25, T30
7/32, 1/4, 5/16, 3/8, 7/16"	Insulated T-handle Inch Hex:
Insulated Metric Nut Drivers:	5/32, 3/16, 7/32, 1/4, 5/16, 3/8"
5.0, 5.5, 6.0, 7.0, 8.0,	Insulated T-handle Metric Hex:
10.0, 13.0mm	4.0, 5.0, 6.0, 8.0mm
Insulated L-key: 10mm	Insulated Inch Deep Offset Ring
Insulated L-key: 1/2"	Wrenches: 1/4, 5/16, 3/8, 7/16,
Insulated Cable Knife: 50mm	1/2, 9/16, 5/8, 11/16, 3/4, 25/32,
Cat. III Voltage Detector-	13/16, 7/8, 15/16, 1, 1-1/16, 1-1/4"
Battery Operated	Insulated Metric Deep Offset
Insulated Folding Ruler In/MM	Ring Wrenches: 8.0, 9.0,
	10.0, 11.0, 12.0, 13.0, 14.0, 15.0,
	17.0, 19.0, 20.0, 22.0, 24.0, 27.0,
	30.0, 32.0mm



Wiha 1000Volt Insulated Tool Sets - Comfort Grip Handles



Master Electrician's Sets



32876 66 Pc. Master Electrician's Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, lpha up to 1000 volt. Individually Tested. Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome/nickel plated mirror-polished

plated, mirror-polished.		
Item# 32876 Set Includes:	↓ ↓ lbs. 21.5	
8.0" Long Nose	6.3" Side Cutters	
6.3" Long Flat Nose	8.0" BiCut SuperCut	
9.0" Combo Pliers/Crimpers	6.3" Stripping Pliers	
8.0" Cable Cutters	8.0" Adjustable Wrench	
Insulated Nut Driver 1/4"	Insulated Slotted 2.0mm	
Insulated Nut Driver 5/16"	Insulated Slotted 2.5mm	
Insulated Nut Driver 11/32"	Insulated Slotted 3.0mm	
Insulated Nut Driver 3/8"	Insulated Slotted 4.0mm	
Insulated Nut Driver 7/16"	Insulated Slotted 4.5mm	
Insulated T-handle Hex 4.0mm	Insulated Slotted 5.5mm	
Insulated T-handle Hex 5.0mm	Insulated Slotted 6.0mm	
Insulated T-handle Hex 6.0mm	Insulated Slotted 8.0mm	
Insulated T-handle Hex 8.0mm	Insulated Slotted 10.0mm	
Insulated T-handle Hex 5/32"	Insulated Phillips #0	
Insulated T-handle Hex 3/16"	Insulated Phillips #1	
Insulated T-handle Hex 7/32"	Insulated Phillips #2	
Insulated T-handle Hex 1/4"	Insulated Phillips #3	
Insulated T-handle Hex 5/16"	Insulated Torx T8	
Insulated T-handle Hex 3/8"	Insulated Torx T10	
Insulated Hex L-key 10.0mm	Insulated Torx T15	
Insulated Hex L-key 1/2"	Insulated Torx T20	
Insulated Socket 1/2"	Insulated Torx T25	
Insulated Socket 9/16"	Insulated Torx T30	
Insulated Socket 5/8"	Insulated Square #1	
Insulated Socket 11/16"	Insulated Square #2	
Insulated Socket 3/4"	Insulated SIt/Ph Terminal #1x80	
Insulated Socket 13/16"	Insulated Slt/Ph Terminal #2x100	
Insulated Socket 7/8"	Insulated Cable Knife 50mm	
Insulated Socket 8.0mm	Insulated Extension 4.9"	
Insulated Socket 10.0mm	Insulated Ratchet 3/8" Driver	
Insulated Socket 13.0mm	Insulated Socket 17.0mm	
Insulated Socket 14.0mm	Insulated Socket 19.0mm	
Insulated Socket 15.0mm	Insulated Socket 22.0mm	



Wiha 1000Volt Insulated Tool Sets - Comfort Grip Handles



32874 50 Piece Insulated Tool Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, ightarrow up to 1000 volt. Individually Tested. Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome/nickel plated, mirror-polished. Cushion Grip Insulated handles. Canvas tool bag.

Item# 32874 Set Includes:	↓ ↓ lbs. 19.8		
6.3" Long Nose Pliers	6.3" Side Cutters		
8.0" Long Nose Pliers	8.0" BiCut SuperCut		
6.3" Combination Pliers	6.3" Stripping Pliers		
9.0" Combo Pliers/Crimpers	8.0" Adjustable Wrench		
10.0" Water Pump Pliers	Battery Operated Voltage Detector		
Slotted: 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.5, 6.0, 6.5, 8.0mm			
Phillips: #0, 1, 2, 3 Square: #1, 2 Slt/Ph Terminal: #1, 2			
TORX: T8, T9, T10, T15, T20, T25, T27, T30			
Hex Inch: 5/32, 3/16, 7/32, 1/4, 5/16, 3/8"			
Nut Driver Inch: 7/32, 1/4, 5/16, 3/8, 7/16, 1/2"			
50mm Cable Stripping Knife & Insulated Inch/Metric Folding Ruler			



32879 25 Pc. Pliers & Screwdriver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, eq up to 1000 volt. Individually Tested.

Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome/nickel plated, mirror-polished. In tool box.

Item# 32879	Set Includes:	↓ ↓ lbs. 11.92
8.0" Long Nose		6.3" Stripping Pliers
9.0" Combinatio	n Pliers	Insulated Inch & Metric Folding Ruler
8.0" BiCut Super	rCut	8.5" Insulated Knife
Slotted: 3.0, 4.5	5, 6.0mm	Phillips: #1, #2
Square: #1, #2		Terminal Block Driver: #1, #2
•	:: 1/4, 5/16, 11/	Terminal Block Driver: #1, #2 /32, 3/8, 7/16, 1/2"
•	, ,	/32, 3/8, 7/16, 1/2"



31 Pc. Pliers & Screwdriver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, A up to 1000 volt. Individually Tested. Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome/nickel plated, mirror-polished. Set includes Insulated Inch & Metric folding ruler.

31 Pc.

Set

Item# 32896 Set Inclu	des: + lbs. 12.85	
6.3" Long Nose Pliers	6.3" Side Cutters	
8.0" Long Nose Pliers	8.0" BiCut SuperCut	
7.0" Linemans Pliers	6.3" Stripping Pliers	
9.0" Combination Pliers	6.3" Round Nose Pliers	
Slotted: 2.0, 2.5, 3.0, 3.5, 4.5, 5.5, 6.5, 8.0, 10.0mm		
Phillips: #0, #1, #2, #3		
Inch Nut Driver: 5/32, 3/16	6, 7/32, 1/4, 5/16, 3/8, 7/16, 1/2, 9/16"	



32878 13 Piece Pliers & Screwdriver Set. In canvas tool bag Set Includeou - Ibo E 16

Item#32878	Set includes: +	+ IDS. 5.16
8.0" Long Nose		50mm Cable Stripping Knife
8.0" BiCut SuperCut		Insulated Slotted: 3.0mm
9.0" Combo Pliers/Crimpers		Insulated Slotted: 4.5mm
Insulated Phillips: #1		Insulated Slotted: 6.0mm
Insulated Phillips: #2		Insulated Square: #1
Insulated Slt/Ph Terminal: #1		Insulated Square: #2
Insulated Slt/Ph Terminal: #2		



Wiha Insulated Pliers with High Visibility Comfort Grip Handle

ightarrow 1000Volt



• Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome and nickel plated, mirror-polished. In zipper carry case

32891	10 Piece Pliers & S	crewdriver Set
Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM		
F-1505, NF	FPA70E & CSA, $igtriangleq$ up	to 1000 volt. Individually Tested.
Item# 328	91 Set Includes:	↓ ↓ lbs. 5.54
8.0" Comb	ination Pliers	8.0" Long Nose
8.0" BiCut	SuperCut	6.3" Cable Cutters
6.3" Universal Wire Stripper		

Insulated Slotted 4.5mm Insulated Slotted 6.5mm



Insulated Phillips #1

Insulated Phillips #2 Insulated Phillips #3

> Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome and nickel plated, mirror-polished. • In zipper carry case

ightarrow 1000Volt

32895 14 Piece Pliers & Screwdriver Set Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, 🛆 up to 1000 volt. Individually Tested. Set Includes: + bs. 6.60 Item# 32895

8.0" Long Nose	6.3" Side Cutters
9.0" Combination Pliers	8.0" BiCut SuperCut
6.3" Stripping Pliers	Insulated Slotted 2.5mm
Insulated Phillips #1	Insulated Slotted 3.0mm
Insulated Phillips #2	Insulated Slotted 3.5mm
Insulated Phillips #3	Insulated Slotted 4.5mm
Insulated Slotted 2.0mm	Insulated Slotted 6.5mm





32888	11 Piece Pliers & Scr	ewdriver Set In Canvas Pouch
Item# 3288	8 Set Includes: 🕁	→ Ibs. 3.58
6.3" Long N	lose	6.3" Side Cutters
8.0" Combination Pliers		6.3" Stripping Pliers
Insulated Slotted 2.5mm		Insulated Phillips #0
Insulated Slotted 3.5mm		Insulated Phillips #1
Insulated Slotted 4.5mm		Insulated Phillips #2
Insulated Slotted 6.0mm		



32892 10 Piece Pliers & Screwdriver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, \bigwedge up to 1000 volt. Individually Tested. Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome and nickel plated, mirror-polished. In canvas tool bag

Item#32892 Set Includes:	 Ibs. 6.64	
8.0" Bent Nose	8.0" Combination Pliers	
6.3" Long Nose	6.3" Side Cutters	
Insulated Phillips #0	Insulated Slotted 3.0mm	
Insulated Phillips #1	Insulated Slotted 4.5mm	
Insulated Phillips #2	Insulated Slotted 6.5mm	



32894	13 Piece Pliers & Scr	ewdriver Set In canvas tool bag
Item# 3289	4 Set Includes: 🖵	→ lbs. 9.5
8.0" Bent N	lose	8.0" Combination Pliers
6.3" Long Nose		6.3" Side Cutters
10" Water Pump Pliers		
Insulated Slotted: 4.5 & 6.5mm		Insulated Nut Driver:
Insulated Phillips: #1 & #2		1/4, 5/16, 3/8, 1/2"



Wiha Insulated Pliers with High Visibility Comfort Grip Handle

• Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome and nickel plated, mirror-polished.



ightarrow 1000Volt

32889 8 Piece Pliers & Cutters Set

Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, 🖄 up to 1000 volt. Individually Tested. Item# 32889 Set Includes: **↓** lbs. 4.63

6.3" Long Nose Pliers	8.0" Long Nose Pliers
6.3" Lineman's Pliers	6.3" Diagonal Cutters
9.0" Lineman's Pliers	8.0" BiCut SuperCut
6.3" Wire Stripping Pliers	Electrician's Knife



ightarrow 1000Volt

32867	10 Piece Pliers & Scre	ewdriver Set In Canvas Pouch
Item#3286	67 Set Includes: 🕁	ulbs. 4.06
6.3" Diagonal Cutters 9.0" Combo Pliers		9.0" Combo Pliers
6.3" Long Nose Pliers		6.3" Wire Strippers
7.0" Crimping Pliers		
Insulated Slotted 4.5mm		Insulated Phillips #1
Insulated Slotted 6.0mm		Insulated Phillips #2
Insulated Square: #2		



\Rightarrow 1000Volt

32869 14 Piece Pliers/Cutters	s & Screwdrivers Set	
Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM		
F-1505, NFPA70E & CSA, $ ightarrow$ up to 1000 volt. Individually Tested.		
Item# 32869 Set Includes:	↓ ↓ lbs. 6.52	
9.0" Lineman's Pliers 8.0" BiCut SuperCut		
8.0" Cable Cutters	8.0" Long Nose Pliers	
6.0" Stripping Pliers 10-20 AWG		
SlimLine Slotted 3.0, 4.5, 6.5mm	SlimLine Phillips #1, 2	
SlimLine Square #1, 2	SlimLine Terminal #2	
Single Pole Tester		



Insulated Phillips #1, 2

0



32899 7 Pc. Pliers & Driver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, \therefore up to 1000 volt. Individually Tested. In molded tool box Item# 32899 Set Includes: + + Ibs. 5.39 9.0" Linemans Pliers 6.3" Long Nose Pliers W/Cutter 6.3" Diagonal Cutter Insulated Phillips #1, 2 Insulated Slotted 3.0, 4.5mm



Insulated Pliers/Cutters & Screwdrivers Sets



 32856
 5 Pc. Insualted Pliers/Cutters & Screwdriver Set

 Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM

 F-1505, NFPA70E & CSA, ☆ up to 1000 volt. Individually Tested.

 Pliers drop forged of high C70 steel. Durable cutting is achieved through additional inductive hardening to approx. 64HRC. Screwdriver blade

 high alloy CVM steel, hardened, black finish. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item No.	Insulated Pliers/Cutters
32856	8.0" Long Nose Pliers
<u>ب ب</u>	6.3" Diagonal Cutters
lbs.	Insulated Slotted & Phillips Drivers
1.81	Slotted: 4.5, 5.5mm
	Phillips: #2



m m m m 1000Volt

 32857
 7 Pc. Insualted Pliers/Cutters & Screwdriver Set

 Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM

 F-1505, NFPA70E & CSA, ☆ up to 1000 volt. Individually Tested.

 Pliers drop forged of high C70 steel. Durable cutting is achieved through additional inductive hardening to approx. 64HRC. Screwdriver blade

 high alloy CVM steel, hardened, black finish. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item No.	Insulated Pliers/Cutters
32857	8.0" BiCut SuperCut Pliers
•••	Insulated Slotted & Phillips Drivers
lbs.	Slotted: 3.5, 4.5, 5.5mm
1.85	Phillips: #0, #1, #2



1000Volt

 32865
 8 Pc. Insualted Pliers/Cutters & SlimLine Blade Set

 Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM

 F-1505, NFPA70E & CSA, ☆ up to 1000 volt. Individually Tested.

 Pliers drop forged of high C70 steel. Durable cutting is achieved through additional inductive hardening to approx. 64HRC. SlimLine blades high alloy CV steel, through hardened. Blades have up to 33% narrower insulation diameter then standard insulated tools.

Item No.	Insulated Pliers/Cutters
32865	8.0" Long Nose Pliers
<u>ب ب</u>	Insulated Slotted & Phillips SlimLine Blades
lbs.	Slotted: 3.0, 4.0, 5.5, 6.5mm
.98	Phillips: #1, #2



$m m \simeq$ 1000Volt

 32858
 7 Pc. Insualted Pliers/Cutters & Screwdriver Set

 Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM

 F-1505, NFPA70E & CSA,
 µp to 1000 volt. Individually Tested.

 Pliers drop forged of high C70 steel. Durable cutting is achieved through additional inductive hardening to approx. 64HRC. Screwdriver blade

 high alloy CVM steel, hardened, black finish. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item No.	Insulated Pliers/Cutters
32858	8.0" Combination Lineman's Pliers
• ` •	Insulated Slotted & Phillips Drivers
lbs.	Slotted: 3.5, 4.5, 5.5mm
1.81	Phillips: #0, #1, #2





 32863
 3 Pc. Insualted Pliers/Cutters & Stripping Pliers Set

 Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM

 F-1505, NFPA70E & CSA, ☆ up to 1000 volt. Individually Tested.

 Pliers drop forged of high C70 steel. Durable cutting is achieved through additional inductive hardening to approx. 64HRC.

Item No.	Insulated Pliers/Cutters & Stripping Pliers
32863	8.0" High Leverage Diagonal Cutters
lbs.	9.0" Lineman's Pliers W/Crimpers
2.21	6.3" Stripping Pliers Strips 0.81-2.59 / AWG #20-#10



 32864
 3 Pc. Insualted Pliers & Cutters Set

 Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM

 F-1505, NFPA70E & CSA,
 µp to 1000 volt. Individually Tested.

 Pliers drop forged of high C70 steel. Durable cutting is achieved through additional inductive hardening to approx. 64HRC.

 Item No.
 Insulated Bliers & Cutters

Item No. Insulated Pliers & Cutters							
	32864	6.3" Diagonal Cutters					
	lbs.	8.0" Long Nose Pliers					
	1.94	8.0" Combination Lineman's Pliers					

	NE Style Lineman's Pliers Set							
Insulated meets AST EN, NF & CSA sta	FPA							
Individually	y Tested							
Knurled s zone on v grip pliers	vinyl							
$lpha$ 1000\	/olt	Extra long cutting edge for flat and round cables						
32833	2 Pc. NE Style Linemar	n's Pliers Set						
Item No.	NE Style Lineman's Plie	ers						
32833	9.5" Insulated & 9.5" Ving	yl Soft Grip - Lineman's Pliers						
•••	, lbs. 2.22							

Cutting capacity up to 3mm

Cutting capacity up to 3mm hardened piano wire

☆1000volt



Double the power at the press of a button BiCut does the job of two pairs of pliers Up to 50% less hand strength required for cutting

Cutting force doubled for extremely hard materials

· Easily switch between two strengths in one-handed operation

 32837
 Insulated BiCut SuperCut. Insulation According to

 VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA,

 △ up to 1000 Volt. Individually Tested. Durable cutting is achieved

 through additional inductive hardening to approx. 64HRC. Drop forged of

 high C70 steel. For cutting various materials from soft to extremely hard,

 such as nails, screws, bolts, wire cables, spring wires, chains, etc.

Item	\leftrightarrow	↔		* *
No.	mm	Inch	Pkg.	lbs.
32837	200	8.0	1	.78





64HRC

cutting edges

32821 Insulated Lineman's Pliers "5-In-1" Professional Design Insulation According to EN/IEC, ASTM, NFPA70E & CSA, \leftrightarrow up to 1000 volt. Individually Tested.

Deep cut radius conduit jaws for non-slip handling. Sure grip knurled & cross hatched flat jaw for non-slip griping. Extra long induction hardened precision matched cutting edges. Lower crimping jaw accepts most standard non-insulated electrical connectors. Large head with square anvil surface on each side. Made from premium CV tool steel forgings. Two component cushion grips for best user comfort.

Item	\leftrightarrow	\leftrightarrow	Cutting Capacity		•••
No.	mm	Inch	Copper AWG	Pkg.	wt.
32821	225	9.0	#4	1	.98

Insulated High Leverage Combination Pliers







32820 High Leverage Combination Pliers. Insulation According to EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, A up to 1000 volt. Individually Tested. DIN ISO 5746

Extra long cutting edge for flat and round cables. Serrated jaws. Cutting edges additionally induction hardened to approx. 64HRC. C70 Special tool steel. Use for gripping, pulling & holding as well as cutting wires and cables ranging in hardness from soft to extremely hard. Two component soft grip ergonomic handles.

Item	\leftrightarrow	\leftrightarrow	Cutting Capacity		•••
No.	mm	Inch	Copper AWG	Pkg.	wt.
32820	225	9.0	#4	1	.86

Insulated NE Style Lineman's Pliers

New dynamic joint provides 40% easier cuts & significantly longer tool life

$rac{1}{1000}$ volt

32831 Insulated NE Style Lineman's Pliers. Insulation According to EN/IEC 60900, ASTM F-1505, NFPA70E and CSA, \Leftrightarrow up to 1000 Volt. Individually Tested. Long life edge is achieved through additional induction hardening to approx. 64HRC. Special C70 tool steel hardened & tempered. Extra long cutting edge for flat and round cables. Two component soft grip ergonomic handles.

Item				•••	
No.	mm	Inch	Pkg.	wt.	
32831	245	9.5	1	1.18	

Insulated Combination Lineman's Pliers



328 Combination Pliers. Insulation According to VDE 0682/ part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, A up to 1000 volt. Individually Tested. DIN ISO 5746 Extra long cutting edge for flat & round cables. Serrated jaws. Cutting edges additionally induction hardened to approx. 64HRC. C70 Special tool steel, Chrome finish. Use for gripping and holding as well as cutting soft and hard wires and cables. Two component soft grip ergonomic handles.

			-		
Item	\leftrightarrow	\rightarrow	Cutting Capacity		↓ • •
No.	mm	Inch	Copper AWG	Pkg.	wt.
32814	160	6.3	#10	1	.53
32816	180	7.0	#9	1	.58
32818	200	8.0	#8	1	.72
52010	200	0.0	#0		.12



32841 Insulated Crimping Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E and CSA, lpha up to 1000 Volt. Individually Tested.

Semi-circular profiles for secure connection between end sleeve and conductor. Long life is achieved through additional induction hardening to 64HRC. C70 special tool steel hardened & tempered.

Item	\leftrightarrow	\leftrightarrow				÷ •
No.	mm	Inch	mm2	AWG	Pkg.	wt.
32841	180	7.0	0.25-2.5	6-30	1	.57




 328
 Diagonal Cutters. Insulation According to VDE 0682/part 201,

 EN/IEC 60900, ASTM F-1505, NFPA70E & CSA,
 µp to 1000 volt.

 Individually Tested. DIN ISO 5749
 Low wear lap joint, riveted and

 able to withstand high levels of load. Lightweight action, clean

 cutting. Long term cutting is achieved through additional inductive

 hardening to approx. 60 HRC. Special tool steel hardened and tempered.

 For soft & medium hard wire. 32832 & 32834 for soft, hard & piano wire.

Item	** *	 Cutting Capacity 		• •	
No.	mm In	ch Copper AWG	Pkg.	wt.	
32830	140 5.	5 #6	1	.47	
32832	160 6.3	3 #6	1	.49	
32834	180 7.0	0 #6	1	.62	

Insulated High Leverage Diagonal Cutters



High Leverage Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, \uparrow up to 1000 volt. Individually Tested. DIN ISO 5749

Semi-circular. Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 64HRC. C70 special tool steel hardened and tempered to high quality. For soft, hard and piano wire, lay-on joint, optimized power transmission.

Item	\leftrightarrow	\checkmark	Cutting Capacity		€ ⁺ €
No.	mm	Inch	Copper AWG	Pkg.	wt.
32835	160	6.3	#6	1	.64
32836	180	7.0	#5	1	.67
32838	200	8.0	#4	1	.80

Insulated Electrician's Diagonal Cutters



1000volt

Item	\leftrightarrow	\leftrightarrow	Cutting Capacity		.
No.	mm	Inch	Copper AWG	Pkg.	wt.
32861	160	6.3	#6	1	.55

Insulated Serrated Edge Cable Cutters



tempered. For cutting of copper & aluminum cables without crushing.								
Item		\leftrightarrow				• ` •		
No.	mm	Inch	Ø	mm2	Pkg.	lbs.		
32826	160	6.3	16	50	1	.42		
32828	200	8.0	20	60	1	.67		

Insulated Stripping Pliers

64HRC cutting edges

G

$riangle 1000 ext{volt}$

32860 Stripping Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E and CSA,

 \triangle up to 1000 volt. Individually Tested. Heavy duty forged, induction hardened cutting edges for even stripping of insulation. Drop-forged from special tool steel, chrome and nickel plated, mirror-polished. Spring and adjusting screw, for stripping up to Ø 5mm/#4 Awg.

Item	\leftrightarrow	\leftrightarrow	Stripping Capacity		+ +
No.	mm	Inch	Copper AWG	Pkg.	wt.
32860	160	6.3	#8 - #28	1	.50



☆1000Volt

 10250
 Insulated Stripping Pliers. Insulation According to

 EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification.

 Individually Tested. Wide long head with ridged gripping surface, shears

 blade and firm wire stripping stations. Wire stripping stations 0.81 / 1.0 /

1.3 / 1.6 / 2.0 / 2.59mm, AWG 20 / 18 / 16 / 14 / 12 / 10.									
Item No.	mm	Inch	Ø	AWG	Pkg.	lbs.			
10250	160	6.3"	0.81-2.59	20-10	1	.26			



Insulated Long Nose Pliers

∑1000volt

328 Long Nose Pliers With Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, lpha up to 1000 volt. Individually Tested. Drop-forged from special tool steel, cutters additionally induction hardened to approx. 64HRC, chrome-nickel plated, mirror-polished.

Item	\leftrightarrow	\leftrightarrow	Cutting Capacity		• ` •
No.	mm	Inch	Copper AWG	Pkg.	wt.
32806	160	6.3	#10	1	.32
32808	200	8.0	#8	1	.42

Insulated Bent Nose Pliers

Angled 40°

1000volt

328 Bent Nose Pliers With Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, lpha up to 1000 volt. Drop-forged from special tool steel, cutters

additionally induction hardened to approx. 64HRC, chrome-nickel plated, mirror-polished. Serrated gripping surface, nose bent 40°.

Item	\leftrightarrow	\leftrightarrow	Cutting Capacity		***
No.	mm	Inch	Copper AWG	Pkg.	wt.
32804	200	8.0	#8	1	.43
32807	160	6.3	#10	1	.32

Insulated Round Nose Pliers



∑1000volt

32870 Round Nose Pliers. Insulation According to VDE 0682/ part 01, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, A up to 1000 volt. Individually Tested. Drop-forged from special tool steel, individually induction hardened, chrome and nickel plated, mirror-polished. Ergonomic comfort grip with slip guard. Serrated jaws.

•	0	01			•
Item	*	→ →→		÷.	
No.	m	im Inch	Pkg.	wt.	
32870	10	6.3	1	.34	

Insulated Long Flat Nose Pliers

∑1000volt

32810 Long Flat Nose Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, ightarrow up to 1000 volt. Individually Tested. DIN ISO 5745 Extra long head. Serrated Jaws are induction hardened. Special CV tool steel forgings, Chrome finish. Two component Soft Grip handles. Use for Gripping and right-angle bending of wires and sheet metal parts

Ose for dripping and hig	gint angit	e benuing of wire		eet metal parts.
Item	\leftrightarrow	\leftrightarrow	-	• • •
No.	mm	Inch	Pkg.	wt.
32810	160	6.3	1	.39

Wiha Canvas Pliers Holster

- · Canvas holster with belt clip and belt loop
- · Security pliers strap

 Screwdr 	iver hold	1						
91256	Pliers	Canvas	Holste	er			8	Ш
Item	Width	Height	•••					
No.	Size	Size	lbs.	pkg.				
91256	3.5 x	6.75	.15	1		6		
							and the second se	



Pen Style Control Cabinet Key



For applications with all common switch cabinets and locking systems





21103	Switch C	Switch Cabinet Keys For applications with all common							
switch cabinets and locking systems. Diecast Zinc									
Item No.	mm	Inch	Pkg.	lbs.					
21103	76	3.0"	1	.22					

Switch Cabinet Key



Wiha Inomic 1000Volt Insulated Pliers





☆1000volt

32850Inomic Combo Pliers. Insulation According to EN/IEC60900, ASTM F-1505, NFPA70E & CSA, Aup to 1000 volt.

Individually Tested. DIN ISO 5749 Precision machined forged head. Induction hardened for longest tool life. Cross hatched flat jaw & deep cut radius jaws for secure gripping of the work piece. Cutting edges are matched for precise cutting action. Award winning ergonomic design with head mounted at 23° angle to grip for reduced user fatigue. Palm side of grip has molded soft panel for added comfort in prolonged use.

Item		$ \rightarrow $	Cutting Capacity		.	
No.	mm	Inch	Copper AWG	Pkg.	lbs.	
32850	180	7.0	#6	1	.46	
32852	Inomic Long No	se Plie	rs			
Item	↔	$ \rightarrow $	Cutting Capacity		• •	
No.	mm	Inch	Copper AWG	Pkg.	lbs.	
32852	160	6.3	#6	1	.43	
32854	Inomic Diagona	I Cutter	s			
Item	↔	\leftrightarrow	Cutting Capacity		• •	
No.	mm	Inch	Copper AWG	Pkg.	lbs.	
32854	160	6.3	#6	1	.41	



91230		anv				
Item	Width		Height	€		
No.	Size		Size	lbs.	pkg.	
91230	4.0	х	4.5	.05	1	

Proturn Insulated Electrician's Shears



32951 Proturn Insulated Electrician's Shears Insulation meets VDE, ASTM F1505, EN/IEC 60900, CSA, NFPA 70E, OSHA Specifications. Made from stainless 420 grade steel

Item				÷+•
No.	mm	Inch	Pkg.	lbs.
32951	160	6.3	1	.22



61630 Insulated Inch & Metric Folding Ruler

10,000Volt Tested/1000Volt Rated. Inch & Metric deep embossed scales. 10 folding sections. 30% fiberglass reinforced polyimide.

No.	Meter	Inch	Sections	Increments	lbs.	pkg.
61630	2	78"	10	1/16 & 1mm	.31	1

Insulated Water Pump Pliers



32954Insulated Industrial Water Pump Pliers. InsulationAccording to VDE, EN/IEC, ASTM, NFPA70E & CSA, a up to1000 Volt. Individually Tested.10 opening settings provides optimaladjustment to objects being gripped. Long life achieved throughadditional induction hardening of jaws to approx.62HRC. Chrome-vanadium tool steel forgings, hardened and tempered. Black finish.

Item	\leftrightarrow	\checkmark	Capac	ities		• ` •	
No.	mm	Inch	Round	Hex	Pkg.	wt.	
32954	250	10.0	1 3/4	2	1	.90	

Rapid & simple push button setting & locking



32956 Insulated Industrial Push Button Water Pump Pliers. Insulation According to VDE, EN/IEC, ASTM, NFPA70E & CSA, Individually Tested. Extra narrow head for working in small spaces. Long life achieved through additional induction hardening of jaws to approx. 62HRC. Finger jam protection for safe operation at all settings. CVM tool steel forgings, hardened & tempered.

	-	-		•			
Item	\leftrightarrow	\leftrightarrow	Capac	ities		.	
No.	mm	Inch	Round	Hex	Pkg.	wt.	
32956	250	10.0	1 3/4	2"	1	.90	



Insulated Industrial Pliers & Cutters

Tools meet ASTM, IEC, VDE, EN, NFPA & CSA standards



Insulated Lineman's Pliers With Crimpers



32917 Insulated Industrial Lineman's Pliers "5-In-1" Professional Design. Insulation According to EN/IEC, ASTM, NFPA70E & CSA, \therefore up to 1000 volt. Individually Tested. Deep cut radius conduit jaws for non-slip handling. Sure grip knurled & cross hatched flat jaw for non-slip griping. Extra long induction hardened precision matched cutting edges. Lower crimping jaw accepts most standard non-insulated electrical connectors. Large head with square anvil surface on each side. Premium CV tool steel forgings.

Item	\leftrightarrow	\leftrightarrow	Cutting Capacity		+ +
No.	mm	Inch	Copper AWG	Pkg.	wt.
32917	225	9.0	#4	1	.98

Insulated Long Nose Pliers With Cutters



1000volt

329 Insulated Industrial Long Nose Pliers With Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, Δ up to 1000 volt. Individually Tested. Drop-forged from special tool steel, cutters additionally induction hardened to approx. 64HRC, half-round jaws, serrated gripping surface.

		,			3
Item	\leftrightarrow	\leftrightarrow	Cutting Capacity		÷.
No.	mm	Inch	Copper AWG	Pkg.	wt.
32926	160	6.3	#10	1	.36
32923	200	8.0	#8	1	.46

Insulated High Leverage Diagonal Cutters



1000volt

32939 Insulated Industrial High Leverage Diagonal Cutters. Insulation According to VDE, EN/IEC, ASTM, NFPA70E & CSA, 1000 volt rated. Individually Tested. DIN ISO 5749 Semi-circular. Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 64HRC. C70 special tool steel hardened and tempered to high quality. For soft, hard and piano wire, lay-on joint, optimized power transmission.

Item	\leftrightarrow		Cutting Capacity		↓ •
No.	mm	Inch	Copper AWG	Pkg.	wt.
32939	200	8.0	#4	1	.66



Insulated NE Style Lineman's Pliers. Insulation According to EN/IEC 60900, ASTM F-1505, NFPA70E and CSA, ightarrow up to 1000 Volt. Individually Tested. Long life edge is achieved through additional induction hardening to approx. 64HRC. Special C70 tool steel hardened & tempered. Extra long cutting edge for flat and round cables.

Item	\leftrightarrow	\leftrightarrow		•••	
No.	mm	Inch	Pkg.	wt.	
32938	245	9.5	1	1.18	



329 Insulated Industrial Diagonal Cutters. Insulation According to VDE, EN/IEC, ASTM, NFPA70E & CSA, 1000Volt Rated. Individually Tested. DIN ISO 5749 Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 64HRC. Special tool steel hardened & tempered. For soft, medium hard wire & piano wire.

Item	\leftrightarrow	\checkmark	Cutting Capacity		• •	
No.	mm	Inch	Copper AWG	Pkg.	wt.	
32933	160	6.3	#6	1	.64	
32929	200	8.0	#6	1	.80	



Insulated Combo Pliers With Dynamic Joint



dynamic 60/40 joint

32930 Insulated Industrial High Leverage Combination Pliers. Insulation According to EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, \wedge up to 1000 volt. Individually Tested. DIN ISO 5746 Extra long cutting edge for flat and round cables. Serrated jaws. Cutting edges additionally induction hardened to approx. 64HRC. Use for gripping, pulling & holding as well as cutting wires and cables ranging in hardness from soft to extremely hard.

Item		\leftrightarrow	Cutting Capacity		• • •	
No.	mm	Inch	Copper AWG	Pkg.	wt.	
32930	200	8.0	#4	1	.92	

Insulated TriCut Strippers & Cutters



32944 Insulated Industrial TriCut Strippers & Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E and CSA, 4 up to 1000 Volt. Individually Tested. Induction hardened cutters & strippers. Cuts cable, strips cable, strips wire leads. Unique 3 in 1 design provides faster combined cutting and stripping. Strips AWG sizes #10 & #14.

Item	\leftrightarrow	\leftrightarrow			€	
No.	mm	Inch	AWG	Pkg.	wt.	
32944	170	6.7	#6	1	.58	

Insulated Heavy Duty Cable Cutters



ightarrow 1000volt

32927 Insulated Industrial Serrated Edge Cable Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E and CSA, \triangle up to 1000 Volt. Individually Tested. Light, clean cutting ground precision cutting edges. Durable cutting is achieved through additional inductive hardening to approx. 64HRC. For cutting of copper & aluminum cables without crushing.

Item	\checkmark	\leftrightarrow				• ` •
No.	mm	Inch	Ø	mm2	Pkg.	lbs.
32927	200	8.0	20	60	1	.78

Insulated Crimpers



riangle1000volt

32945 Insulated Industrial Crimping Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E and CSA, ightarrow up to 1000 Volt. Individually Tested. Semi-circular profiles for secure connection between end sleeve and conductor. Long life is achieved through additional induction hardening to 64HRC. Crimps 6 - 30 AWG Connectors.

Item		↔				↓ ↓
No.	mm	Inch	mm2	AWG	Pkg.	wt.
32945	180	7.0	0.25-2.5	6-30	1	.64

Insulated Stripping Pliers



32947 Insulated Industrial Stripping Pliers. Insulation According to VDE, EN/IEC, ASTM, NFPA70E & CSA, 1000Volt Rated. Individually Tested. DIN ISO 5745 Made from Premium CV tool steel forgings. Induction hardened jaws and cutters to 64HRC. Spring & adjusting screw, for stripping up to Ø 5mm/#4 Awg.

Item	\checkmark	\leftrightarrow	Stripping Capacity		• ` •
No.	mm	Inch	Copper AWG	Pkg.	wt.
32947	160	6.3	#8 - #28	1	.46



Toll Free: (800) 494-6104

Insulated Industrial BiCut SuperCut



Item	\leftrightarrow	\leftrightarrow		↓ •
No.	mm	Inch	Pkg.	lbs.
32936	200	8.0	1	.78

Insulated BiCut SuperCut & Screwdriver Set

Tools meet ASTM, IEC, VDE, EN, NFPA & CSA standards



Phillips: #0, #1, #2

Slotted: 3.0, 4.5, 5.5mm

lbs.

1.86

Wiha Insulated Industrial Tool Sets



329813 Pc. Insulated Industrial Pliers & CuttersItem No.Insulated Pliers & Cutters329818.0° Combo Pliers, 8.0° Long Pliers, 8.0° Diagonal Cutters+++ lbs. 2.18



\pm 1000Volt

 32983
 5 Pc. Insulated Industrial Diagonal Cutters & Screwdrivers

 Item No.
 Insulated Diagonal Cutters & Screwdrivers

 32983
 6.3"/160mm Diagonal Cutter

Insulated Drivers: Slotted: 3.0, 4.5mm • Phillips: #1, #2





Wiha Insulated Industrial Tool Sets



Insulated Pliers/Cutters & Cat. III Voltage Detector 32982 6.3" Long Pliers, 6.3" Diagonal Cutters Voltage Detector with both light and sound alerts **↓ ↓** lbs. .98



32999 9 Piece Insulated Industrial Pliers & Cutters Set

Insulated plie	ers & cutters set in a light w	eight tool box tray.
Item No.	9.0" Lineman's Pliers	8.0" High Lev. Combo Pliers
32999	6.3" Long Nose Pliers	8.0" Cable Cutters
•••	8.0" Long Nose Pliers	6.3" Stripping Pliers
lbs.	6.3" Diagonal Cutters	7.0" Crimping Pliers
6.34	8.0" Diagonal Cutters	



32989 28 Piece Insulated Industrial Pliers & Cutters Set

Insulated p	nsulated pliers & cutters set in a light weight tool box tray.							
Item No.	Set Includes:	•••						
32989	9.0" Lineman's Pliers	lbs.						
	8.0" High Leverage Combo Pliers	6.34						
	6.3" & 8.0" Long Nose Pliers							
	8.0" Cable Cutters							
	6.3" & 8.0" Diagonal Cutters							
	6.3" Stripping Pliers							
	7.0" Crimping Pliers							
	Slotted: 2.5, 3.0, 3.5, 4.0, 4.5, 5.5, 6.0,	6.5, 8.0, 10.0mm						
	Phillips: #0, #1, #2, #3							
	Xeno Slotted/Phillips: #1, #2 & Square:	#1, #2						
	Cat. III Voltage Detector - Battery Oper	ated						

Notes:





Wiha Insulated Industrial Tool Sets





32986 11 Pc. Pliers & Screwdriver Set. Insulation According to VDE 0682/part 201, DIN EN 60900, EN/IEC 60900, ASTM F-1505, NFPA70E, A up to 1000 volt. Individually Tested. In Roll Out Pouch Item# 32986 Set Includes: ••• lbs. 3.62 6.3" Long Nose Pliers 6.3" Diagonal Cutters 8.0" Combination Pliers 6.3" Stripping Pliers Insulated Slotted: 3.0, 4.5, 5.5mm

Insulated Phillips: #1, #2 Insulated Square: #1, #2

In Roll Out Pouch



32987 8 Pc. Pliers & Cutters Set. Insulation According to VDE 0682/part 201, DIN EN 60900, EN/IEC 60900, ASTM F-1505, NFPA70E, A up to 1000 volt. Individually Tested. In Roll Out Pouch Item# 32987 Set Includes: **J** lbs. 5.52 6.3" Diagonal Cutters 6.3" Long Nose Pliers

8.0" Long Nose Pliers	8.0" H.D. Diagonal Cutters
9.0" Lineman's w/Cutters	6.3" Stripping Pliers
8.0" Cable Cutters	7.0" Crimpers



32988 22 Pc. Pliers & Cutters Set. Insulation According to VDE 0682/part 201, DIN EN 60900, EN/IEC 60900, ASTM F-1505, NFPA70E,

rested. In Roll Out Pouches							
Item# 32988 Set Includes	s: 🕞 Ibs. 5.74						
8.0" Long Nose Pliers	6.3" Diagonal Cutters						
9.0" Lineman's w/Cutters	8.0" H.D. Diagonal Cutte	rs					
8.0" Cable Cutters	6.3" Stripping Pliers						
7.0" Crimping Pliers							
15 Pc. SlimLine Blade Set inc	ludes: Insulated SlimLine I	Blade Holder					
Slotted: 3.0, 4.0, 5.5, 6.5	Phillips: #1, #2	Xeno: #1, #2					
TORX®: T8, T10, T15, T20	Square: #1, #2						



32973 22 Pc. Pliers & Driver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, % up to 1000 volt. Individually Tested. In molded tool box Item# 32973 Set Includes: - Ubs. 8.70 9.0" Linemans Pliers W/Cutters 8.0" Long Nose Pliers W/Cutter 8.0" Diagonal Cutters 50mm Cable Stripping Knife Insulated Slim Phillips: #1, 2 Insulated Slim Slotted: 3.5, 4.5mm Insulated Slim Xeno: #1, 2 Insulated Slim Square: #1, 2 Insulated T-handle Hex Inch: 5/32, 3/16, 7/32, 1/4, 5/16, 3/8" Insulated Inch Nut Drivers: 3/8, 7/16, 1/4, 5/16"



☆1000Volt

32390	11 Pc. Pliers & Driv	er Set. Insulation According to VDE						
0682/part	0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA,							
$\stackrel{\frown}{\simeq}$ up to 10	000 volt. Individuall	y Tested. In canvas tool bag						
Item# 323	90 Set Includes:	↓ lbs. 6.30						
8.0" Linem	ans Pliers	6.3" Long Nose Pliers W/Cutter						
8.0" Long	Nose Pliers W/Cutter	6.3" Diagonal Cutter						
8.0" High L	_everage Cutter							
Insulated F	Phillips: #0, 1, 2	Insulated Slotted: 3.0, 4.5, 6.5mm						



igta1000Volt

0

32399 10 Pc. Pliers & Driv	ver Set. Insulation According to VDE					
0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E & CSA,						
igtriangleq up to 1000 volt. Individually Tested. In canvas zipper pouch						
Item# 32399 Set Includes:	:					
8.0" Linemans Pliers 8.0" Long Nose Pliers W/Cutter						
8.0" Diagonal Cutter	6.3" Wire Stripper					
10.0" Adjustable Pliers						
Insulated Phillips: #1, 2	Insulated Slotted: 3.0, 4.5, 6.5mm					





No Hassle Guarantee

Wiha branded tools are regarded as the most durable, best designed and highly innovative products around. Our tools are used by demanding professional tradespeople and tool aficionados alike. They are meant to be used and utilized often. However, if you are not happy for any reason return them within 12 months of purchase with proof of purchase and we will **Repair** or **Replace**.

Rest assured, if for some reason there is a defect in material or workmanship we will replace your tool free of charge for as long as you own the tool.

Failures due to misuse, abuse or normal wear and tear are not covered by this guarantee. We stand by our products with what we believe is the best **No Hassle Guarantee** in the industry.

Exclusions

Wiha Tools has the right to exclude Bits, Tweezers and Ceramic Screwdrivers. These products are either consumable or wear easily.

All torque tools are designed for 5,000 cycles or 1 year (whichever comes first). If a tool becomes out of specification within that period Wiha Tools will **Repair** or **Replace**. Visit <u>www.wihatools.com</u> to learn more about our Torque Control Service Program.

Legal

Some areas do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific rights, and you may also have other rights, which vary, from state to state, province to province, or country to country.

This **No Hassle Guarantee** is the sole and exclusive guarantee for the Willi Hahn Corporation dba Wiha Tools. No employee, agent, dealer, or other person is authorized to alter this guarantee or make any other guarantees on behalf of Wiha Tools.

Willi Hahn Corporation USA Attn: No Hassle Guarantee 1348 Dundas Circle Monticello, MN 55362 800-494-6104

WihQ (M) Toll Free: (800) 494-6104

46 Tools that work for you

Numerical Index by Item Number

Item No.	Page	Item No.	Page	Item No.	Page	Item No.	Page	Item No.	Page
10250	37	20022	4	21094	6	28391	18	31391	9
11950	13	20022	4	21094	6	28392	18	31394	9 10
11960	14	20024	4	21095	6	28392	17	31395	10
		20027	4						
11975	14			21103	38	28394	17	31425	10
11980	14	20032	4	21105	38	28395	17	31428	10
12326	13	20091	4	21208	5	28396	17	31429	10
12327	11	20093	4	21210	5	28398	18	31430	10
12851	10	20131	4	21212	5	28399	18	31431	10
12852	11	20133	4	21213	5	28724	17	31432	10
12853	13	20135	4	21214	5	28726	17	31433	10
12854	10	20136	4	21217	5	28727	17	31434	10
12855	10	20137	4	21219	5	28734	17	31435	10
12856	11	20138	4	21290	5	28736	17	31436	10
12857	11	20140	4	21325	5	28738	17	31437	10
12858	13	20141	4	21327	5	28740	16	31438	10
12859	13	20142	4	21329	5	28741	16	31439	10
13650	8	20142	4	21331	5	28742	16	31450	9
	-				-		-		
13651	8	20145	4	21333	5	28750	16	31460	9
13652	8	20146	4	21335	5	28751	16	31491	11
13653	8	20147	4	21391	5	28752	16	31493	11
13654	8	20148	4	25500	25	28791	16	31495	11
13655	8	20149	4	25511	25	28792	16	31496	11
13656	8	20151	4	28301	18	29006	10	31506	10
13657	8	20154	4	28302	17,18	29009	11	31507	10
13658	8	20190	4	28304	18	29012	13	31508	10
13659	8	20192	4	28307	19	29240	13	31509	10
13662	8	20194	5	28308	19	29250	13	31510	10
13663	8	20196	5	28309	19	30114	16	31511	10
13664	8	21008	6	28310	19	30138	16	31512	10
13665	8	21009	6	28312	19			31512	
			6			30152	16		10
13666	8	21010	-	28315	19	30190	16	31514	10
13667	8	21011	6	28317	19	30192	16	31515	10
13668	8	21012	6	28319	19	30700	25	31516	10
13669	8	21013	6	28320	19	30701	25	31517	10
13670	8	21014	6	28321	19	30711	25	31518	10
13671	8	21015	6	28327	19	30712	25	31519	10
13672	8	21017	6	28329	19	30746	20	31520	10
13673	8	21019	6	28330	19	30747	20	31521	10
13690	8	21020	6	28331	19	30770	21	31522	10
13691	8	21022	6	28332	19	31326	9	31524	10
13693	8	21024	6	28333	19	31327	9	31590	11
13694	8	21027	6	28334	19	31328	9	31592	11
15000	7	21030	6	28335	19	31329	9	31595	11
	7	21032	6	28336	19	31329	9	31608	12
		21032							
15050	7		6	28337	19	31331	9	31609	12
19767	13	21042	6	28338	19	31332	9	31610	12
20006	4	21044	6	28339	19	31333	9	31611	12
20007	4	21046	6	28340	19	31334	9	31612	12
20008	4	21048	6	28341	19	31335	9	31613	12
20009	4	21050	6	28342	19	31336	9	31614	12
20010	4	21052	6	28343	19	31337	9	31615	12
	4	21054	6	28344	19	31338	9	31616	12
	4	21056	6	28346	19	31339	9	31617	12
	4	21057	6	28347	19	31340	9	31618	12
	4	21058	6	28350	17	31341	9	31619	12
20014	4	21050	6	28366	17	31342	9	31620	12
		21060			17				
	4		6	28367		31343	9	31621	12
20017	4	21064	6	28368	17	31344	9	31622	12
		21066	6	28369	17	31345	9	31623	12
20018	4								
20018 20019	4 4 4	21068 21093	6 6	28371 28390	17 18	31350 31390	9	31624 31626	12 12



Item No.	Page	
31627	12	
31628	12	
31630	12	
31632	12	
31650	9	
31691	12	
31694	12	
31703	12	
31704	12	
31705	12	
31707	12	
31708	12	
31709	12	
31710	12	
31712	12	
31713	12	
31714	12	
31715	12	
31716	12	
31718 31720	12	
31720	12 12	
31790	12	
31792	12	
31805	9	
31807	9	
31809	9	
31811	9	
31813	9	
31815	9	
31817	9	
31830	9	
31832	9	
31834	9	
31836	9	
31838	9	
31840	9	
31842	9	
31844	9	
31890	9	
32000	20	
32001	20	
32002	20	
32003	20	
32004	20	
32005	22	
32010	22	
32012	22	
32015	22	
32017	22	
32023	22	
32024 32025	22 22	
32025	22	
32020	22	
32027	22	
32020	22	
32031	22	
32034	22	
32039	22	
32042	22	
02040	22	

Item No.	Page
32046	20
32049	20
32052	20
32055	20
32058	20
32079	21
32085	20
32087	25
32088	20
32089	25
32090	22
32091	23
32092	23
32093	23
32094	23
32095	23
32100	22
32101	22
32102	22
32103	22
32104	22
32105	22
32106	20
32107	20
32108	20
32145	20
32146	20
32188	23
32189	21
32190	23
32192	23
32196	21
32197	21
32198	21
32199	25
32206	26
32209	26
32212	26
32215	26
32218	26
32221	26
32224	26
32227	26
32230	26
32233	26
32236	26
32238	26
32239	26
32240	26
32241	26
32255	26
32258	26
32261	26
32264	26
32267	26
32268	26
32270	26
32273	26
32276	26
32278	26
32280	26

Item No.	Page
32288	26
32291	26
32292	26
32293	26
32294	26
32294	26
32302	24
32303	24
32304	24
32305	24
32306	24
32308	24
32366	24
32390	44
32399	44
32400	25
32401	25
32402	25
32403	25
32505	24
32511	24
32512	20
32513	20
32514	20
32515	20
32516	24
32517	20
32518	20
32519	20
32521	24
32526	24
32531	24
32536	24
32541	24
32546	24
32551	24
32556	24
32561	24
32566	24
32590	24
32592	24
32596	21
32800	29
32801	29
32804	38
32806	38
32807	38
32808	38
32808	38
32814	36
32816	36
32818	36
32820	36
32821	36
32826	37
32828	37
32830	37
32831	36
32832	37
32833	35
32833	37
52034	51

	_			Base
Item No.	-		Item No.	-
32835	37		32985	43
32836	37		32986	44
32837	35		32987	44
32838	37		32988	44
32841	36		32989	43
32850	39		32990	28
32852	39		32999	43
32854	39		33441	15
32856	34		33443	15
32857	34		33445	15
32858	34		33447	15
32860	37		33449	15
32861	37		33478	15
32862	35		33481	15
32863	35		33482	15
32864	35		33483	15
32865	34		33485	15
32867	33		33486	15
32868	33		33487	15
32869	33		33490	15
32870	38		33532	22
32871	28		33632	15
32872	28		33634	15
32873	28		33637	15
32874	31		33641	15
32875	28		35811	24
32876	30		35812	24
32877	30		35844	20
32878	31		35845	20
32879	31		35890	24
32886	28		35891	24
32888	32		38006	27
32889	33		38007	27
32891	32		38025	27
32892	32		38050	27
32894	32		38051	27
32895	32		40800	13
32896	31		61630	39
32899	33		75205	14
32917	40		75210	14
32923	40		75215	14
32926	40		75220	14
32927	41		75302	14
32929	40		75304	14
32930	41		76208	7
32933	40		76210	7
32936	42		76212	7
32938	40		76215	7
32939	40		76290	7
32942	42		91230	39
32944	41		91256	38
32945	41			
32947	41			
32951	39			
32954	39			
32956	39			
32973	44			
32981	42			
32982	43	<u> </u>	Prones M	ARNING: Thi
32983	42	could ex	pose you	to Chrome 6, D
32984	42	Phthalat	es. These	chemicals are

is product DEHP & Phthalates. These chemicals are known to the state of California to cause cancer. For more information go to P65warnings.ca.gov/

MANUFACTURING EXCELLENCE AWARD BESTES KMU 2014

WIHA – WINNER OF THE MX AWARD 2014. GERMANYS BEST SME.





99001.wo - TorqueControl Catalog

99934.wo - Hex Tools Catalog

99006.wo - Tech Tools Catalog 99945.w

99945.wo - ESD Catalog

99977.wo - Pliers/Crimpers Catalog